

Revision Date: 02-Mar-2018

**Revision Number:** 1

1. PRODUCT AND COMPANY IDENTIFICATION

### Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

## INSL-X CABINET COAT SATIN BASE 2 CC-552BF

UF552B Water thinned paint All Paint No information available

## Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 insl-x.ca

### **Manufacturer**

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 insl-x.com Emergency Telephone CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is not considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

## Label elements

## Warning

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Other information

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Titanium dioxide	13463-67-7	7 - 13%
Kaolin	1332-58-7	1 - 5%
Ammonia	7664-41-7	0.1 - 0.25%

4. FIRST AI	D MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.
5. FIRE-FIGHT	ING MEASURES
5. FIRE-FIGHT	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
	Use extinguishing measures that are appropriate to local
Suitable Extinguishing Media Protective Equipment And Precautions For	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)
Suitable Extinguishing Media Protective Equipment And Precautions For Firefighters	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Closed containers may rupture if exposed to fire or
Suitable Extinguishing Media Protective Equipment And Precautions For Firefighters Specific Hazards Arising From The Chemical	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Closed containers may rupture if exposed to fire or extreme heat.
Suitable Extinguishing Media Protective Equipment And Precautions For Firefighters Specific Hazards Arising From The Chemical Sensitivity To Mechanical Impact	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Closed containers may rupture if exposed to fire or extreme heat. No

## Lower Explosion Limit Upper Explosion Limit

#### Not applicable Not applicable

NFPA Health: 1

Flammability: 0

Instability: 0

Special: Not Applicable

#### **NFPA Legend**

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** 

**Other Information** 

**Environmental precautions** 

Methods For Clean-Up

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so.

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Storage

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWAEV
	-	-	3 mg/m <sup>3</sup> - TWA	-	_
Kaolin	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	5 mg/m <sup>3</sup> - TWAEV
Ammonia	25 ppm - TWA	25 ppm - TWA	25 ppm - TWA	25 ppm - TWA	25 ppm - TWAEV
	35 ppm - STEL	17 mg/m <sup>3</sup> - TWA	35 ppm - STEL	35 ppm - STEL	17 mg/m <sup>3</sup> - TWAEV
		35 ppm - STEL			35 ppm - STEV
		24 mg/m <sup>3</sup> - STEL			24 mg/m <sup>3</sup> - STEV

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits N/E - Not established

#### **Engineering Measures**

Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection

**Hygiene Measures** 

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** pН Viscosity (cps) Solubility Water solubility **Evaporation Rate** Vapor Pressure Vapor Density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Flash Point Method Flammability (solid, gas) **Upper Explosion Limit** Lower Explosion Limit Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition Coefficient (n-octanol/water)

liquid little or no odor No information available 9.6 - 9.91.15 - 1.19No information available No information available 35 - 45 25 - 35 55 - 65 65 - 75 < 50 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

## **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

Product Information Information on likely routes of exposure			
Principal Routes of Exposure	Eye contact, skin contact and inhalation.		
Acute Toxicity Product Information	No information available		
Symptoms related to the physical, chemical and toxic	cological characteristics		
Symptoms	No information available		
Delayed and immediate effects as well as chronic effe	ects from short and long-term exposure		
Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.		
Inhalation Ingestion	May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
Sensitization Neurological Effects	No information available.		
Mutagenic Effects	No information available.		
Reproductive Effects	No information available.		
Developmental Effects	No information available.		
Target organ effects	No information available.		
STOT - single exposure	No information available.		
STOT - repeated exposure Other adverse effects	No information available. No information available.		
	No information available.		
Aspiration Hazard			
Numerical measures of toxicity			
The following values are calculated based on chapter 3.1 of the GHS document			
ATEmix (aral)	00120 ma/ka		

ATEmix (oral)	88138 mg/kg
ATEmix (inhalation-dust/mist)	312.9 mg/L

**Component** 

<u>Titanium dioxide</u> LD50 Oral: > 10000 mg/kg (Rat) <u>Kaolin</u> LD50 Oral: > 5000 mg/kg (Rat) <u>Ammonia</u> LC50 Inhalation (Vapor): 2000 ppm (Rat, 4 hr.)

#### Chronic Toxicity

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION** 

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### **Product Information**

#### **Acute Toxicity to Fish**

No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

## Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

### **Bioaccumulation / Accumulation**

No information available.

#### Mobility in Environmental Media

No information available.

#### <u>Ozone</u>

No information available

### **Component**

#### Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

# Acute Toxicity to Aquatic Invertebrates

No information available

### Acute Toxicity to Aquatic Plants

No information available

## **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

TDG

Not regulated

ICAO / IATA

IMDG / IMO

Not regulated

Not regulated

## 15. REGULATORY INFORMATION

## International Inventories

**TSCA: United States**Yes - All components are listed or exempt.**DSL: Canada**Yes - All components are listed or exempt.

## National Pollutant Release Inventory (NPRI)

<u>NPRI Parts 1- 4</u> This product contains the following Parts 1-4 NPRI chemicals:

Chemical name	CAS No.	Weight-%	NPRI Parts 1-4
Ammonia	7664-41-7	0.1 - 0.25%	Listed

#### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION				
HMIS	Health: 1	Flammability: 0	Reactivity: 0	PPE: -
Note: The PPE rati	zard rd rd ırd supervisor or S.O.P.			ployees from the hazards the material will

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	02-Mar-2018
Reason For Revision	Not available

#### **Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable

federal, provincial, and local laws and regulations.

## **END OF SAFETY DATA SHEET**