

Revision Date: 23-Jun-2017 Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name GARAGEGUARD WATERBORNE EPOXY GARAGE FLOOR

COATING NEUTRAL BASE

Product Code EGG-190F

Alternate Product Code XF0941

Product Class WATERBORNE EPOXY

Color All Recommended use Paint

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898

insl-x.ca

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180

insl-x.com

Emergency Telephone Number(s)

CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Danger

Hazard statements

Causes skin irritation

Causes serious eye damage

Suspected of damaging fertility or the unborn child

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure

Revision Date: 23-Jun-2017



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed call a POISON CENTER or physician

Eyes

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or physician

Skin

If on skin wash with plenty of soap and water

If skin irritation occurs get medical attention

Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

Other hazards

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, a small amount of clean sand may be added. Stir often during application.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)	
Aliphatic polyamine	U84660-00-1	10 - 30%	
Talc	14807-96-6	10 - 30%	

Nepheline syenite	37244-96-5	10 - 30%
2-Propoxyethanol	2807-30-9	5 - 10%
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5%
Distillates (petroleum), solvent-refined light	64741-89-5	0.1 - 0.25%
paraffinic		

4. FIRST AID MEASURES

General Advice Immediately call a POISON CENTER or doctor/physician.

Eye Contact Immediate medical attention is required. Immediately flush

with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15

Revision Date: 23-Jun-2017

minutes. Keep eye wide open while rinsing.

Skin Contact Immediate medical attention is required. Wash off

immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before

reuse.

Inhalation Call a physician or Poison Control Center immediately.

Move to fresh air. If not breathing, give artificial respiration.

Ingestion Never give anything by mouth to an unconscious person.

Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical

advice.

Protection Of First-Aiders

Use personal protective equipment.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And Precautions For

Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Not applicable
Not applicable

Flash Point Method Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 2 Flammability: 0 Instability: 0 Special: -

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental PrecautionsSee Section 12 for additional Ecological Information.

Methods For Clean-Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 23-Jun-2017

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Talc	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m ³ - TWA	2 mg/m³ - TWA	3 mg/m ³ - TWAEV
Nepheline syenite	N/E	N/E	N/E	10 mg/m ³ - TWA	N/E
2-Propoxyethanol	N/E	N/E	N/E	25 ppm - TWA	N/E
				110 mg/m ³ - TWA	
				Danger of cutaneous	

monomethyl ether 150 ppm - STEL Skin Skin 150 ppm - STEL Skin 150 ppm - STEL Skin absorption can contribute to overall Substance may be 150 ppm - STEL Skin absorption can contribute to overall exposure. 150 ppm - STEL Skin absorption 150 ppm - STEL Danger of cutaneous absorption absorption Skin absorption can contribute to overall exposure.					absorption	
through intact skin exposure.	, .,	150 ppm - STEL	606 mg/m³ - TWA 150 ppm - STEL 909 mg/m³ - STEL Substance may be readily absorbed	150 ppm - STEL Skin absorption can contribute to overall	150 ppm - STEL Danger of cutaneous	100 ppm - TWAEV 606 mg/m³ - TWAEV 150 ppm - STEV 909 mg/m³ - STEV Skin absorption can contribute to overall

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Revision Date: 23-Jun-2017

Personal Protective Equipment

Eye/Face Protection
Skin Protection

Respiratory Protection

Safety glasses with side-shields.

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

Density (lbs/gal) 10.2 - 10.6 **Specific Gravity** 1.22 - 1.27

pH No information available

Viscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information available

Evaporation Rate

Vapor Pressure

No information available
No information available

Vapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40

 Wt. % Volatiles
 45 - 55

 Vol. % Volatiles
 60 - 70

 VOC Regulatory Limit (g/L)
 < 300</td>

Boiling Point (°F) 212.0
Boiling Point (°C) 100.0

Freezing Point (°F)

Freezing Point (°C)

No information available

No information available

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Flammability (solid, gas)

Upper Explosion Limit

Not applicable

Not applicable

Not applicable

Lower Explosion Limit Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products None under normal use.

Possibility Of Hazardous Reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Causes eye irritation Risk of serious damage to eyes May

cause burns Severely irritating to eyes

Skin contact Irritating to skin. Prolonged skin contact may cause skin

irritation and/or dermatitis. May cause burns.

Inhalation Harmful by inhalation. Causes respiratory tract irritation.

Vapours may be irritating to eyes, nose, throat, and lungs. May cause additional affects as listed under "Ingestion". Harmful if swallowed. Ingestion may cause gastrointestinal

Revision Date: 23-Jun-2017

Ingestion Harmful if swallowed. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. Can burn mouth,

throat, and stomach.

Sensitization:No information available.Neurological EffectsNo information available.Mutagenic EffectsNo information available.

Reproductive Effects Possible risk of impaired fertility. Possible risk of harm to

the unborn child.

Developmental EffectsNo information available.Target Organ EffectsNo information available.

STOT - single exposure May cause disorder and damage to the. Respiratory

system. Digestive System. Blood.

Revision Date: 23-Jun-2017

STOT - repeated exposure Causes damage to organs through prolonged or repeated

exposure if swallowed. Kidney.

Other adverse effectsNo information available.Aspiration HazardNo information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2406 mg/kg
ATEmix (dermal) 11108 mg/kg
ATEmix (inhalation-dust/mist) 7.9 mg/L

Component

2-Propoxyethanol

LD50 Oral: 3089-3090 mg/kg (Rat) LD50 Dermal: 960 µL/kg (Rabbit)

LC50 Inhalation (Vapor): 9060 mg/m³ (Rat) Dipropylene glycol monomethyl ether

LD50 Oral: 5400 µL/kg (Rat) LD50 Dermal: 10 mL/kg (Rabbit)

Distillates (petroleum), solvent-refined light paraffinic

LD50 Oral: > 15 g/kg (Rat) LD50 Dermal: > 5 g/kg (Rabbit)

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 23-Jun-2017

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

Revision Date: 23-Jun-2017

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical NameCAS-NoWeight % (max)NPRI Parts 1- 42-Propoxyethanol2807-30-99.769515-9.77ListedDipropylene glycol monomethyl ether34590-94-81.1533-1.15Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

855-724-6802

Revision Date: 23-Jun-2017
Reason For Revision Not available

Revision Date: 23-Jun-2017

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET