

Revision Date: 23-Jun-2017

**Revision Number:** 1

1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** 

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufactured For Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 insl-x.ca

## **Manufacturer**

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 insl-x.com GARAGEGUARD WATERBORNE EPOXY GARAGE FLOOR COATING SHOWROOM GRAY

EGG-310F XF0910 WATERBORNE EPOXY Gray Paint No information available

Emergency Telephone Number(s)

CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

## Label elements

Danger

Hazard statements Causes skin irritation Causes serious eye damage May cause cancer Suspected of damaging fertility or the unborn child Causes damage to organs Causes damage to organs through prolonged or repeated exposure



Odor little or no odor

## **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/mist/vapors/spray Do not eat, drink or smoke when using this product

## **Precautionary Statements - Response**

Specific treatment (see .? on this label) If exposed call a POISON CENTER or physician Eyes

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or physician

## Skin

If on skin wash with plenty of soap and water If skin irritation occurs get medical attention Take off contaminated clothing and wash before reuse

### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Other information

No information available

### Other hazards

**IMPORTANT:** Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, a small amount of clean sand may be added. Stir often during application.

## 3. COMPOSITION INFORMATION ON COMPONENTS

## EGG-310F - GARAGEGUARD WATERBORNE EPOXY GARAGE FLOOR COATING SHOWROOM GRAY

Chemical Name	CAS-No	Weight % (max)
Talc	14807-96-6	10 - 30%
Titanium dioxide	13463-67-7	10 - 30%
Aliphatic polyamine	U84660-00-1	10 - 30%
2-Propoxyethanol	2807-30-9	7 - 13%
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5%
Silica, crystalline	14808-60-7	0.25 - 0.5%
Carbon black	1333-86-4	0.1 - 0.25%
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	0.1 - 0.25%

4. FIRST AID MEASURES	
General Advice	Immediately call a POISON CENTER or doctor/physician.
Eye Contact	Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
Skin Contact	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before reuse.
Inhalation	Call a physician or Poison Control Center immediately. Move to fresh air. If not breathing, give artificial respiration.
Ingestion	Never give anything by mouth to an unconscious person. Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No

Sensitivity To Static Disch	arge	No	
Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method		Not applicable Not applicable Not applicable	
Flammability Limits In Air			
Lower Explosion Limit Upper Explosion Limit		Not applicable Not applicable	
NFPA Health: 2	Flammability: 0	Instability: 0	Special: Not Applicable
NFPA Legend			

# 0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

## **Personal Precautions**

Other Information

**Environmental Precautions** 

Methods For Clean-Up

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so.

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient

Keep container tightly closed. Keep out of the reach of

ventilation, wear suitable respiratory equipment.

7. HANDLING AND STORAGE

Handling

Storage

Incompatible Materials

No information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

children.

### Exposure Limits

No exposure limits have been established for this product.

## EGG-310F - GARAGEGUARD WATERBORNE EPOXY GARAGE FLOOR COATING SHOWROOM GRAY

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Talc	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWAEV
Titanium dioxide	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV
2-Propoxyethanol	N/E	N/E	N/E	25 ppm - TWA 110 mg/m <sup>3</sup> - TWA Danger of cutaneous absorption	N/E
Dipropylene glycol monomethyl ether	100 ppm - TWA 150 ppm - STEL Skin	100 ppm - TWA 606 mg/m <sup>3</sup> - TWA 150 ppm - STEL 909 mg/m <sup>3</sup> - STEL Substance may be readily absorbed through intact skin	100 ppm - TWA 150 ppm - STEL Skin absorption can contribute to overall exposure.	100 ppm - TWA 150 ppm - STEL Danger of cutaneous absorption	100 ppm - TWAEV 606 mg/m <sup>3</sup> - TWAEV 150 ppm - STEV 909 mg/m <sup>3</sup> - STEV Skin absorption can contribute to overall exposure.
Silica, crystalline	0.025 mg/m <sup>3</sup> - TWA	0.025 mg/m <sup>3</sup> - TWA	0.025 mg/m <sup>3</sup> - TWA	0.10 mg/m <sup>3</sup> - TWA	0.1 mg/m <sup>3</sup> - TWAEV
Carbon black	3 mg/m <sup>3</sup> - TWA	3.5 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWA	3.5 mg/m <sup>3</sup> - TWAEV

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Hygiene Measures** 

### **Engineering Measures**

#### Personal Protective Equipment

Eye/Face Protection Skin Protection Respiratory Protection Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Freezing Point (°F) Freezing Point (°C) Flash Point (°C) Flash Point (°C) Flash Point Method Flammability (solid, gas) Upper Explosion Limit Lower Explosion Limit Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°C) Partition Coefficient (n-octanol/water)
- No information available No information available Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available

## 10. STABILITY AND REACTIVITY

Reactivity	Not Applicable	
Chemical Stability	Stable under normal conditions.	
Conditions To Avoid	Prevent from freezing.	
Incompatible Materials	No materials to be especially mentioned.	
Hazardous Decomposition Products	None under normal use.	
Possibility Of Hazardous Reactions	None under normal conditions of use.	

## **11. TOXICOLOGICAL INFORMATION**

Product Information	
Information on likely routes of exposure	
Principal Routes of Exposure	Eye contact, skin contact and inhalation.
Acute Toxicity	
Product Information	No information available
Information on toxicological effects	
Symptoms	No information available
Delayed and immediate effects as well as	chronic effects from short and long-term exposure
Eye contact	Causes eye irritation Risk of serious damage to eyes May cause burns Severely irritating to eyes
Skin contact	Irritating to skin. Prolonged skin contact may cause skin irritation and/or dermatitis. May cause burns.
Inhalation	Harmful by inhalation. Causes respiratory tract irritation. Vapours may be irritating to eyes, nose, throat, and lungs.
	May cause additional affects as listed under "Ingestion".
Ingestion	Harmful if swallowed. Ingestion may cause gastrointestinal

Sensitization: Neurological Effects Mutagenic Effects Reproductive Effects

Developmental Effects Target Organ Effects STOT - single exposure

**STOT - repeated exposure** 

irritation, nausea, vomiting and diarrhea. Can burn mouth, throat, and stomach. No information available. No information available. No information available. Possible risk of impaired fertility. Possible risk of harm to the unborn child. No information available. No information available. May cause disorder and damage to the. Respiratory system. Digestive System. Blood. Causes damage to organs through prolonged or repeated exposure if inhaled. Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint. Causes damage to organs through prolonged or repeated exposure if swallowed. Kidney. No information available. No information available.

Other adverse effects Aspiration Hazard

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-dust/mist) 2997 mg/kg 10554 mg/kg 10.6 mg/L

## **Component**

Titanium dioxide LD50 Oral: > 10000 mg/kg (Rat) 2-Propoxyethanol LD50 Oral: 3089-3090 mg/kg (Rat) LD50 Dermal: 960 µL/kg (Rabbit) LC50 Inhalation (Vapor): 9060 mg/m<sup>3</sup> (Rat) Dipropylene glycol monomethyl ether LD50 Oral: 5400 µL/kg (Rat) LD50 Dermal: 10 mL/kg (Rabbit) Silica. crystalline LD50 Oral: 500 mg/kg (Rat) Carbon black LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rabbit) Distillates (petroleum), solvent-refined light paraffinic LD50 Oral: > 15 g/kg (Rat) LD50 Dermal: > 5 g/kg (Rabbit)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide		
	1 - Human Carcinogen	Known Human Carcinogen
Silica, crystalline		, i i i i i i i i i i i i i i i i i i i
	2B - Possible Human Carcinogen	
Carbon black		

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

## Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

## Product Information

## Acute Toxicity to Fish

No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

### Acute Toxicity to Aquatic Plants

No information available

### Persistence / Degradability

No information available.

## **Bioaccumulation / Accumulation**

No information available.

### Mobility in Environmental Media

No information available.

### <u>Ozone</u>

No information available

## **Component**

### Acute Toxicity to Fish

#### Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## **14. TRANSPORT INFORMATION**

TDG	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

## National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical Name	CAS-No	Weight % (max)	NPRI Parts 1-4
2-Propoxyethanol	2807-30-9	10.30489-10.30	Listed
Dipropylene glycol monomethyl ether	34590-94-8	1.0136-1.01	Listed


#### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.



Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc	.ac.ca/ewh-semt/c	ontaminants/lead	-plomb/asked	auestions-aues	tions_posees-eng.p	shp.
	.go.oo. o o o		p.o		pooooo og.p	· · · p ·

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 855-724-6802
Revision Date:	23-Jun-2017
Reason For Revision	Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

## END OF SAFETY DATA SHEET