

Revision Date: 03-Oct-2018 Revision Number: 4

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SURE STEP ANTI-SLIP COATING TILE RED

Product Code SU-0505

Alternate Product Code XA1105

Product Class WATER THINNED PAINT

Color Red Recommended use Paint

Restrictions on use No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. CHEMTREC (US): 800-424-9300 101 Paragon Drive CHEMTREC (outside US): (703)-527-3887

Montvale, NJ 07645 Phone: 1-866-708-9180

Pnone: 1-866-708-9180

insl-x.com

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

### Label elements

#### Danger

#### Hazard statements

Harmful if swallowed May cause cancer

Causes damage to organs through prolonged or repeated exposure



Appearance liquid Odor little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product Do not breathe dust/fume/gas/mist/vapors/spray

## **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

## **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

### Other information

No information available

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Silica, crystalline	14808-60-7	35
Glass, oxide	65997-17-3	5
2-Propanol-1-butoxy	5131-66-8	5
Iron oxide	1309-37-1	5
Propylene glycol	57-55-6	5

## 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important None known.

SU-0505 - SURE STEP ANTI-SLIP COATING TILE RED

Symptoms/Effects

Notes To Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And Precautions For As in ar

**Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 03-Oct-2018

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

#### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

### ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

Revision Date: 03-Oct-2018

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL
Silica, crystalline	0.025 mg/m <sup>3</sup> - TWA	-
Glass, oxide	1 fiber/cm3 - TWA 5 mg/m³ - TWA	N/E
Iron oxide	5 mg/m³ - TWA	10 mg/m³ - TWA 15 mg/m³ - TWA Rouge 5 mg/m³ - TWA Rouge

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

**Odor** little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 11.2 - 11.3

 Specific Gravity
 1.34 - 1.36

pH No information available Viscosity (cps) No information available

Viscosity (cps)

Solubility(ies)

Water solubility

Evaporation Rate

Vapor pressure @20 °C (kPa)

No information available
No information available
No information available

Vapor pressure @20 °C (kPa)No information availableVapor densityNo information available

 Wt. % Solids
 50 - 60

 Vol. % Solids
 35 - 45

 Wt. % Volatiles
 40 - 50

 Vol. % Volatiles
 55 - 65

SU-0505 - SURE STEP ANTI-SLIP COATING TILE RED

Revision Date: 03-Oct-2018

 VOC Regulatory Limit (g/L)
 < 250</td>

 Boiling Point (°F)
 212

 Boiling Point (°C)
 100

 Freezing Point (°F)
 32

 Freezing Point (°C)
 0

Flash Point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact** Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SU-0505 - SURE STEP ANTI-SLIP COATING TILE RED

Revision Date: 03-Oct-2018

Sensitization
No information available
Neurological Effects
No information available.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure if inhaled.

Other adverse effects
Aspiration Hazard
No information available.
No information available

#### Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1540 mg/kg ATEmix (dermal) 99059 mg/kg

#### **Component Information**

Silica, crystalline

LD50 Oral: 500 mg/kg (Rat) 2-Propanol-1-butoxy LD50 Oral: 5660 mg/kg (Rat) LD50 Dermal: 3100 mg/kg (Rabbit)

Iron oxide

LD50 Oral: > 5000 mg/kg (Rat) vendor data

Propylene glycol

LD50 Oral: 20000 mg/kg (Rat) LD50 Dermal: 20800 mg/kg (Rabbit)

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	1 - Human Carcinogen	Known Human	Listed
Silica, crystalline		Carcinogen	

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

### 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

#### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

## **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

## **Mobility in Environmental Media**

No information available.

#### Ozone

No information available

### **Component Information**

### **Acute Toxicity to Fish**

No information available

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

### **Acute Toxicity to Aquatic Invertebrates**

No information available

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

## **Acute Toxicity to Aquatic Plants**

No information available

10		L CONSIDERA	TIONIC
IJ.	DIJI UJAI		

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA: United States** Yes - All components are listed or exempt. **DSL: Canada** Yes - All components are listed or exempt.

## Federal Regulations

#### SARA 311/312 hazardous categorization

Acute health hazard Yes Chronic Health Hazard Yes Fire hazard No Sudden release of pressure hazard No Reactive Hazard No

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

## **California Proposition 65**

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

### State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Silica, crystalline	X	X	X
Iron oxide	Х	X	X

#### Legend

X - Listed

## 16. OTHER INFORMATION

HMIS -Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

**HMIS Legend** 

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554

Revision Date: 03-Oct-2018
Revision Summary Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET** 

<sup>\* -</sup> Chronic Hazard