

Revision Date: 11-Feb-2019 Revision Number: 5

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name WATERBORNE SEMI-GLOSS SWIMMING POOL PAINT ROYAL

**BLUE** 

Product Code WR-1024

Alternate Product Code XA0824, XA0840

Product Class WATER THINNED PAINT

ColorBlueRecommended usePaint

Restrictions on use No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. CHEMTREC (US): 800-424-9300 101 Paragon Drive CHEMTREC (outside US): (703)-527-3887

Montvale, NJ 07645 Phone: 1-866-708-9180

insl-x.com

# 2. HAZARDS IDENTIFICATION

# Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Carcinogenicity                                    | Category 1A |
|--|-------------|
| Reproductive toxicity                              | Category 1B |
| Specific target organ toxicity (repeated exposure) | Category 1  |

### Label elements

# Danger

#### Hazard statements

May cause cancer

May damage fertility or the unborn child

Causes damage to organs through prolonged or repeated exposure



Appearance liquid Odor little or no odor

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

## **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

### Other information

No information available

## 3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name   | CAS No.    | Weight-%  |
|---|------------|-----------|
| Silica, crystalline   | 14808-60-7 | 10 - 15   |
| Titanium dioxide  | 13463-67-7 | 5 - 10    |
| 2-Butoxyethanol   | 111-76-2   | 5 - 10    |
| Silica, mica  | 12001-26-2 | 1 - 5     |
| Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol | 25265-77-4 | 1 - 5     |
| 2,2,4-trimethyl-1,3-propanediol diisobutyrate                             | 6846-50-0  | 1 - 5     |
| 1-Methyl-2-pyrrolidinone  | 872-50-4   | 1 - 5     |
| 2-Amino-2-methly-1-propanol   | 124-68-5   | 0.1 - 0.5 |

# 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician

Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Revision Date: 11-Feb-2019

Protective Equipment And Precautions For As in any fire, wear self-contained breathing apparatus

Firefighters pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

**Flash Point Data** 

Flash Point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable

# **NFPA Legend**

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

WR-1024 - WATERBORNE SEMI-GLOSS SWIMMING POOL PAINT ROYAL BLUE

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

Revision Date: 11-Feb-2019

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

| Chemical name       | ACGIH TLV                     | OSHA PEL                          |
|---------------------|-------------------------------|-----------------------------------|
| Silica, crystalline | 0.025 mg/m <sup>3</sup> - TWA | -                                 |
| Titanium dioxide    | 10 mg/m³ - TWA                | 15 mg/m³ - TWA                    |
| 2-Butoxyethanol     | 20 ppm - TWA                  | 50 ppm - TWA                      |
|                     |                               | 240 mg/m <sup>3</sup> - TWA       |
|                     |                               | prevent or reduce skin absorption |
| Silica, mica        | 3 mg/m³ - TWA                 | 20 mppcf - TWA                    |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

**Odor** little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 9.65 - 9.75

 Specific Gravity
 1.16 - 1.18

pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information available

WR-1024 - WATERBORNE SEMI-GLOSS SWIMMING POOL PAINT ROYAL BLUE

Revision Date: 11-Feb-2019

Vapor pressure @20 °C (kPa)No information availableVapor densityNo information available

Wt. % Solids 40 - 50 30 - 40 Vol. % Solids 50 - 60 Wt. % Volatiles 60 - 70 Vol. % Volatiles VOC Regulatory Limit (g/L) < 340 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing Point (°F) 32 Freezing Point (°C) O

Flash Point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

# 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact** Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SensitizationNo information availableNeurological EffectsNo information availableMutagenic EffectsNo information available

**Reproductive Effects** May damage fertility or the unborn child.

Developmental EffectsNo information available.Target organ effectsNo information available.STOT - single exposureNo information available.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure if inhaled.

Other adverse effects
Aspiration Hazard
No information available.
No information available

# Numerical measures of toxicity

# The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2929 mg/kg
ATEmix (dermal) 18499 mg/kg
ATEmix (inhalation-dust/mist) 300.9 mg/L
ATEmix (inhalation-vapor) 194.5 mg/L

#### **Component Information**

| Chemical name   | Oral LD50           | Dermal LD50             | Inhalation LC50      |
|---|---------------------|-------------------------|----------------------|
| Silica, crystalline<br>14808-60-7   | = 500 mg/kg (Rat)   | -                       | -                    |
| Titanium dioxide<br>13463-67-7  | > 10000 mg/kg (Rat) | -                       | -                    |
| 2-Butoxyethanol<br>111-76-2   | = 1300 mg/kg (Rat)  | > 2000 mg/kg ( Rabbit ) | > 4.9 mg/L (Rat) 3H  |
| Propanoic acid, 2-methyl-,<br>monoester with<br>2,2,4-trimethyl-1,3-pentanediol<br>25265-77-4 | = 3200 mg/kg (Rat)  | > 15200 mg/kg (Rat)     | > 3.55 mg/L (Rat)6 h |
| 2,2,4-trimethyl-1,3-propanediol<br>diisobutyrate<br>6846-50-0                                 | > 3200 mg/kg (Rat)  | -                       | -                    |
| 1-Methyl-2-pyrrolidinone<br>872-50-4  | = 3914 mg/kg (Rat)  | = 8 g/kg (Rabbit)       | = 3.1 mg/L (Rat) 4 h |
| 2-Amino-2-methly-1-propanol<br>124-68-5   | = 2900 mg/kg (Rat)  | > 2000 mg/kg ( Rabbit ) | -                    |

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name       | IARC                 | NTP         | OSHA   |
|---------------------|----------------------|-------------|--------|
|                     | 1 - Human Carcinogen | Known Human | Listed |
| Silica, crystalline |                      | Carcinogen  |        |
|                     | 2B - Possible Human  |             | Listed |
| Titanium dioxide    | Carcinogen           |             |        |

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

# Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

#### **Acute Toxicity to Fish**

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

# Persistence / Degradability

No information available.

#### Bioaccumulation

No information available.

### **Mobility in Environmental Media**

No information available.

### **Ozone**

No information available

#### **Component Information**

### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

# **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

environmental protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

# Federal Regulations

#### SARA 311/312 hazardous categorization

Acute health hazard No
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical name            | CAS No.  | Weight-% | CERCLA/SARA 313            |
|--------------------------|----------|----------|----------------------------|
|                          |          |          | (de minimis concentration) |
| 2-Butoxyethanol          | 111-76-2 | 5 - 10   | 1.0                        |
| 1-Methyl-2-pyrrolidinone | 872-50-4 | 1 - 5    | 1.0                        |

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical nameCAS No.Weight-%Hazardous Air Pollutant

<u>(HAP)</u>

Revision Date: 11-Feb-2019

### WR-1024 - WATERBORNE SEMI-GLOSS SWIMMING **POOL PAINT ROYAL BLUE**

Revision Date: 11-Feb-2019

111-76-2 5 - 102-Butoxyethanol Listed

# **US State Regulations**

# **California Proposition 65**



MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

### State Right-to-Know

| Chemical name            | Massachusetts | New Jersey | Pennsylvania |
|--------------------------|---------------|------------|--------------|
| Silica, crystalline      | X             | X          | X            |
| Titanium dioxide         | X             | X          | X            |
| 2-Butoxyethanol          | X             | X          | X            |
| Silica, mica             | X             | X          | X            |
| 1-Methyl-2-pyrrolidinone | X             | X          | X            |

### Legend

X - Listed

# 16. OTHER INFORMATION

HMIS -Health: 2\* Flammability: 0 Reactivity: 0 PPE: -

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By **Product Stewardship Department** 

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 11-Feb-2019 **Revision Summary** Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**