



BLOCK OUT INTERIOR

ALKYD/STYRENE ACRYLATE

PRIMER-SEALER NO-4000

(FORMERLY KNOWN AS ODOUR LESS)

Features

- Use on Smoke Damaged Walls
- Quick Drying
- Blocks most stains

General Description

Block Out Interior Primer is a solvent based, quick drying sealer which is effective over a broad spectrum of stains including many which are difficult to seal with a water based stain suppressor. Block Out Interior Primer can be used over water, tannin, smoke, rust, pencil, ink, nicotine, coffee and most other stains. Block Out Interior Primer can be used on bare or previously painted surfaces. It dries in 30 minutes and can be top-coated in two hours.

Recommended For

Seals stains on interior drywall, plaster or wood prior to repainting with either alkyd or latex paints in any level of sheen. Use to block out water or nicotine stains on acoustical tile. It is also an excellent choice for sealing soot and smoke stains on fire damaged walls. It can be confidently used for maintenance work on occupied premises. This product can be used on exterior masonry surfaces and for spot priming on exterior wood, shingles and composition siding.

Limitations

- Do not apply if the surface, material or ambient temperature is below 7.2 °C (45 °F).
- Do not use as a whole house paint primer on siding.
- Not recommended for use on PVC or CPVC plastics.

Product Information

Colours — Standard:

NO-4000, White

— Tint Bases:

N/A

Can tint up to 2 oz. Universal Colorant

— Special Colours:

Contact your dealer.

Certifications & Qualifications:

The product supported by this data sheet contains a maximum of 350 grams per litre VOC / VOS (2.92 lbs/gal.) excluding water and exempt solvents.

Master Painters Institute MPI # 39, 45 and 136

Technical Assistance:

Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.Insl-x.ca

Technical Data◇

White

Vehicle Type Alkyd/Styrene Acrylic

Pigment Type Titanium Dioxide

Volume Solids 56.9 ± 1.0%

Coverage per 3.79 L at Recommended Film Thickness 30.2 – 39.5 sq. m. (325 – 425 sq. ft.)

Recommended Film Thickness – Wet 3.8 – 5.0 mils
– Dry 2.2 – 2.8 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.

Dry Time @ 25 °C (77 °F) @ 50% RH – Tack Free 30 Minutes
– To Recoat 2 Hours
– To Cure 7 to 10 Days

High humidity and cool temperatures will result in longer dry, recoat and service times.

Dries By Oxidation

Viscosity 85 – 90 KU

Flash Point 39.4 °C (103 °F) or greater (TT-P-141, Method 4293)

Gloss / Sheen Flat

Surface Temperature at Application – Min. 7.2 °C (45 °F)
– Max. 32.2 °C (90 °F)

Thin With Do Not Thin

Clean Up Thinner Mineral Spirits

Weight Per 3.79 L 6 kg (13.3 lbs)

Storage Temperature – Min. 7.2 °C (45 °F)
– Max. 35 °C (95 °F)

Volatile Organic Compounds (VOC)

343 Grams/Litre 2.86 Lbs./Gallon

◇ Reported values are for White. Contact dealer for values of other bases or colours.

BLOCK OUT INTERIOR Alkyd/Styrene Acrylate Primer-Sealer NO-4000

Surface Preparation

The surface to be painted must be clean, dry and free of dirt, wax, grease, rust, mildew, loose and peeling paint and all other contamination. Dirt, wax and chalk should be removed using a detergent solution. Scrub stained area vigorously to remove as much of the stain as possible. Mildew should be removed by washing with a solution of one part household bleach* and three parts water. Rinse well and allow it to dry. Grease and oil should be removed using an Oil and Grease Emulsifier. Loose or peeling paint should be scraped or sanded and any remaining tightly adhering paint should be sanded to a featheredge. Remove sanding dust with a tack rag. Loose wallpaper and any residual paste should be removed by scraping, sanding or using a commercial wallpaper remover.

*Follow bleach manufacturer's instructions for safe handling and use of bleach solution.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Stir product thoroughly before application. Block Out Interior Primer can be applied by brush, roller, pad or spray. When applying by roller, let the texture of the surface determine the depth of nap. When brushing, use either a natural bristle brush or one with a nylon/polyester filament recommended for use with solvent based products. If applying by airless sprayer use a tip size .013 - .015. Do not apply Block Out Interior Primer unless the surface, material and ambient temperatures are 7.2 °C (45 °F) or over. Do not paint if surface temperature is within 5 degrees of the dew point.

NOTE: For best results, apply finish coat within 48 hours.

Clean Up

Clean tools with mineral spirits immediately after use. Clean spills quickly with mineral spirits. Dried material is difficult to remove.

Environmental Health & Safety Information

CAUTION

READ INSTRUCTIONS BEFORE USING

DANGER OF COMBUSTION

Keep away from flames or sparks.

Materials such as rags used with this product may begin to burn by themselves.

After use, put rags in water or lay flat to dry, then discard.

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN

Refer to Safety Data Sheet for additional health and safety information.