

SAFETY DATA SHEET

Revision Date: 25-Feb-2020

Revision Number: 5

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

FLOOR & PATIO LATEX ENAMEL HIGH GLOSS WHITE 12101

12101 Water thinned paint White Paint No information available

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

Emergency Telephone

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Germ cell mutagenicity | Category 1B |
|------------------------|-------------|
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 1B |

Label elements

Danger

Hazard statements

May cause genetic defects Suspected of causing cancer May damage fertility or the unborn child



Appearance liquid

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

Other hazards

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% |
|--|------------|-----------|
| Titanium dioxide | 13463-67-7 | 15 - 20 |
| Sodium C14-C16 olefin sulfonate | 68439-57-6 | 0.1 - 0.5 |
| Sodium nitrite | 7632-00-0 | 0.1 - 0.5 |
| Carbamic acid, 1H-benzimidazol-2-yl-, methyl | 10605-21-7 | 0.1 - 0.5 |
| ester | | |

| 4. FIRST AID MEASURES | | |
|-----------------------|---|--|
| General Advice | If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance. | |
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. | |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. | |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. | |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. | |

Odor little or no odor

| Most Important Symptoms/Effects | None known. | | |
|--|--------------------------|--|--|
| Notes To Physician | Treat symptomatically. | | |
| | 5. FIRE-FIGHT | ING MEASURES | 6 |
| Suitable Extinguishing Media | | | easures that are appropriate to local e surrounding environment. |
| Protective equipment and prec | autions for firefighters | | elf-contained breathing apparatus SHA/NIOSH (approved or equivalent) ar. |
| Specific Hazards Arising From | The Chemical | Closed containers ma extreme heat. | ay rupture if exposed to fire or |
| Sensitivity to mechanical impa | ict | No | |
| Sensitivity to static discharge | | No | |
| Flash Point Data Flash point (°F) Flash Point (°C) Method | | Not applicable Not applicable Not applicable | |
| Flammability Limits In Air | | | |
| Lower flammability limit: Upper flammability limit: | | Not applicable Not applicable | |
| NFPA Health: 2 | Flammability: 0 | Instability: 0 | Special: Not Applicable |
| NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate 3 - High 4 - Severe | | | |

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
|---------------------------|--|
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental precautions | See Section 12 for additional Ecological Information. |
| Methods for Cleaning Up | Soak up with inert absorbent material. Sweep up and shovel into suitable |

containers for disposal.

| | 7. HANDLING AND STORAGE |
|------------------------|--|
| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
| Storage | Keep container tightly closed. Keep out of the reach of children. |
| Incompatible Materials | No information available |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL |
|------------------|---------------------------|----------------|
| Titanium dioxide | TWA: 10 mg/m ³ | 15 mg/m³ - TWA |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

| Engineering Measures | Ensure adequate ventilation, especially in confined areas. |
|---|--|
| Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection | Safety glasses with side-shields. Protective gloves and impervious clothing. Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors. |
| Hygiene Measures | Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance Odor |
|--------------------|
| Odor Threshold |
| Density (Ibs/gal) |
| Specific Gravity |
| рН |
| Viscosity (cps) |
| Solubility(ies) |
| Water solubility |
| Evaporation Rate |
| Vapor pressure |
| Vapor density |

liquid little or no odor No information available 10.1 - 10.5 1.21 - 1.27 No information available No information available

12101 - FLOOR & PATIO LATEX ENAMEL HIGH GLOSS WHITE

| Wt. % Solids Vol. % Solids Wt. % Volatiles | 45 - 55 35 - 45 45 - 55 |
|--|-------------------------------|
| Vol. % Volatiles | 55 - 65 |
| VOC Regulatory Limit (g/L) | < 50 |
| Boiling Point (°F) | 212 |
| Boiling Point (°C) | 100 |
| Freezing point (°F) | 32 |
| Freezing Point (°C) | 0 |
| Flash point (°F) | Not applicable |
| Flash Point (°C) | Not applicable |
| Method | Not applicable |
| Flammability (solid, gas) | Not applicable |
| Upper flammability limit: | Not applicable |
| Lower flammability limit: | Not applicable |
| Autoignition Temperature (°F) | No information available |
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient | No information available |

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No information available

| Eye contact Skin contact | May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. |
|-----------------------------|---|
| Inhalation | May cause irritation of respiratory tract. |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Sensitization | No information available |
| Neurological Effects | No information available. |
| Mutagenic Effects | Suspected of causing genetic defects. |
| Reproductive Effects | May damage fertility or the unborn child. |
| Developmental Effects | No information available. |
| Target organ effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 27127 mg/kg

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-------------------------------------|---------------------|----------------------------------|---------------------|
| Titanium dioxide | > 10000 mg/kg (Rat) | - | - |
| 13463-67-7 | | | |
| Sodium C14-C16 olefin sulfonate | = 2220 mg/kg (Rat) | > 740 mg/kg (Rabbit) | - |
| 68439-57-6 | | | |
| Sodium nitrite | = 85 mg/kg (Rat) | - | = 5.5 mg/L (Rat)4 h |
| 7632-00-0 | | | |
| Carbamic acid, | > 5050 mg/kg (Rat) | > 10000 mg/kg (Rabbit)= 2 g/kg (| - |
| 1H-benzimidazol-2-yl-, methyl ester | = 6400 mg/kg (Rat) | Rat) = 8500 mg/kg (Rabbit) | |
| 10605-21-7 | · · | | |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP | OSHA |
|------------------|---------------------|-----|--------|
| | 2B - Possible Human | | Listed |
| Titanium dioxide | Carcinogen | | |
| | 2A - Probable Human | | Listed |
| Sodium nitrite | Carcinogen | | |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester</u> LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

Acute Toxicity to Aquatic Plants

No information available

| | 13. DISPOSAL CONSIDERATIONS |
|-----------------------|---|
| Waste Disposal Method | Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options. |
| | |

14. TRANSPORT INFORMATION

| DOT | Not regulated |
|-------------|----------------------------|
| ICAO / IATA | Not regulated |
| IMDG / IMO | Not regulated |
| | 15. REGULATORY INFORMATION |

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | No - Not all of the components are listed. |

Federal Regulations

| SARA 311/312 hazardous categorization | |
|---------------------------------------|-----|
| Acute health hazard | No |
| Chronic Health Hazard | Yes |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

| Chemical name | Massachusetts | New Jersey | Pennsylvania |
|---------------------------------------|---------------|------------|--------------|
| Titanium dioxide | Х | X | Х |
| Silica amorphous | Х | | Х |
| Sodium nitrite | Х | X | Х |
| Carbamic acid, 1H-benzimidazol-2-yl-, | | X | |

methyl ester

Legend

X - Listed

16. OTHER INFORMATION HMIS Health: 2* Flammability: 0 Reactivity: 0 PPE: HMIS Legend 0 - Minimal Hazard 1 - Slight Hazard 2 - Moderate Hazard 2 - Moderate Hazard 3 - Serious Hazard 1 - Slight Hazard

- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Prepared By | Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554 |
|------------------|---|
| Revision Date: | 25-Feb-2020 |
| Revision Summary | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet