

Revision Date: 13-Feb-2022 Revision Number: 6

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name FLOOR & PATIO LATEX ENAMEL HIGH GLOSS LIGHT GRAY

Product Code 12170
Alternate Product Code 12170

Product Class Water thinned paint

**Color** Gray Recommended use Paint

Restrictions on use No information available

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180

www.benjaminmoore.com

**Emergency Telephone** 

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

# 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Serious eye damage/eye irritation | Category 2A |
|-----------------------------------|-------------|
| Germ cell mutagenicity            | Category 1B |
| Carcinogenicity                   | Category 2  |
| Reproductive toxicity             | Category 1B |

### Label elements

### Danger

### Hazard statements

Causes serious eye irritation May cause genetic defects Suspected of causing cancer May damage fertility or the unborn child



Appearance liquid Odor little or no odor

### **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

#### Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

### **Precautionary Statements - Storage**

Store locked up

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

### Other information

No information available

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

# 3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name                   | CAS No.    | Weight-%  |
|---------------------------------|------------|-----------|
| Titanium dioxide                | 13463-67-7 | 10 - 15   |
| Ethoxylated octylphenol         | 9036-19-5  | 1 - 5     |
| Sodium C14-C16 olefin sulfonate | 68439-57-6 | 0.1 - 0.5 |
| Carbon black                    | 1333-86-4  | 0.1 - 0.5 |
| Sodium nitrite                  | 7632-00-0  | 0.1 - 0.5 |

# 12170 - FLOOR & PATIO LATEX ENAMEL HIGH GLOSS LIGHT GRAY

| Carbamic acid, 1H-benzimidazol-2-yl-, methyl | 10605-21-7 | 0.1 - 0.5 |
|--|------------|-----------|
| ester  |            |           |

### 4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective equipment and precautions for firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 13-Feb-2022

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable

### NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure Limits**

| Chemical name    | ACGIH TLV                          | OSHA PEL        |
|------------------|------------------------------------|-----------------|
| Titanium dioxide | TWA: 10 mg/m <sup>3</sup>          | 15 mg/m³ - TWA  |
| Carbon black     | TWA: 3 mg/m³ inhalable particulate | 3.5 mg/m³ - TWA |
|                  | matter                             |                 |

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection**Use only with adequate ventilation. In operations where exposure limits are

exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator

Revision Date: 13-Feb-2022

specified for paint spray or organic vapors.

**Hygiene Measures** 

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

liquid **Appearance** 

Odor little or no odor

**Odor Threshold** No information available

9.5 - 9.9Density (lbs/gal) 1.13 - 1.19 **Specific Gravity** 

No information available Hq

Viscosity (cps) No information available Solubility(ies) No information available Water solubility No information available **Evaporation Rate** No information available Vapor pressure No information available

Vapor density No information available Wt. % Solids 45 - 55 Vol. % Solids 35 - 45 Wt. % Volatiles 45 - 55 55 - 65 Vol. % Volatiles < 50

VOC Regulatory Limit (g/L) **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C)

Not applicable Flash point (°F) Flash Point (°C) Not applicable Method Not applicable Flammability (solid, gas) Not applicable **Upper flammability limit:** Not applicable Lower flammability limit: Not applicable

**Autoignition Temperature (°F)** No information available **Autoignition Temperature (°C)** No information available **Decomposition Temperature (°F)** No information available **Decomposition Temperature (°C)** No information available Partition coefficient No information available

# 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

**Chemical Stability** Stable under normal conditions.

Conditions to avoid Prevent from freezing.

**Incompatible Materials** No materials to be especially mentioned.

Hazardous Decomposition Products None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

### **Product Information**

### Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact**Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Sensitization**No information available
Neurological Effects
No information available.

Mutagenic EffectsSuspected of causing genetic defects.Reproductive EffectsMay damage fertility or the unborn child.

Developmental Effects
Target organ effects
STOT - single exposure
STOT - repeated exposure
Other adverse effects
Aspiration Hazard
No information available.
No information available.
No information available.
No information available.

### Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 16712 mg/kg

### **Component Information**

| Chemical name                                 | Oral LD50            | Dermal LD50          | Inhalation LC50    |
|---|----------------------|----------------------|--------------------|
| Titanium dioxide                              | > 10000 mg/kg (Rat)  | -                    | -                  |
| 13463-67-7                                    |                      |                      |                    |
| Ethoxylated octylphenol                       | = 1700 mg/kg (Rat)   | -                    | -                  |
| 9036-19-5                                     | = 4190 mg/kg ( Rat ) |                      |                    |
| Sodium C14-C16 olefin sulfonate<br>68439-57-6 | = 2220 mg/kg (Rat)   | > 740 mg/kg (Rabbit) | > 52 mg/L (Rat)4 h |
| Carbon black                                  | > 15400 mg/kg (Rat)  | > 3 g/kg (Rabbit)    | -                  |

# 12170 - FLOOR & PATIO LATEX ENAMEL HIGH GLOSS LIGHT GRAY

Revision Date: 13-Feb-2022

| 1333-86-4                           |                    |                        |                      |
|-------------------------------------|--------------------|------------------------|----------------------|
| Sodium nitrite                      | = 85 mg/kg (Rat)   | -                      | = 5.5 mg/L (Rat) 4 h |
| 7632-00-0                           |                    |                        |                      |
| Carbamic acid,                      | > 5050 mg/kg (Rat) | > 10000 mg/kg (Rabbit) | -                    |
| 1H-benzimidazol-2-yl-, methyl ester |                    |                        |                      |
| 10605-21-7                          |                    |                        |                      |

### **Chronic Toxicity**

# Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name    | IARC                | NTP | OSHA   |
|------------------|---------------------|-----|--------|
|                  | 2B - Possible Human |     | Listed |
| Titanium dioxide | Carcinogen          |     |        |
|                  | 2B - Possible Human |     | Listed |
| Carbon black     | Carcinogen          |     |        |
|                  | 2A - Probable Human |     | Listed |
| Sodium nitrite   | Carcinogen          |     |        |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

### **Acute Toxicity to Fish**

No information available

# **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

### Persistence / Degradability

No information available.

### **Bioaccumulation**

There is no data for this product.

# **Mobility in Environmental Media**

No information available.

### **Ozone**

No information available

# **Component Information**

### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

# **Acute Toxicity to Aquatic Invertebrates**

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

# **Acute Toxicity to Aquatic Plants**

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 13-Feb-2022

environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

# 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.

No - Not all of the components are listed.

One or more component is listed on NDSL.

# Federal Regulations

### SARA 311/312 hazardous categorization

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No

# 12170 - FLOOR & PATIO LATEX ENAMEL HIGH GLOSS LIGHT GRAY

Reactive Hazard

No

Revision Date: 13-Feb-2022

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

### **California Proposition 65**

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### State Right-to-Know

| Chemical name                         | Massachusetts | New Jersey | Pennsylvania |
|---------------------------------------|---------------|------------|--------------|
| Titanium dioxide                      | Χ             | X          | X            |
| Carbon black                          | Χ             | X          | X            |
| Sodium nitrite                        | Χ             | X          | X            |
| Carbamic acid, 1H-benzimidazol-2-yl-, |               | X          |              |
| methyl ester                          |               |            |              |

### Legend

X - Listed

### 16. OTHER INFORMATION

HMIS - Health: 2\* Flammability: 0 Reactivity: 0 PPE: -

# **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 13-Feb-2022 Revision Summary Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**