

SAFETY DATA SHEET

Revision Date: 10-Jul-2018

Revision Number: 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

FLOOR & PATIO LATEX ENAMEL HIGH GLOSS DECK GRAY 12171

12171 WATER THINNED PAINT Gray Paint No information available

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

Emergency Telephone

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Carcinogenicity Category 2 | | |
|----------------------------|-----------------|------------|
| | Carcinogenicity | Category 2 |

Label elements

| Warning | |
|--|------------------------|
| Hazard statements Suspected of causing cancer | |
| | |
| Appearance liquid | Odor little or no odor |

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

Other hazards

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% |
|--|------------|----------|
| Titanium dioxide | 13463-67-7 | 15 |
| Ethoxylated octylphenol | 9036-19-5 | 5 |
| Carbon black | 1333-86-4 | 0.5 |
| Sodium C14-C16 olefin sulfonate | 68439-57-6 | 0.5 |
| Sodium nitrite | 7632-00-0 | 0.5 |
| Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl- | 330-54-1 | 0.5 |

| 4. FIRST AID MEASURES | | |
|------------------------------------|---|--|
| General Advice | No hazards which require special first aid measures. | |
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. | |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. | |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. | |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. | |
| Most Important Symptoms/Effects | None known. | |

| Notes To Physician Treat symptomatically | <i>י</i> . |
|--|--|
| 5. FIRE-FIGHT | ING MEASURES |
| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity To Mechanical Impact | No |
| Sensitivity To Static Discharge | No |
| Flash Point Data Flash Point (°F) Flash Point (°C) Method | Not applicable Not applicable Not applicable |
| Flammability Limits In Air | |
| Lower flammability limit: Upper flammability limit: | Not applicable Not applicable |
| NFPA Health: 1 Flammability: 0 | Instability: 0 Special: Not Applicable |
| NFPA Legend 0 - Not Hazardous 1 - Slightly | |

- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
|---------------------------|---|
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental precautions | See Section 12 for additional Ecological Information. |
| Methods for Cleaning Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |

7. HANDLING AND STORAGE

| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
|------------------------|--|
| Storage | Keep container tightly closed. Keep out of the reach of children. |
| Incompatible Materials | No information available |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL |
|--|----------------|-----------------|
| Titanium dioxide | 10 mg/m³ - TWA | 15 mg/m³ - TWA |
| Carbon black | 3 mg/m³ - TWA | 3.5 mg/m³ - TWA |
| Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl- | 10 mg/m³ - TWA | N/E |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

| Engineering Measures | Ensure adequate ventilation, especially in confined areas. |
|----------------------|--|
|----------------------|--|

Personal Protective Equipment

| Eye/Face Protection | Safety glasses with side-shields. |
|------------------------|--|
| Skin Protection | Protective gloves and impervious clothing. |
| Respiratory Protection | In case of insufficient ventilation wear suitable respiratory equipment. |
| Hygiene Measures | Avoid contact with skin, eyes and clothing. Remove and wash contaminated |

9. PHYSICAL AND CHEMICAL PROPERTIES

clothing before re-use. Wash thoroughly after handling.

| Water solubilityNo information availableEvaporation RateNo information availableVapor pressure @20 °C (kPa)No information availableVapor densityNo information availableWt. % Solids45 - 55Vol. % Solids35 - 45Wt. % Volatiles45 - 55Vol. % Volatiles55 - 65VOC Regulatory Limit (g/L)< 50 | Evaporation Rate Vapor pressure @20 °C (kPa) Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) | No information available No information available No information available 45 - 55 35 - 45 45 - 55 55 - 65 < 50 |
|--|--|--|
|--|--|--|

12171 - FLOOR & PATIO LATEX ENAMEL HIGH GLOSS DECK GRAY

Boiling Point (°C) Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°C) Partition coefficient Revision Date: 10-Jul-2018

100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

| Product Information | | |
|--|--|--|
| Information on likely routes of | exposure | |
| Principal Routes of Exposure | Eye contact, skin contact and inhalation. | |
| Acute Toxicity | | |
| Product Information | No information available | |
| Symptoms related to the physical, chemical and toxicological characteristics | | |
| Symptoms | No information available | |
| Delayed and immediate effects | as well as chronic effects from short and long-term exposure | |
| Eye contact Skin contact Inhalation Ingestion Sensitization | May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. No information available | |
| Sensitization | | |

| Neurological Effects Mutagenic Effects | No information available. No information available. |
|---|--|
| Reproductive Effects | No information available. |
| Developmental Effects | No information available. |
| Target organ effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

16676 mg/kg

Component Information

Titanium dioxide LD50 Oral: > 10000 mg/kg (Rat) Ethoxylated octylphenol LD50 Oral: mg/kg (rat, 4 hr) Carbon black LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rat) LD50 Oral: 180 mg/kg (Rat) LC50 Inhalation (Dust): 5.5 mg/m³ (Rat, 4 hr.) Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-LD50 Oral: 1017 mg/kg (Rat) LD50 Dermal: > 5000 mg/kg (Rat)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP | OSHA |
|------------------|---------------------|-----|--------|
| | 2B - Possible Human | | Listed |
| Titanium dioxide | Carcinogen | | |
| | 2B - Possible Human | | Listed |
| Carbon black | Carcinogen | | |
| | 2A - Probable Human | | Listed |
| Sodium nitrite | Carcinogen | | |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-</u> LC50: 3.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Not regulated

| ICAO / IATA | Not regulated |
|-------------|---------------|
|-------------|---------------|

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | No - Not all of the components are listed. |

Federal Regulations

SARA 311/312 hazardous categorization

| Acute health hazard | No |
|-----------------------------------|-----|
| Chronic Health Hazard | Yes |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

WARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

| Chemical name | Massachusetts | New Jersey | Pennsylvania |
|--------------------------------------|---------------|------------|--------------|
| Titanium dioxide | Х | X | X |
| Carbon black | Х | X | X |
| Sodium nitrite | Х | Х | Х |
| Urea, | Х | Х | Х |
| N-(3,4-dichlorophenyl)-N,N-dimethyl- | | | |

Legend

X - Listed

| 16. OTHER INFORMATION | | | | |
|--|----------------------------------|---------------|--------|--|
| HMIS - Health: 1* | Flammability: 0 | Reactivity: 0 | PPE: - | |
| HMIS Legend 0 - Minimal Hazard 1 - Slight Hazard 2 - Moderate Hazard 3 - Serious Hazard 4 - Severe Hazard * - Chronic Hazard X - Consult your supervisor or S.O.P | . for "Special" handling instruc | tions. | | |

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Prepared By | Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554 |
|------------------|---|
| Revision Date: | 10-Jul-2018 |
| Revision Summary | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET