

Revision Date: 11-May-2022

Revision Number: 6

1. PRODUCT AND COMPANY IDENTIFICATION

AURA GRAND ENTRANCE SATIN WHITE

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

K14701 K14701 Water thinned paint White Paint No information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com/en-ca

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization

Category 1

Label elements

Warning

Hazard statements May cause an allergic skin reaction



Odor little or no odor

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

Skin

IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material	Date HMIRA filed and
		_	Information Review Act	date exemption granted
			registry number	(if applicable)
			(HMIRA registry #)	
Titanium dioxide	13463-67-7	10 - 30%	-	-
Tetramethyl-5-decyne-4,7-diol,	126-86-3	0.1 - 0.25%	-	-
2,4,7,9-				

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice

Eye Contact

Skin Contact

No hazards which require special first aid measures.

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin

	irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health: 1 Flammability: 0	Instability: 0 Special: Not Applicable
NEPA Legend	

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Avoid contact with skin, eyes and clothing. Ensure

Other Information

Environmental precautions

Methods for Cleaning Up

adequate ventilation.

Prevent further leakage or spillage if safe to do so.

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Storage

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	TWA: 10 mg/m ³	10 mg/m³ - TWA	10 mg/m ³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWAEV
			3 mg/m ³ - TWA		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits N/E - Not established

IN/E - INOL ESTADIISTIED

Engineering Measures

Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection

Hygiene Measures

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold Density (lbs/gal) liquid little or no odor No information available 10.6 - 11.1

Specific Gravity pH Viscosity (cps) Solubility(ies) Water solubility Evaporation Rate Vapor pressure Vapor density Wt. % Solids Vol. % Solids Vol. % Solids Vol. % Volatiles VoC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing point (°C) Freezing Point (°C) Flash point (°C) Flash Point (°C) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°C)	1.28 - 1.32 No information available No information available No information available No information available No information available No information available 45 - 55 30 - 40 45 - 55 60 - 70 < 50 212 100 32 0 Not applicable Not applicable
Autoignition Temperature (°C) Decomposition Temperature (°F) Decomposition Temperature (°C) Partition coefficient	No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

<u>Product Information</u> Information on likely routes of exposure

Principal Routes of Exposure

Acute Toxicity Product Information Eye contact, skin contact and inhalation.

No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Skin contact	May cause slight irritation Prolonged skin contact may cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	40266 mg/kg
ATEmix (dermal)	160565 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			
Tetramethyl-5-decyne-4,7-diol,	> 500 mg/kg (Rat)	> 1000 mg/kg (Rabbit)	> 20 mg/L (Rat)1 h
2,4,7,9-			
126-86-3			

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide	_	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-</u> LC50: 42 mg/L (Carp (Cyprinus carpio) - 24 hr.)

Acute Toxicity to Aquatic Invertebrates

Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-LC50: 91 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

<u>Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-</u> EC50: 82 mg/L (Algae (Selenastrum capricornutum) - 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

TDG

Not regulated

ICAO / IATA

IMDG / IMO

Not regulated

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	No - Not all of the components are listed.
	One or more component is listed on NDSL.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None

<u>NPRI Part 5</u> This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

	<u>HMIS</u> -	Health: 1	Flammability: 0	Reactivity: 0	PPE: ·
--	---------------	-----------	-----------------	---------------	--------

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Issuing Date	01-Apr-2022
Revision Date: Reason for revision	11-May-2022 Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet