

Material Safety Data Sheet

Revision Date: 28-Feb-2011

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Product Class Color SUPER SPEC SWEEP-UP LATEX FLAT K15301 WATER THINNED PAINT White

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 201-573-9600 www.benjaminmoore.com Emergency Telephone Number(s) CANUTEC: 613-996-6666

2. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Components

| Chemical Name | CAS-No | Weight % (max) |
|---------------------|------------|----------------|
| Limestone | 1317-65-3 | 40 - 70% |
| Titanium dioxide | 13463-67-7 | 7 - 13% |
| Diatomaceous earth | 61790-53-2 | 1 - 5% |
| Silica, amorphous | 7631-86-9 | 1 - 5% |
| Silica, crystalline | 14808-60-7 | 0.1 - 0.25% |

3. HAZARDS IDENTIFICATION

Emergency Overview

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.

Appearance liquid

Odor little or no odor

Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

| Acute Effects | |
|-----------------|--|
| Eyes | May cause slight irritation. |
| Skin | Substance may cause slight skin irritation. |
| Inhalation | May cause irritation of respiratory tract. |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Chronic Effects | Repeated contact may cause allergic reactions in very susceptible persons. |
| | Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint. |

See Section 11 for additional Toxicological information.

| Aggravated Medical Conditions None known | | | | | |
|--|---|--------------------|---------------|--------|--|
| HMIS | Health: 1* | Flammability: 0 | Reactivity: 0 | PPE: - | |
| HMIS Lege 0 - Minimal I 1 - Slight Ha 2 - Moderate 3 - Serious I 4 - Severe H * - Chronic X - Consult handling ins | Hazard azard e Hazard Hazard Hazard Hazard your supervisor or S.C | D.P. for "Special" | | | |

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has choosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

4. FIRST AID MEASURES

| General Advice | No hazards which require special first aid measures. |
|--------------------|---|
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Notes To Physician | Treat symptomatically |

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

| Protective Equipment And Preca | utions For Firefighters | As in any fire, wear self-contained b pressure-demand, MSHA/NIOSH (a and full protective gear. | |
|--|-------------------------|--|--------------------------|
| Specific Hazards Arising From T | he Chemical | Closed containers may rupture if exp heat. | posed to fire or extreme |
| Sensitivity To Mechanical Impac | t | No | |
| Sensitivity To Static Discharge | | No | |
| Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method Flammability Limits In Air Upper Explosion Limit Lower Explosion Limit | | Not applicable Not applicable Not applicable Not applicable Not applicable | |
| | nmability: 0 Insta | bility: 0 Special: Not Appl | licable |
| NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate | | | |

- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
|---------------------------|---|
| Environmental Precautions | Prevent further leakage or spillage if safe to do so. |
| Methods For Clean-Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |
| Other Information | None known |
| | 7. HANDLING AND STORAGE |
| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or |
| | sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
| Storage | |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Hazardous Components

| Chemical Name | ACGIH | Alberta | British Columbia | Ontario | Quebec |
|---------------------|-------------------------------|---|--|---|----------------------------------|
| Limestone | N/E | 10 mg/m ³ - TWA | 10 mg/m ³ - TWA 3 mg/m ³ - TWA 20 mg/m ³ - STEL | N/E | 10 mg/m³ - TWAEV |
| Titanium dioxide | 10 mg/m ³ - TWA | 10 mg/m³ - TWA | 10 mg/m ³ - TWA 3 mg/m ³ - TWA | 10 mg/m ³ - TWAEV | 10 mg/m³ - TWAEV |
| Diatomaceous earth | N/E | 10 mg/m ³ - TWA 3 mg/m ³ - TWA | 1.5 mg/m ³ - TWA 4 mg/m ³ - TWA | 10 mg/m ³ - TWAEV containing no asbestos and less than 1% crystalline silica 3 mg/m ³ - TWAEV containing no asbestos and less than 1% crystalline silica | 6 mg/m³ - TWAEV |
| Silica, amorphous | N/E | N/E | N/E | N/E | N/E |
| Silica, crystalline | 0.025 mg/m ³ - TWA | 0.1 mg/m ³ - TWA | 0.025 mg/m ³ - TWA | 0.10 mg/m ³ - TWAEV designated substance regulation | 0.1 mg/m ³ - TWAEV |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits N/E - Not established

 Engineering Measures
 Ensure adequate ventilation, especially in confined areas.

 Personal Protective Equipment
 Safety glasses with side-shields.

 Skin Protection
 Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

9. PHYSICAL AND CHEMICAL PROPERTIES

Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing Point (°C) Flash Point (°C) Flash Point (°C) Flash Point Method Upper Explosion Limit Lower Explosion Limit

35 - 45 55 - 65 < 100 212 100 32 0 Not applicable Not applicable Not available Not available

10. STABILITY AND REACTIVITY

| Chemical Stability | Stable under normal conditions. |
|------------------------------------|--|
| Conditions To Avoid | Prevent from freezing |
| Incompatible Materials | No materials to be especially mentioned |
| Hazardous Decomposition Products | None under normal use. |
| Possibility Of Hazardous Reactions | Hazardous polymerisation will not occur. |

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product No information available

Component

Limestone LD50 Oral: 6,450 mg/kg (Rat) vendor data Sensitization: No sensitizing effects known.

<u>Titanium dioxide</u> LD50 Oral: > 24000 mg/kg (Rat) LD50 Dermal: > 10000 mg/m³ (Rabbit) LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Silica, amorphous LD50 Oral: > 10000 mg/kg (Rat) LD50 Dermal: 2,000 mg/kg (Rabbit) LC50 Inhalation (Dust): > 2 mg/L

Silica, crystalline LD50 Oral: 500 mg/kg (Rat) vendor data

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

| Chemical Name | ACGIH | IARC | NTP | OSHA Carcinogen |
|---------------------|----------------|---------------|-------------|--------------------|
| | | 2B - Possible | | Listed |
| Titanium dioxide | | Human | | |
| | | Carcinogen | | |
| | A2 - Suspected | 1 - Human | Known Human | Listed |
| Silica, crystalline | Human | Carcinogen | Carcinogen | |
| | Carcinogen | - | | |

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

ACGIH - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

Product

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Component

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal MethodDispose of in accordance with federal, state, provincial, and local regulations. Dry,
empty containers may be recycled in a can recycling program. Local requirements
may vary, consult your sanitation department or state-designated environmental
protection agency for more disposal options.

| 14. TRANSPORT INFORMATION | | |
|----------------------------|---------------|--|
| TDG | Not regulated | |
| ICAO / IATA | Not regulated | |
| IMDG / IMO | Not regulated | |
| 15. REGULATORY INFORMATION | | |

International Inventories

| United States TSCA | Yes - All components are listed or exempt. |
|--------------------|--|
| Canada DSL | Yes - All components are listed or exempt. |

15. REGULATORY INFORMATION

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

This product may contain trace amounts of (other) NPRI Parts I-4 reportable chemicals. Contact the preparer for further information.

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

This product may contain trace amounts of (other) NPRI Part 5 reportable chemicals. Contact the preparer for further information.

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2A Very toxic materials



16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture_e.html.

Prepared By Product Stewardship Department Benjamin Moore & Co. 360 Route 206 - P.O. Box 4000 Flanders, NJ 07836 866-690-1961

Revision Date: Revision Summary 28-Feb-2011 No information available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

K15301 End of MSDS