

Revision Date: 17-Jul-2024 Revision Number: 1

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name GENNEX WATERBORNE COLORANT - BLACK

Product Code
Alternate Product Code
Product Class
Color
Recommended use

N229S1
Colorant
Black
Colorant
Colorant

Restrictions on use No information available

Initial supplier identifier

Benjamin Moore & Co. Ltd. 8775 Keele Street Concord, ON L4K 2N1 www.benjaminmoore.ca Telephone: 1-800-361-5898 Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com **Emergency Telephone** 

CHEMTREC: +1 703-741-5970 /

1-800-424-9300

+1-703-527-3887 outside US & Canada CANUTEC: 613-996-6666 (Canada

Transport Emergency Only)

### 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1
Carcinogenicity	Category 1A

# Label elements

#### Danger

#### Hazard statements

May cause an allergic skin reaction May cause cancer





Appearance liquid

Odor little or no odor

Revision Date: 17-Jul-2024

#### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

# **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material	Date HMIRA filed and
				date exemption granted
			registry number (HMIRA	(if applicable)
			registry #)	
Carbon black	1333-86-4	7 - 13%	-	-
Wollastonite	13983-17-0	1 - 5%	-	-
Polypropylene glycol	25322-69-4	1 - 5%	-	-
Oxirane, phenyl-, polymer with	83653-00-3	1 - 5%	-	-
oxirane, monoalkyl ether				
2-Propenoic acid, butyl ester	141-32-2	0.1 - 0.25%	-	-
Silica, crystalline	14808-60-7	0.1 - 0.25%	-	-

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 17-Jul-2024

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective equipment and precautions for firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F) Not Applicable
Flash Point (°C) Not applicable
Method Not applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

**NFPA** 

Health hazards 1
Flammability 0
Stability 0

Special: Not Applicable

### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

# 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 17-Jul-2024

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Limits**

Chemical name	OSHA PEL	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Carbon black	3.5 mg/m <sup>3</sup> - TWA	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	3.5 mg/m <sup>3</sup> - TWA	3 mg/m³ - TWA	3 mg/m³ - TWA	3.5 mg/m³ - TWAEV
Wollastonite	-	TWA: 1 mg/m³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	-	-	-	10 mg/m³ - TWAEV 5 mg/m³ - TWAEV
2-Propenoic acid, butyl ester	-	dermal sensitizer TWA: 2 ppm	2 ppm - TWA 10 mg/m³ - TWA	2 ppm - TWA Dermal Sensitizer	2 ppm - TWA	2 ppm - TWAEV
Silica, crystalline	TWA: 50 μg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>

T14/4 F0 / 2 I			
TWA: 50 μg/m <sup>3</sup>	respirable		
excludes	particulate matter		
construction work,			
agricultural			
operations, and			
exposures that			
result from the			
processing of			
sorptive clays			
(vacated) TWA: 0.1			
mg/m³ respirable			
dust			
: (250)/(%SiO2 +			
5) mppcf TWA			
respirable fraction			
: (10)/(%SiO2 +			
2) mg/m³ TWA			
respirable fraction			

### Legend

OSHA - Occupational Safety & Health Administration Exposure Limits

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not Established

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas.

Revision Date: 17-Jul-2024

**Personal Protective Equipment** 

Eye/Face Protection
Skin Protection

**Respiratory Protection** 

Safety glasses with side-shields

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

**Hygiene Measures** 

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

**Density (lbs./gal) 8.9 - 9.3 Specific Gravity 1.06 - 1.11** 

pH No information available

Viscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information available

Vapor pressure @20 °C (kPa)

Relative vapor density

No information available
No information available

**Wt. % Solids** 20 - 30 **Vol. % Solids** 10 - 20

Page 5 / 11

N229S1 - GENNEX WATERBORNE COLORANT -

**BLACK** 

Revision Date: 17-Jul-2024

70 - 80 Wt. % Volatiles Vol. % Volatiles 80 - 90 **VOC Regulatory Limit (g/L)** 0 212 **Boiling Point (°F) Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C)

Flash point (°F) Not Applicable Flash Point (°C) Not applicable Not applicable Method Not applicable Flammability (solid, gas) **Upper flammability limit:** Not applicable

Lower flammability limit: No information available **Autoignition Temperature (°F)** No information available **Autoignition Temperature (°C)** No information available **Decomposition Temperature (°F)** No information available **Decomposition Temperature (°C)** No information available Partition coefficient No information available

# 10. STABILITY AND REACTIVITY

Not Applicable Reactivity

**Chemical Stability** Stable under normal conditions.

Conditions to avoid Prevent from freezing.

No materials to be especially mentioned. **Incompatible Materials** 

**Hazardous Decomposition Products** None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

**Product Information** 

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

**Product Information** No information available

Symptoms related to the physical, chemical and toxicological characteristics

No information available **Symptoms** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eve contact** May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or **BLACK** 

Inhalation Ingestion

Sensitization

Neurological Effects Mutagenic Effects

**Reproductive Effects** 

Target organ effects

**Developmental Effects** 

STOT - single exposure

STOT - repeated exposure

repeated contact may dry skin and cause irritation.

Revision Date: 17-Jul-2024

May cause irritation of respiratory tract.

Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

No information available.
No information available.

No information available. No information available. No information available. No information available.

No information available.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

No information available. No information available.

Other adverse effects
Aspiration Hazard

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 13747 mg/kg mg/l

#### **Component Information**

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Polypropylene glycol 25322-69-4	= 3750 mg/kg (Rat) > 2 g/kg (Rat)	-	-
Oxirane, phenyl-, polymer with oxirane, monoalkyl ether 83653-00-3	2000	-	-
2-Propenoic acid, butyl ester 141-32-2	= 2680 mg/kg (Rat)	= 2001 mg/kg (Rabbit)	= 10.3 mg/L (Rat) 4 h

#### **Chronic Toxicity**

Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Carbon black	Carcinogen		
	1 - Human Carcinogen	Known	X
Silica, crystalline			

Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

#### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

### **Mobility in Environmental Media**

No information available.

### **Ozone**

Not applicable

### **Component Information**

### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

### 13. DISPOSAL CONSIDERATIONS

#### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated

Revision Date: 17-Jul-2024

Revision Date: 17-Jul-2024

environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

### **International Inventories**

TSCA: United States

PSL: Canada

Yes - All components are listed or exempt.

No - Not all of the components are listed.

One or more component is listed on NDSL.

### **Federal Regulations**

### SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

None

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

### **California Proposition 65**

Page 9 / 11

BLACK

**WARNING:** This product can expose you to chemicals including Carbon Black, which are known to the State of California to cause cancer, and Ethylene Glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Revision Date: 17-Jul-2024

## U.S. State Right-to-Know

### Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania
Carbon black	X	X	X
2-Propenoic acid, butyl ester	X	X	X
Silica, crystalline	X	X	X

### Legend

X - Listed

# National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical name	CAS No.	<u>Weight-%</u>	NPRI Parts 1- 4
2-Propenoic acid, butyl ester	141-32-2	0.2337121-0.23	Listed

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

None

### **WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

### 16. OTHER INFORMATION

#### **HMIS**

Health hazards 1\*
Flammability 0
Reactivity: 0
Personal protection -

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Revision Date: 17-Jul-2024

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 17-Jul-2024 Reason for revision Not available

#### **Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**