

Revision Date: 17-Jul-2024 Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name GENNEX WATERBORNE COLORANT - WHITE

Product Code

Alternate Product Code
Product Class
Color

Recommended use

N229W1

Colorant

White

Colorant

Restrictions on use No information available

Initial supplier identifier

Benjamin Moore & Co. Ltd. 8775 Keele Street Concord, ON L4K 2N1 www.benjaminmoore.ca Telephone: 1-800-361-5898 **Manufacturer**

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 1-866-708-9180 www.benjaminmoore.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 /

1-800-424-9300

+1-703-527-3887 outside US & Canada CANUTEC: 613-996-6666 (Canada Transport Emergency Only)

LIAZABBO IBENITIEIOATIONI

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2

Label elements

Warning

Hazard statements

May cause an allergic skin reaction Suspected of causing cancer Suspected of damaging fertility or the unborn child



Appearance liquid

Odor little or no odor

Revision Date: 17-Jul-2024

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material	Date HMIRA filed and
		_	Information Review Act	date exemption granted
			registry number (HMIRA	(if applicable)
			registry #)	
Titanium dioxide	13463-67-7	30 - 60%	-	-
Polypropylene glycol	25322-69-4	1 - 5%	-	-
Talc	14807-96-6	1 - 5%	-	-

Silica amorphous	7631-86-9	1 - 5%	-	-
Aluminum hydroxide	21645-51-2	1 - 5%	-	-
Propylene glycol	57-55-6	1 - 5%	-	-
Magnesium carbonate	546-93-0	1 - 5%	-	-
Trimethylolpropane	77-99-6	0.1 - 0.25%	-	-
2-Propenoic acid, butyl ester	141-32-2	0.1 - 0.25%	_	-

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General AdviceNo hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 17-Jul-2024

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F)

Flash Point (°C)

Method

Not Applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA

Health hazards 2
Flammability 0
Stability 0

Special: Not Applicable

NFPA Legend

0 - Not Hazardous

1 - Slightly

2 - Moderate

3 - High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautionsSee Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 17-Jul-2024

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Ī	Chemical name	OSHA PEL	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
	Titanium dioxide	15 mg/m ³ - TWA	TWA: 0.2 mg/m ³	10 mg/m ³ - TWA	10 mg/m ³ - TWA	10 mg/m ³ - TWA	10 mg/m ³ - TWAEV

Talc	20 mppcf - TWA	nanoscale respirable particulate matter TWA: 2.5 mg/m³ finescale respirable particulate matter TWA: 2 mg/m³	2 mg/m³ - TWA	3 mg/m³ - TWA 2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m³ - TWAEV
		particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter				
Silica amorphous	20 mppcf - TWA	-	-	-	-	-
Aluminum hydroxide	-	TWA: 1 mg/m³ respirable particulate matter As Aluminum insoluble compounds [RR-51357-5] TWA: 1 mg/m³ respirable particulate matter	-	1.0 mg/m ³ - TWA	1 mg/m³ - TWA	-
Propylene glycol	-	-	-	-	10 mg/m³ - TWA 50 ppm - TWA 155 mg/m³ - TWA	-
Magnesium carbonate	-	-	-	10 mg/m³ - TWA 3 mg/m³ - TWA	-	10 mg/m³ - TWAE\
2-Propenoic acid, butyl ester	-	dermal sensitizer TWA: 2 ppm	2 ppm - TWA 10 mg/m³ - TWA	2 ppm - TWA Dermal Sensitizer	2 ppm - TWA	2 ppm - TWAEV

OSHA - Occupational Safety & Health Administration Exposure Limits

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not Established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Revision Date: 17-Jul-2024

Personal Protective Equipment

Eye/Face Protection Skin Protection Respiratory Protection Safety glasses with side-shields Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing. Remove and **Hygiene Measures**

wash contaminated clothing before re-use. Wash

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor

liquid

little or no odor

Odor Threshold No information available

 Density (lbs./gal)
 15.1 - 15.5

 Specific Gravity
 1.80 - 1.85

pH No information available
Viscosity (cps) No information available
Solubility(ies) No information available
Water solubility No information available
Evaporation Rate No information available
Vapor pressure @20 °C (kPa) No information available

Vapor pressure @20 °C (kPa)No information availableRelative vapor densityNo information availableWt. % Solids65 - 75

Wt. % Solids Vol. % Solids 40 - 50 Wt. % Volatiles 25 - 35 Vol. % Volatiles 50 - 60 VOC Regulatory Limit (g/L) 0 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C)

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Lower flammability limit:No information availableAutoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°C)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

10. STABILITY AND REACTIVITY

Revision Date: 17-Jul-2024

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Revision Date: 17-Jul-2024

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

May cause slight irritation Eve contact

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

May cause irritation of respiratory tract. Inhalation

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. No information available. No information available.

Sensitization **Neurological Effects** No information available. **Mutagenic Effects**

Reproductive Effects Possible risk of impaired fertility. Possible risk of harm to

the unborn child.

No information available. **Developmental Effects** Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available. **Aspiration Hazard** No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 6721 mg/kg ATEmix (dermal) 124566 mg/kg 34.2 mg/l ATEmix (inhalation-dust/mist)

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Polypropylene glycol 25322-69-4	= 3750 mg/kg (Rat) > 2 g/kg (Rat)	-	-
Silica amorphous 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Aluminum hydroxide 21645-51-2	> 5000 mg/kg (Rat)	-	-
Propylene glycol 57-55-6	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
Trimethylolpropane 77-99-6	= 14100 mg/kg (Rat) = 14000 mg/kg (Rat)	-	> 0.29 mg/L (Rat)4 h
2-Propenoic acid, butyl ester 141-32-2	= 2680 mg/kg (Rat)	= 2001 mg/kg (Rabbit)	= 10.3 mg/L (Rat)4 h

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

Revision Date: 17-Jul-2024

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 17-Jul-2024

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States

Yes - All components are listed or exempt.

No - Not all of the components are listed.

One or more component is listed on NDSL.

Federal Regulations

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Revision Date: 17-Jul-2024

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

U.S. State Right-to-Know Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	Χ	X	X
Talc	Χ	X	X
Silica amorphous	Χ		X
Propylene glycol		X	X
Magnesium carbonate	Χ	X	
2-Propenoic acid, butyl ester	X	X	X

Legend X - Listed

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical name	CAS No.	<u>Weight-%</u>	NPRI Parts 1- 4
2-Propenoic acid, butyl ester	141-32-2	0.1083165-0.11	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

Revision Date: 17-Jul-2024

16. OTHER INFORMATION

HMIS

Health hazards 2*
Flammability 0
Reactivity: 0
Personal protection -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 17-Jul-2024 **Reason for revision** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of

employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet

Revision Date: 17-Jul-2024

Page 12/12