

SAFETY DATA SHEET

Revision Date: 12-Aug-2018

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

SUPER SPEC INTERIOR LATEX EGGSHELL FINISH PASTEL BASE C2741B WATER THINNED PAINT All Paint

No information available

Emergency Telephone

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not applicable

Other information No information available

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% |
|------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 25 |
| Propylene glycol | 57-55-6 | 5 |

| | 4. FIRST AID MEASURES |
|------------------------------------|---|
| General Advice | No hazards which require special first aid measures. |
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | None known. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|--|--|
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity To Mechanical Impact | No |
| Sensitivity To Static Discharge | No |
| Flash Point Data Flash Point (°F) Flash Point (°C) Method | Not applicable Not applicable Not applicable |
| Flammability Limits In Air | |
| Lower flammability limit: Upper flammability limit: | Not applicable Not applicable |

| <u>NFPA</u> | Health: 1 | Flammability: 0 | Instability: 0 | Special: Not Applicable | |
|-------------|-----------|-----------------|----------------|-------------------------|--|
| NFPA Le | | | | | |

Ν 0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

| | 6. ACCIDENTAL RELEASE MEASURES |
|---------------------------|--|
| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental precautions | See Section 12 for additional Ecological Information. |
| Methods for Cleaning Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |
| | 7. HANDLING AND STORAGE |
| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
| Storage | Keep container tightly closed. Keep out of the reach of children. |
| Incompatible Materials | No information available |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL |
|------------------|----------------|----------------|
| Titanium dioxide | 10 mg/m³ - TWA | 15 mg/m³ - TWA |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

| Engineering Measures | Ensure adequate ventilation, especially in confined areas. |
|-------------------------------|--|
| Personal Protective Equipment | |
| Eye/Face Protection | Safety glasses with side-shields. |
| Skin Protection | Protective gloves and impervious clothing. |

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** pН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) **Boiling Point (°C)** Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°F) **Decomposition Temperature (°C) Partition coefficient**

liquid little or no odor No information available 10.4 - 10.8 1.25 - 1.30 No information available 40 - 50 25 - 35 50 - 60 65 - 75 < 150 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

| Product Information | | | | |
|--|---------------|---|----------------------------|-----------------------|
| Information on likely routes of e | xposure | | | |
| Principal Routes of Exposure | Eye contact | , skin contact and inhala | ation. | |
| Acute Toxicity | | | | |
| Product Information | No informat | on available | | |
| Symptoms related to the physic | al, chemical | and toxicological cha | racteristics | |
| Symptoms | No informat | on available | | |
| Delayed and immediate effects a | as well as ch | ronic effects from sho | ort and long-term expo | sure |
| Eye contact Skin contact | | slight irritation. nay cause slight skin irr | itation. Prolonged or rep | eated contact may drv |
| Inhalation | skin and ca | use irritation. rritation of respiratory tr | | ····· |
| Ingestion | Ingestion m | ay cause gastrointestina | al irritation, nausea, vom | iting and diarrhea. |
| Sensitization | | on available | | |
| Neurological Effects | | on available. | | |
| Mutagenic Effects Reproductive Effects | | on available. on available. | | |
| Developmental Effects | | on available. | | |
| Target organ effects | | on available. | | |
| STOT - single exposure | | on available. | | |
| STOT - repeated exposure | | on available. | | |
| Other adverse effects | | on available. | | |
| Aspiration Hazard | | on available | | |
| Numerical measures of toxicity | | | | |
| The following values are calcula | ited based o | n chapter 3.1 of the GI | IS document | |
| ATEmix (oral) | 23834 mg/l | • | | |
| ATEmix (dermal) | 1336178 m | g/kg | | |
| Component Information | | | | |
| <u>Titanium dioxide</u> LD50 Oral: > 10000 mg/kg (Rat) | | | | |
| Propylene glycol | | | | |
| LD50 Oral: 20000 mg/kg (Rat) LD50 Dermal: 20800 mg/kg (Rabb | oit) | | | |
| Carcinogenicity | | | | |
| The information below indicates w | hether each a | agency has listed any in | gredient as a carcinogel | n:. |
| Chemical name | | IARC | NTP | OSHA |

C2741B - SUPER SPEC INTERIOR LATEX EGGSHELL FINISH PASTEL BASE

| | 2B - Possible Human | Listed |
|------------------|---------------------|--------|
| Titanium dioxide | Carcinogen | |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Propylene glycol</u> LC50: 710 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

Acute Toxicity to Aquatic Plants

No information available

| | 13. DISPOSAL CONSIDERATIONS |
|-----------------------|---|
| Waste Disposal Method | Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options. |
| | 14. TRANSPORT INFORMATION |
| DOT | Not regulated |
| ICAO / IATA | Not regulated |
| IMDG / IMO | Not regulated |
| | 15. REGULATORY INFORMATION |

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | Yes - All components are listed or exempt. |

Federal Regulations

SARA 311/312 hazardous categorization

| Acute health hazard | No |
|-----------------------------------|----|
| Chronic Health Hazard | No |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

| Chemical name | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Titanium dioxide | Х | Х | Х |
| Propylene glycol | | X | Х |

Legend

X - Listed

| 16. OTHER INFORMATION |
|-----------------------|
|-----------------------|

HMIS - Health: 1 Flammability: 0 Reactivity: 0

PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Prepared By | Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554 |
|------------------|---|
| Revision Date: | 12-Aug-2018 |
| Revision Summary | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET