

# **SAFETY DATA SHEET**

Revision Date: 19-Jul-2018 Revision Number: 2

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SUPER SPEC INTERIOR LATEX PEARL FINISH WHITE

Product Code 27701
Alternate Product Code 27701

Product Class WATER THINNED PAINT

Color White Recommended use Paint

Restrictions on use No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. CHEMTREC (US): 800-424-9300 101 Paragon Drive CHEMTREC (outside US): (703)-527-3887

101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

# 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

## Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid Odor little or no odor

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

# 3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name    | CAS No.    | Weight-% |
|------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 20       |
| Kaolin           | 1332-58-7  | 10       |
| Ammonia          | 7664-41-7  | 0.5      |

# 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective Equipment And Precautions For** 

**Firefighters** 

As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 19-Jul-2018

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

**Flash Point Data** 

Flash Point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit: Not applicable

27701 - SUPER SPEC INTERIOR LATEX PEARL FINISH WHITE

Revision Date: 19-Jul-2018

Upper flammability limit: Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

## **NFPA Legend**

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

#### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

| Chemical name    | ACGIH TLV      | OSHA PEL       |
|------------------|----------------|----------------|
| Titanium dioxide | 10 mg/m³ - TWA | 15 mg/m³ - TWA |
| Kaolin           | 2 mg/m³ - TWA  | 15 mg/m³ - TWA |
|                  |                | 5 mg/m³ - TWA  |
| Ammonia          | 25 ppm - TWA   | 50 ppm - TWA   |
|                  | 35 ppm - STEL  | 35 mg/m³ - TWA |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

27701 - SUPER SPEC INTERIOR LATEX PEARL

**FINISH WHITE** 

Freezing Point (°C)

Partition coefficient

Revision Date: 19-Jul-2018

**Personal Protective Equipment** 

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** liquid

**Odor** little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 10.3 - 10.7

 Specific Gravity
 1.23 - 1.28

PH
Viscosity (cps)
No information available
No information available
No information available
No information available
Water solubility
No information available
Evaporation Rate
No information available
No information available

Vapor pressure @20 °C (kPa)No information availableVapor densityNo information available

Wt. % Solids 45 - 55 30 - 40 Vol. % Solids 45 - 55 Wt. % Volatiles Vol. % Volatiles 60 - 70VOC Regulatory Limit (g/L) < 150 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing Point (°F) 32

Flash Point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Lower flammability limit:Not applicableAutoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information available

# 10. STABILITY AND REACTIVITY

No information available

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

27701 - SUPER SPEC INTERIOR LATEX PEARL

**FINISH WHITE** 

Revision Date: 19-Jul-2018

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

#### Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact** Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

No information available Sensitization **Neurological Effects** No information available. No information available. **Mutagenic Effects** No information available. **Reproductive Effects Developmental Effects** No information available. Target organ effects No information available. **STOT - single exposure** No information available. STOT - repeated exposure No information available. Other adverse effects No information available. **Aspiration Hazard** No information available

# Numerical measures of toxicity

#### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 32167 mg/kg
ATEmix (dermal) 676235 mg/kg
ATEmix (inhalation-dust/mist) 379.7 mg/L

# Component Information

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

Revision Date: 19-Jul-2018

#### Ammonia

LC50 Inhalation (Vapor): 2000 ppm (Rat, 4 hr.)

# Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name    | IARC                | NTP | OSHA   |
|------------------|---------------------|-----|--------|
|                  | 2B - Possible Human |     | Listed |
| Titanium dioxide | Carcinogen          |     |        |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

# **Product Information**

### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

# **Bioaccumulation**

No information available.

#### **Mobility in Environmental Media**

No information available.

#### **Ozone**

No information available

# **Component Information**

#### **Acute Toxicity to Fish**

# Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

# **Acute Toxicity to Aquatic Plants**

No information available

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 19-Jul-2018

environmental protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

# 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.

Yes - All components are listed or exempt.

# **Federal Regulations**

#### SARA 311/312 hazardous categorization

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

Revision Date: 19-Jul-2018

# **US State Regulations**

# **California Proposition 65**

⚠ WARNING: Cancer and Reproductive Harm— www.P65warnings.ca.gov

#### State Right-to-Know

| Chemical name    | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Titanium dioxide | X             | X          | X            |
| Kaolin           | X             | X          | X            |
| Propylene glycol |               | X          | X            |

## Legend

X - Listed

#### 16. OTHER INFORMATION

HMIS -Health: 1 Flammability: 0 Reactivity: 0 PPE: -

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**Prepared By Product Stewardship Department** 

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 19-Jul-2018

27701 - SUPER SPEC INTERIOR LATEX PEARL FINISH WHITE

Revision Date: 19-Jul-2018

Revision Summary Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**