

SAFETY DATA SHEET

Revision Date: 20-Jan-2021 Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name BENJAMIN MOORE SUPER SPEC INTERIOR LATEX PEARL

FINISH MEDIUM BASE

Product Code 2772B
Alternate Product Code 2772B

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

<u>Manufacturer</u> <u>Emergency Telephone</u>

Benjamin Moore & Co. CHEMTREC: +1 703-741-5970 / 1-800-424-9300

101 Paragon Drive +1 703-527-3887 (outside US & Canada) Montvale, NJ 07645

2. HAZARDS IDENTIFICATION

Classification

Phone: 1-866-708-9180 www.benjaminmoore.com

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid Odor little or no odor

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% |
|---|------------|----------|
| Titanium dioxide | 13463-67-7 | 5 - 10 |
| Kaolin | 1332-58-7 | 1 - 5 |
| Kaolin, calcined | 92704-41-1 | 1 - 5 |
| Propylene glycol | 57-55-6 | 1 - 5 |
| Propanoic acid, 2-methyl-, monoester with | 25265-77-4 | 1 - 5 |
| 2,2,4-trimethyl-1,3-pentanediol | | |

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 20-Jan-2021

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Revision Date: 20-Jan-2021

Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautions See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL |
|------------------|--|----------------|
| Titanium dioxide | TWA: 10 mg/m ³ | 15 mg/m³ - TWA |
| Kaolin | TWA: 2 mg/m³ particulate matter | 15 mg/m³ - TWA |
| | containing no asbestos and <1% | 5 mg/m³ - TWA |
| | crystalline silica, respirable particulate | _ |
| | matter | |

Revision Date: 20-Jan-2021

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 9.75 - 9.85

 Specific Gravity
 1.16 - 1.18

pH No information available Viscosity (cps) No information available

Solubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information available

 Vapor density
 No inform

 Wt. % Solids
 40 - 50

 Vol. % Solids
 30 - 40

 Wt. % Volatiles
 50 - 60

 Vol. % Volatiles
 60 - 70

 VOC Regulatory Limit (g/L)
 < 150</td>

 Roiling Point (FF)
 212

Boiling Point (°F) 212
Boiling Point (°C) 100
Freezing point (°F) 32
Freezing Point (°C) 0

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

10. STABILITY AND REACTIVITY

Revision Date: 20-Jan-2021

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation.

Skin contactSubstance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization No information available **Neurological Effects** No information available. **Mutagenic Effects** No information available. Reproductive Effects No information available. **Developmental Effects** No information available. Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. No information available. Other adverse effects No information available **Aspiration Hazard**

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 82008 mg/kg ATEmix (dermal) 477935 mg/kg

Component Information

Revision Date: 20-Jan-2021

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------------------|---------------------|------------------------|-----------------|
| Titanium dioxide | > 10000 mg/kg (Rat) | - | - |
| 13463-67-7 | | | |
| Kaolin | > 5000 mg/kg (Rat) | > 5000 mg/kg (Rat) | - |
| 1332-58-7 | | | |
| Kaolin, calcined | > 2000 mg/kg (Rat) | - | - |
| 92704-41-1 | | | |
| Propylene glycol | = 20 g/kg (Rat) | = 20800 mg/kg (Rabbit) | - |
| 57-55-6 | | | |
| Propanoic acid, 2-methyl-, | = 3200 mg/kg (Rat) | > 15200 mg/kg (Rat) | - |
| monoester with | | | |
| 2,2,4-trimethyl-1,3-pentanediol | | | |
| 25265-77-4 | | | |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP | OSHA |
|------------------|---------------------|-----|--------|
| | 2B - Possible Human | | Listed |
| Titanium dioxide | Carcinogen | | |

[•] Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes:

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

[&]quot;No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 20-Jan-2021

environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.

Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute health hazard No
Chronic Health Hazard No
Fire hazard No

Revision Date: 20-Jan-2021

Sudden release of pressure hazard No Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65



WARNING: Cancer and Reproductive Harm— www.P65warnings.ca.gov

State Right-to-Know

| Chemical name | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Titanium dioxide | X | X | X |
| Kaolin | X | X | X |

Legend

X - Listed

16. OTHER INFORMATION

HMIS -Health: 1 Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Revision Date: 20-Jan-2021

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554

Revision Date: 20-Jan-2021 Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet