



# SAFETY DATA SHEET

Revision Date: 12-Aug-2016

Revision Number: 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** CENTURY SMALL BATCH INTERIOR PAINT SOFT TOUCH  
**Product Code** MATTE SERAPHINITE  
**Product Code** K030P5  
**Alternate Product Code** K030P5  
**Product Class** WATER THINNED PAINT  
**Color** Green  
**Recommended use** Paint  
**Restrictions on use** No information available

**Manufactured For**  
Benjamin Moore & Co., Limited  
8775 Keele Street  
Concord ON L4K 2N1  
Phone: 1-800-361-5898  
www.benjaminmoore.com

**Manufacturer**  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 855-724-6802  
www.benjaminmoore.com

**Emergency Telephone Number(s)**  
CANUTEC: 613-996-6666

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is not considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

### Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

**Appearance** liquid

**Odor** little or no odor

### Other information

No information available

**Other hazards**

May cause allergic skin reaction

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Silica, amorphous	7631-86-9	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Propylene glycol	57-55-6	1 - 5%
Hexanedioic acid, dihydrazide	1071-93-8	0.1 - 0.25%
Sodium C14-C16 olefin sulfonate	68439-57-6	0.1 - 0.25%

### 4. FIRST AID MEASURES

<b>General Advice</b>	No hazards which require special first aid measures.
<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
<b>Inhalation</b>	Move to fresh air. If symptoms persist, call a physician.
<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
<b>Most Important Symptoms/Effects</b>	May cause allergic skin reaction.
<b>Notes To Physician</b>	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective Equipment And Precautions For Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Specific Hazards Arising From The Chemical</b>	Closed containers may rupture if exposed to fire or extreme heat.
<b>Sensitivity To Mechanical Impact</b>	No
<b>Sensitivity To Static Discharge</b>	No

**Flash Point Data**

Flash Point (°F) Not applicable  
Flash Point (°C) Not applicable  
Flash Point Method Not applicable

**Flammability Limits In Air**

Lower Explosion Limit Not applicable  
Upper Explosion Limit Not applicable

**NFPA** Health: 1 Flammability: 0 Instability: 0 **Special:** Not Applicable

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental Precautions** See Section 12 for additional Ecological Information.

**Methods For Clean-Up** Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**7. HANDLING AND STORAGE**

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

**Incompatible Materials** No information available

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Limits**

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA 3 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV

Propylene glycol	N/E	N/E	N/E	10 mg/m <sup>3</sup> - TWA 50 ppm - TWA 155 mg/m <sup>3</sup> - TWA	N/E
------------------	-----	-----	-----	---	-----

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists  
 Alberta - Alberta Occupational Exposure Limits  
 British Columbia - British Columbia Occupational Exposure Limits  
 Ontario - Ontario Occupational Exposure Limits  
 Quebec - Quebec Occupational Exposure Limits  
 N/E - Not established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

Safety glasses with side-shields.

**Skin Protection**

Protective gloves and impervious clothing.

**Respiratory Protection**

In case of insufficient ventilation wear suitable respiratory equipment.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	liquid
<b>Odor</b>	little or no odor
<b>Odor Threshold</b>	No information available
<b>Density (lbs/gal)</b>	8.8 - 8.9
<b>Specific Gravity</b>	1.05 - 1.07
<b>pH</b>	No information available
<b>Viscosity (cps)</b>	No information available
<b>Solubility</b>	No information available
<b>Water Solubility</b>	No information available
<b>Evaporation Rate</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>Vapor Density</b>	No information available
<b>Wt. % Solids</b>	35 - 45
<b>Vol. % Solids</b>	30 - 40
<b>Wt. % Volatiles</b>	55 - 65
<b>Vol. % Volatiles</b>	60 - 70
<b>VOC Regulatory Limit (g/L)</b>	< 50
<b>Boiling Point (°F)</b>	212
<b>Boiling Point (°C)</b>	100
<b>Freezing Point (°F)</b>	32
<b>Freezing Point (°C)</b>	0
<b>Flash Point (°F)</b>	Not applicable
<b>Flash Point (°C)</b>	Not applicable
<b>Flash Point Method</b>	Not applicable
<b>Flammability (solid, gas)</b>	Not applicable
<b>Upper Explosion Limit</b>	Not applicable
<b>Lower Explosion Limit</b>	Not applicable
<b>Autoignition Temperature (°F)</b>	No information available
<b>Autoignition Temperature (°C)</b>	No information available
<b>Decomposition Temperature (°F)</b>	No information available

Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available

## 10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions To Avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility Of Hazardous Reactions	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

Principal Routes of Exposure	Eye contact, skin contact and inhalation.
------------------------------	---

### Acute Toxicity

Product Information	No information available
---------------------	--------------------------

#### Information on toxicological effects

Symptoms	No information available
----------	--------------------------

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	May cause slight irritation
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization:	May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 93379 mg/kg  
ATEmix (dermal) 55018 mg/kg

**Component**

Silica, amorphous

LD50 Oral: > 5000 mg/kg (Rat)  
LD50 Dermal: 2,000 mg/kg (Rabbit)  
LC50 Inhalation (Dust): > 2 mg/L

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

Propylene glycol

LD50 Oral: 20000 mg/kg (Rat)  
LD50 Dermal: 20800 mg/kg (Rabbit)

**Chronic Toxicity**

**Carcinogenicity**

*The information below indicates whether each agency has listed any ingredient as a carcinogen:.*

Chemical Name	IARC	NTP
Titanium dioxide	2B - Possible Human Carcinogen	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

**Legend**

IARC - International Agency for Research on Cancer  
NTP - National Toxicity Program  
OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

**Product Information**

**Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Persistence / Degradability**

No information available.

**Bioaccumulation / Accumulation**

No information available.

**Mobility in Environmental Media**

No information available.

**Ozone**

No information available

**Component**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

**Acute Toxicity to Aquatic Plants**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**14. TRANSPORT INFORMATION**

**TDG**

Not regulated

**ICAO / IATA**

Not regulated

**IMDG / IMO**

Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA: United States**

Yes - All components are listed or exempt.

**DSL: Canada**

Yes - All components are listed or exempt.

## National Pollutant Release Inventory (NPRI)

### NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Parts 1- 4</u>
Propylene glycol	57-55-6	1 - 5%	Listed

### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

## 16. OTHER INFORMATION

**HMIS - Health: 1 Flammability: 0 Reactivity: 0 PPE: -**

### **HMIS Legend**

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

### **Prepared By**

Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
855-724-6802



---

**Revision Date:** 12-Aug-2016  
**Reason For Revision** Not available

**Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**