

Revision Date: 16-Nov-2022

Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

BENJAMIN MOORE STIPPLE LATEX ENAMEL INTERIOR SATIN FINISH WHITE 35000

35000 Water thinned paint White Paint No information available

> Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not applicable

Other information No information available **WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%
Titanium dioxide	13463-67-7	10 - 15
Kaolin, calcined	92704-41-1	1 - 5
Limestone	1317-65-3	1 - 5
Nepheline syenite	37244-96-5	1 - 5
Propanoic acid, 2-methyl-, monoester with	25265-77-4	1 - 5
2,2,4-trimethyl-1,3-pentanediol		

	4. FIRST AID MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.
	5. FIRE-FIGHTING MEASURES
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

No

No

extreme heat.

Closed containers may rupture if exposed to fire or

Specific Hazards Arising From The Chemical

Sensitivity to mechanical impact

Sensitivity to static discharge

Flash Point Data Flash point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health hazards Flammability Stability Special:	1 0 0 Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate 3 - High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

|--|

Titanium dioxide	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	15 mg/m³ - TWA
Limestone	-	15 mg/m³ - TWA 5 mg/m³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	
Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	Protective gloves and impervious clothing.
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated

9. PHYSICAL AND CHEMICAL PROPERTIES

clothing before re-use. Wash thoroughly after handling.

Appearance	liquid
Odor Odor Threshold	little or no odor
	No information available
Density (Ibs/gal)	
Specific Gravity	1.34 - 1.39
pH Missional (an all)	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available
Wt. % Solids	40 - 50
Vol. % Solids	30 - 40
Wt. % Volatiles	50 - 60
Vol. % Volatiles	60 - 70
VOC Regulatory Limit (g/L)	< 100
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing point (°F)	32
Freezing Point (°C)	0
Flash point (°F)	Not applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available

Decomposition Temperature (°F) Decomposition Temperature (°C) Partition coefficient No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable		
Chemical Stability		Stable under normal conditions.	
Conditions to avoid		Prevent from freezing.	
Incompatible Materials		No materials to be especially mentioned.	
Hazardous Decomposition Prod	lucts	None under normal use.	
Possibility of hazardous reactions		None under normal conditions of use.	
1	1. TOXICOLOGI	CAL INFORMATION	
Product Information			
Information on likely routes of e	exposure		
Principal Routes of Exposure	Eye contact, skin cont	act and inhalation.	
Acute Toxicity			
Product Information	No information availab	le	
Symptoms related to the physic	al, chemical and toxic	ological characteristics	
Symptoms	No information availab	le	
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Eye contact	May cause slight irritat	tion.	
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry		
Inholation	skin and cause irritation. May cause irritation of respiratory tract.		
Inhalation Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
Sensitization	No information available		
Neurological Effects	No information available.		
Mutagenic Effects	No information available.		
Reproductive Effects	No information available.		
Developmental Effects Target organ effects	No information available. No information available.		
STOT - single exposure	No information availab		
STOT - repeated exposure	No information availab	le.	
Other adverse effects	No information available.		
Aspiration Hazard	No information availab	le	

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

57799 mg/kg

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Kaolin, calcined 92704-41-1	> 2000 mg/kg (Rat)	-	-
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	-

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

Not applicable

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
	14. TRANSPORT INFORMATION
DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated
	15. REGULATORY INFORMATION
International Inventories	
TSCA: United States DSL: Canada	Yes - All components are listed or exempt. Yes - All components are listed or exempt.
Federal Regulations	
SARA 311/312 Hazard Categorie Acute health hazard Chronic Health Hazard Fire hazard Sudden release of pressure ha	No No

Reactive Hazard

No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

U.S. State Right-to-Know

Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	Х	Х	Х
Limestone	Х	Х	Х

Legend

X - Listed

16. OTHER INFORMATION

Ш	MIS	3
---	-----	---

Health hazards	1
Flammability	0
Reactivity:	0
Personal protection	-

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	16-Nov-2022
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet