

SAFETY DATA SHEET

Revision Date: 13-Jun-2019 Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ULTRA SPEC MASONRY ELASTOMERIC WATERPROOF

COATING - FLAT BASE 3

Product Code K3593X
Alternate Product Code K3593X

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180

www.benjaminmoore.com

Emergency Telephone CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

Warning

Hazard statements

Suspected of causing cancer

May cause damage to organs through prolonged or repeated exposure



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material	Date HMIRA filed and
				date exemption granted
			registry number	(if applicable)
			(HMIRA registry #)	
Nepheline syenite	37244-96-5	10 - 30%	-	-
Titanium dioxide	13463-67-7	1 - 5%	-	-
Ethylene glycol	107-21-1	1 - 5%	-	-
Silica, mica	12001-26-2	1 - 5%	-	-
Zinc oxide	1314-13-2	0.5 - 1%	-	-
Diphenyl ketone	119-61-9	0.1 - 0.25%	-	-

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice For further assistance, contact your local Poison Control

Center.

Eye Contact Rinse thoroughly with plenty of water for at least 15

K3593X - ULTRA SPEC MASONRY ELASTOMERIC WATERPROOF COATING - FLAT BASE 3

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Call a POISON CENTER or doctor/physician if exposed or you feel unwell. If large quantities of this material are swallowed, call a physician immediately.

Revision Date: 13-Jun-2019

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautions See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 13-Jun-2019

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Nepheline syenite	N/E	N/E	N/E	10 mg/m ³ - TWA	N/E
Titanium dioxide	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV
Ethylene glycol	100 mg/m³ - Ceiling	100 mg/m ³ - Ceiling	10 mg/m³ - TWA 20 mg/m³ - STEL 100 mg/m³ - Ceiling 50 ppm - Ceiling	100 mg/m ³ - Ceiling	50 ppm - Ceiling 127 mg/m³ - Ceiling
Silica, mica	3 mg/m ³ - TWA	3 mg/m³ - TWA	3 mg/m³ - TWA	3 mg/m³ - TWA	3 mg/m ³ - TWAEV
Zinc oxide	2 mg/m³ - TWA 10 mg/m³ - STEL	2 mg/m³ - TWA 10 mg/m³ - STEL	2 mg/m³ - TWA 10 mg/m³ - STEL	2 mg/m³ - TWA 10 mg/m³ - STEL	10 mg/m³ - TWAEV 5 mg/m³ - TWAEV 10 mg/m³ - STEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

Revision Date: 13-Jun-2019

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 10.2 - 10.6

 Specific Gravity
 1.22 - 1.27

pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information available

Vapor pressureNo information availableVapor densityNo information available

 Wt. % Solids
 45 - 55

 Vol. % Solids
 35 - 45

 Wt. % Volatiles
 45 - 55

 Vol. % Volatiles
 55 - 65

 VOC Regulatory Limit (g/L)
 < 100</td>

VOC Regulatory Limit (g/L) < 10
Boiling Point (°F) 212
Boiling Point (°C) 100
Freezing point (°F) 32
Freezing Point (°C) 0

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Lower flammability limit:

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

No information available

No information available

Partition coefficient No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions

None under normal conditions of use.

Revision Date: 13-Jun-2019

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion May be harmful if swallowed. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

May cause adverse kidney effects.

No information available. Sensitization **Neurological Effects** No information available. No information available. **Mutagenic Effects** No information available. **Reproductive Effects Developmental Effects** No information available. **Target organ effects** No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available. **Aspiration Hazard** No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 23293 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ethylene glycol 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)= 9530 μL/kg (Rabbit)	-
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Diphenyl ketone 119-61-9	> 10 g/kg (Rat)	= 3535 mg/kg (Rabbit)	-

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide	_	
	2B - Possible Human Carcinogen	
Diphenyl ketone	_	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

K3593X - ULTRA SPEC MASONRY ELASTOMERIC WATERPROOF COATING - FLAT BASE 3

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Ethylene glycol

LC50: 8050 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, provincial,

and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal

Revision Date: 13-Jun-2019

options.

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.
Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical nameCAS No.Weight-%NPRI Parts 1- 4Ethylene glycol107-21-11 - 5%Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 1* Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 13-Jun-2019 **Reason for revision** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet