



# Benjamin Moore®

## SAFETY DATA SHEET

Revision Date: 11-Sep-2023

Revision Number: 6

### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name</b>	<b>ULTRA SPEC MASONRY 100% ELASTOMERIC WATERPROOF COATING - LOW LUSTRE BASE 1</b>
<b>Product Code</b>	<b>K3601X</b>
<b>Alternate Product Code</b>	K3601X
<b>Product Class</b>	Water thinned paint
<b>Color</b>	All
<b>Recommended use</b>	Surface coating
<b>Restrictions on use</b>	No information available

**Manufactured For**

Benjamin Moore & Co., Limited  
8775 Keele Street  
Concord ON L4K 2N1  
Phone: 1-800-361-5898  
[www.benjaminmoore.com/en-ca](http://www.benjaminmoore.com/en-ca)

**Manufacturer**

Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-866-708-9180  
[www.benjaminmoore.com](http://www.benjaminmoore.com)

**Emergency Telephone**

CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
+1 703-527-3887 (outside US & Canada)  
CANUTEC: 613-996-6666 (Transport Emergency Only)

### 2. HAZARDS IDENTIFICATION

**Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Carcinogenicity	Category 1A
-----------------	-------------

**Label elements**

**Danger**

**Hazard statements**

May cause cancer



**Appearance** liquid

**Odor** little or no odor

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Limestone	1317-65-3	10 - 30%	-	-
Titanium dioxide	13463-67-7	7 - 13%	-	-
Propylene glycol	57-55-6	1 - 5%	-	-
Zinc oxide	1314-13-2	1 - 5%	-	-
Silica, mica	12001-26-2	1 - 5%	-	-
Ammonium hydroxide	1336-21-6	0.25 - 0.5%	-	-
Diphenyl ketone	119-61-9	0.1 - 0.25%	-	-
Silica, crystalline	14808-60-7	0.1 - 0.25%	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data	
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability Limits In Air	
Lower flammability limit:	Not applicable
Upper flammability limit:	Not applicable
NFPA	
Health hazards	1
Flammability	0
Stability	0
Special:	Not Applicable

### **NFPA Legend**

0 - Not Hazardous  
1 - Slightly  
2 - Moderate  
3 - High  
4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions**

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

### **Other Information**

Prevent further leakage or spillage if safe to do so.

### **Environmental precautions**

See Section 12 for additional Ecological Information.

### **Methods for Cleaning Up**

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

## **7. HANDLING AND STORAGE**

### **Handling**

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

### **Storage**

Keep container tightly closed. Keep out of the reach of children.

### **Incompatible Materials**

No information available

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Exposure Limits**

<b>Chemical name</b>	<b>ACGIH TLV</b>	<b>Alberta</b>	<b>British Columbia</b>	<b>Ontario</b>	<b>Quebec</b>
Limestone	-	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA 3 mg/m <sup>3</sup> - TWA 20 mg/m <sup>3</sup> - STEL	-	10 mg/m <sup>3</sup> - TWAEV
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA 3 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV
Propylene glycol	-	-	-	10 mg/m <sup>3</sup> - TWA 50 ppm - TWA 155 mg/m <sup>3</sup> - TWA	-
Zinc oxide	STEL: 10 mg/m <sup>3</sup> respirable particulate	2 mg/m <sup>3</sup> - TWA 10 mg/m <sup>3</sup> - STEL	2 mg/m <sup>3</sup> - TWA 10 mg/m <sup>3</sup> - STEL	2 mg/m <sup>3</sup> - TWA 10 mg/m <sup>3</sup> - STEL	10 mg/m <sup>3</sup> - TWAEV 5 mg/m <sup>3</sup> - TWAEV

	matter TWA: 2 mg/m <sup>3</sup> respirable particulate matter TWA: 0.5 mg/m <sup>3</sup> Ba As Barium soluble compounds [RR-00049-7]				10 mg/m <sup>3</sup> - STEV
Silica, mica	TWA: 0.1 mg/m <sup>3</sup> respirable particulate matter	3 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWAEV
Ammonium hydroxide	STEL: 35 ppm TWA: 25 ppm	-	-	-	-
Silica, crystalline	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists  
Alberta - Alberta Occupational Exposure Limits  
British Columbia - British Columbia Occupational Exposure Limits  
Ontario - Ontario Occupational Exposure Limits  
Quebec - Quebec Occupational Exposure Limits  
N/E - Not established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

**Skin Protection**

**Respiratory Protection**

Safety glasses with side-shields  
Protective gloves and impervious clothing.  
In case of insufficient ventilation wear suitable respiratory equipment.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance**

liquid

**Odor**

little or no odor

**Odor Threshold**

No information available

**Density (lbs./gal)**

10.9 - 11.0

**Specific Gravity**

1.30 - 1.35

**pH**

No information available

**Viscosity (cps)**

No information available

**Solubility(ies)**

No information available

**Water solubility**

No information available

**Evaporation Rate**

No information available

**Vapor pressure @20 °C (kPa)**

No information available

**Relative vapor density**

No information available

**Wt. % Solids**

55 - 65

**Vol. % Solids**

40 - 50

**Wt. % Volatiles**

35 - 45

**Vol. % Volatiles**

50 - 60

**VOC Regulatory Limit (g/L)**

<100

**Boiling Point (°F)**

212

---

Boiling Point (°C)	100
Freezing point (°F)	32
Freezing Point (°C)	0
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

## 10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

Principal Routes of Exposure	Eye contact, skin contact and inhalation.
------------------------------	---

### Acute Toxicity

Product Information	No information available
---------------------	--------------------------

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available
----------	--------------------------

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	May cause slight irritation
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea,

---

**Sensitization**  
**Neurological Effects**  
**Mutagenic Effects**  
**Reproductive Effects**  
**Developmental Effects**  
**Target organ effects**  
**STOT - single exposure**  
**STOT - repeated exposure**

vomiting and diarrhea.  
No information available.  
No information available.  
No information available.  
No information available.  
No information available.  
No information available.  
No information available.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
No information available.  
No information available.

**Other adverse effects**  
**Aspiration Hazard**

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 17659 mg/kg  
**ATEmix (inhalation-dust/mist)** 130.7 mg/l

### Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Propylene glycol 57-55-6	= 20 g/kg ( Rat )	= 20800 mg/kg ( Rabbit )	-
Zinc oxide 1314-13-2	> 5000 mg/kg ( Rat )	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg ( Rat )	-	-
Diphenyl ketone 119-61-9	> 10 g/kg ( Rat )	= 3535 mg/kg ( Rabbit )	-

### Chronic Toxicity

#### **Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
Titanium dioxide	2B - Possible Human Carcinogen	
Diphenyl ketone	2B - Possible Human Carcinogen	
Silica, crystalline	1 - Human Carcinogen	Known

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

---

**Legend**

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

#### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### **Persistence / Degradability**

No information available.

#### **Bioaccumulation**

There is no data for this product.

#### **Mobility in Environmental Media**

No information available.

#### **Ozone**

Not applicable

### **Component Information**

#### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

#### **Acute Toxicity to Aquatic Plants**

No information available



### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

**TDG** Not regulated

**ICAO / IATA** Not regulated

**IMDG / IMO** Not regulated

### 15. REGULATORY INFORMATION

**International Inventories**

**TSCA: United States** Yes - All components are listed or exempt.  
**DSL: Canada** Yes - All components are listed or exempt.

**National Pollutant Release Inventory (NPRI)**

**NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

*None*

**NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

*None*

**WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

### 16. OTHER INFORMATION

**HMIS**

<b>Health hazards</b>	1*
<b>Flammability</b>	0
<b>Reactivity:</b>	0
<b>Personal protection</b>	-

**HMIS Legend**

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision Date:** 11-Sep-2023  
**Reason for revision** Not available

**Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**