SAFETY DATA SHEET

Revision Date: *03-Jun-2025* **Revision Number:** *7*

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name **ULTRA SPEC MASONRY 100% ELASTOMERIC WATERPROOF COATING - LOW LUSTRE BASE 2**

Product Code **K3602X**

Alternate Product Code K3602X
Product Class Water thinned paint
Color All
Recommended use Surface coating
Restrictions on use No information available

Manufactured For
Benjamin Moore & Co., Limited
1651 Stellar Drive, Unit 1
Whitby, Ontario L1N 6A7
Phone: 1-800-361-5898
www.benjaminmoore.com/en-ca

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.benjaminmoore.com

Emergency Telephone
CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)
CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Carcinogenicity	Category 1A

Label elements

Danger

Hazard statements
May cause cancer

Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage
Store locked up

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other information
No information available

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Limestone	1317-65-3	10 - 30%	-	-
Titanium dioxide	13463-67-7	7 - 13%	-	-
Propylene glycol	57-55-6	1 - 5%	-	-
Zinc oxide	1314-13-2	1 - 5%	-	-
Silica, mica	12001-26-2	1 - 5%	-	-
Ammonium hydroxide	1336-21-6	0.25 - 0.5%	-	-
Diphenyl ketone	119-61-9	0.1 - 0.25%	-	-
Silica, crystalline	14808-60-7	0.1 - 0.25%	-	-

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable

Flammability Limits In Air

Lower flammability limit:	Not applicable
Upper flammability limit:	Not applicable

NFPA

Health hazards	1
Flammability	0

Stability	0
Special:	Not Applicable

NFPA Legend
0 - Not Hazardous
1 - Slightly
2 - Moderate
3 - High
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions — Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information — Prevent further leakage or spillage if safe to do so.

Environmental precautions — See Section 12 for additional Ecological Information.

Methods for Cleaning Up — Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling — Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage — Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials — No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Limestone	-	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA 20 mg/m³ - STEL	-	10 mg/m³ - TWAEV
Titanium dioxide	TWA: 0.2 mg/m³ nanoscale respirable particulate matter TWA: 2.5 mg/m³ finescale respirable particulate matter	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV

Propylene glycol	-	-	-	10 mg/m³ - TWA 50 ppm - TWA 155 mg/m³ - TWA	-
Zinc oxide	STEL: 10 mg/m³ respirable particulate matter TWA: 2 mg/m³ respirable particulate matter TWA: 0.5 mg/m³ Ba As Barium soluble compounds [RR-00049-7]	2 mg/m³ - TWA 10 mg/m³ - STEL	2 mg/m³ - TWA 10 mg/m³ - STEL	2 mg/m³ - TWA 10 mg/m³ - STEL	10 mg/m³ - TWAEV 5 mg/m³ - TWAEV 10 mg/m³ - STEV
Silica, mica	TWA: 0.1 mg/m³ respirable particulate matter	3 mg/m³ - TWA	3 mg/m³ - TWA	3 mg/m³ - TWA	3 mg/m³ - TWAEV
Ammonium hydroxide	STEL: 35 ppm TWA: 25 ppm	-	-	-	-
Silica, crystalline	TWA: 0.025 mg/m³ respirable particulate matter	TWA: 0.025 mg/m³	TWA: 0.025 mg/m³	TWA: 0.10 mg/m³	TWA: 0.1 mg/m³

Legend
ACGIH - American Conference of Governmental Industrial Hygienists
Alberta - Alberta Occupational Exposure Limits
British Columbia - British Columbia Occupational Exposure Limits
Ontario - Ontario Occupational Exposure Limits
Quebec - Quebec Occupational Exposure Limits
N/E - Not established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	little or no odor
Odor Threshold	No information available
Density (lbs./gal)	11.0 - 11.4
Specific Gravity	1.31 - 1.36
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available

Wt. % Solids	55 - 65
Vol. % Solids	40 - 50
Wt. % Volatiles	35 - 45
Vol. % Volatiles	50 - 60
VOC Regulatory Limit (g/L)	<100
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing point (°F)	32
Freezing Point (°C)	0
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information
Information on likely routes of exposure

Principal Routes of Exposure	Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information	No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	May cause slight irritation
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	No information available.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	22472 mg/kg
ATEmix (dermal)	99999 mg/kg
ATEmix (inhalation-dust/mist)	131.5 mg/l

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Propylene glycol 57-55-6	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-
Diphenyl ketone 119-61-9	> 10 g/kg (Rat)	= 3535 mg/kg (Rabbit)	-

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
Titanium dioxide	2B - Possible Human Carcinogen	
	2B - Possible Human Carcinogen	

Diphenyl ketone		
Silica, crystalline	1 - Human Carcinogen	Known

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend
IARC - International Agency for Research on Cancer
NTP - National Toxicity Program
OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects
The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish
No information available

Acute Toxicity to Aquatic Invertebrates
No information available

Acute Toxicity to Aquatic Plants
No information available

Persistence / Degradability
No information available.

Bioaccumulation
There is no data for this product.

Mobility in Environmental Media
No information available.

Ozone
Not applicable

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)
Propylene glycol
LC50: 710 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol
EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

Acute Toxicity to Aquatic Plants
No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4
This product contains the following Parts 1-4 NPRI chemicals:

None

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

16. OTHER INFORMATION

HMIS

Health hazards	1*
Flammability	0
Reactivity:	0
Personal protection	-

HMIS Legend
0 - Minimal Hazard
1 - Slight Hazard
2 - Moderate Hazard
3 - Serious Hazard
4 - Severe Hazard
* - Chronic Hazard
X - Consult your supervisor or S.O.P. for "Special" handling instructions.
Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By
Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 03-Jun-2025
Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet