

Material Safety Data Sheet

Revision Date: 17-Jun-2008 **Revision Number: 1**

PRODUCT AND COMPANY IDENTIFICATION

Product Name IMPERVO 440 SPAR VARNISH

Product Code C440

Manufacturer **Emergency Telephone Number(s)**

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 201-573-9600

www.benjaminmoore.com

2. COMPOSITION INFORMATION ON COMPONENTS

CHEMTREC: 800-424-9300

Hazardous Components

Chemical Name	CAS-No	Weight % (max)				
Distillates, petroleum, hydrotreated light	64742-47-8	30				
Stoddard solvent	8052-41-3	15				
Linseed oil	8001-26-1	10				
Hydrocarbons, terpene processing by-products	68956-56-9	5				

3. HAZARDS IDENTIFICATION

Emergency Overview WARNING

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis. Combustible material.

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded.

Appearance liquid **Odor** solvent

This material is considered hazardous by the OSHA Hazard Communication **OSHA Regulatory Status**

Standard (29 CFR 1910.1200).

Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Effects

EyesContact with eyes may cause irritation. **Skin**May cause skin irritation and/or dermatitis.

Inhalation High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs

and may cause headaches, dizziness, drowsiness, unconsciousness, and other

Revision Date: 17-Jun-2008

central nervous system effects.

Ingestion Ingestion may cause irritation to mucous membranes. Small amounts of this product

aspirated into the respiratory system during ingestion or vomiting may cause mild to

severe pulmonary injury, possibly progressing to death.

Chronic Effects Avoid repeated exposure.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 2 Flammability: 2 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, Benjamin Moore & Co., has choosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact

lenses and continue flushing for at least 15 minutes. Keep eye wide open while

rinsing. If symptoms persist, call a physician.

Skin ContactWash off immediately with soap and plenty of water removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

If not breathing, give artificial respiration. Call a physician immediately.

Ingestion Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting

without medical advice. Never give anything by mouth to an unconscious person.

Consult a physician.

Notes To Physician Treat symptomatically

Protection Of First-Aiders

Remove all sources of ignition.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Foam, dry powder or water. Use extinguishing measures

that are appropriate to local circumstances and the

surrounding environment.

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 17-Jun-2008

and full protective gear.

Specific Hazards Arising From The Chemical Combustible material. Closed containers may rupture if

exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and

vapors.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge Yes

Flash Point Data

Flash Point (°F) 107
Flash Point (°C) 41.7
Flash Point Method PMCC

Flammability Limits In Air

Lower Explosion LimitNot availableUpper Explosion LimitNot available

NFPA Health: 2 Flammability: 2 Instability: 0 Special: -

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned by Benjamin Moore & Co. are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsUse personal protective equipment. Remove all sources of ignition.

Environmental Precautions Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if

significant spillages cannot be contained.

C440 - IMPERVO 440 SPAR VARNISH

Methods For Clean-Up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly

labeled containers. Clean contaminated surface thoroughly.

Other Information None known

7. HANDLING AND STORAGE

Handling Use only in area provided with appropriate exhaust ventilation. Do not breathe

vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open

Revision Date: 17-Jun-2008

flames, hot surfaces and sources of ignition.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away

from heat. Keep in properly labeled containers.

DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or

waste in a sealed water-filled metal container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

Hazardous Components

Chemical Name	ACGIH	OSHA	
Distillates, petroleum, hydrotreated light	N/E	N/E	
Stoddard solvent	100 ppm - TWA	PEL 2900 mg/m ³ / 500 ppm	
Linseed oil	N/E	N/E	
Hydrocarbons, terpene processing by-	N/E	N/E	
products			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Skin Protection

Safety glasses with side-shields.

Long sleeved clothing. Protective gloves.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

When spraying the product or applying in confined areas, wear a NIOSH approved

respirator specified for paint spray or organic vapors.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling. When using do not eat, drink or

smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Date: 17-Jun-2008

AppearanceliquidOdorsolventDensity (lbs/gal)7.5Specific Gravity0.91

pH Not available
Viscosity (centistokes) Not available
Evaporation Rate Not available
Vapor Pressure Not available
Vapor Density Not available

Wt. % Solids 61.5 Vol. % Solids 56.9 Wt. % Volatiles 38.5 Vol. % Volatiles 43.1 < 350.0 VOC (g/L) Not available **Boiling Point (°F) Boiling Point (°C)** Not available Freezing Point (°F) Not available Freezing Point (°C) Not available 107

Flash Point (°F)
Flash Point (°C)
Flash Point Method
Upper Explosion Limit
Lower Explosion Limit
Not available

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions. Hazardous polymerisation

does not occur.

Conditions To Avoid Keep away from open flames, hot surfaces, static electricity

and sources of ignition.

Incompatible Materials Incompatible with strong acids and bases and strong

oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating

gases and vapors.

Possibility Of Hazardous Reactions

None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Revision Date: 17-Jun-2008

Component

Distillates, petroleum, hydrotreated light

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3,000 mg/kg (Rabbit)

Stoddard solvent

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3160 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 6.1 mg/L (Rat)

Hydrocarbons, terpene processing by-products

Sensitization:

May cause sensitization by skin contact

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

Product

Acute Toxicity to Fish
No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Component

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Dry, empty containers may be recycled in a can recycling program. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 17-Jun-2008

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Contact Benjamin Moore & Co. for further information.

IMDG / IMOContact Benjamin Moore & Co. for further information.

15. REGULATORY INFORMATION

International Inventories

United States TSCA Canada DSL

Yes - All components are listed or exempt. No - Not all of the components are listed.

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

This product may contain trace amounts of (other) SARA reportable chemicals. Contact Benjamin Moore & Co. for further information.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

This product may contain trace amounts of (other) HAPs chemicals. Contact Benjamin Moore & Co. for further information.

State Regulations

California Proposition 65

Revision Date: 17-Jun-2008

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Distillates, petroleum,	X	X	X		X
hydrotreated light					
Stoddard solvent	X	Χ	X		X
Linseed oil			X		X
Hydrocarbons, terpene		Χ			
processing by-products					

Legend

X - Listed

16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co.

360 Route 206 - P.O. Box 4000

Flanders, NJ 07836

973-252-2593

Revision Date: 17-Jun-2008 **Revision Summary** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of MSDS