

# SAFETY DATA SHEET

Revision Date: 07-Apr-2016

**Revision Number: 2** 

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# ULTRA SPEC EXT LOW LUSTRE FINISH WHITE

K45501 K45501 WATER THINNED PAINT White Paint No information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com

## Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com Emergency Telephone Number(s) CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is not considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

## Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Other information No information available

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Titanium dioxide	13463-67-7	10 - 30%
Nepheline syenite	37244-96-5	3 - 7%
Kaolin	1332-58-7	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Sodium C14-C16 olefin sulfonate	68439-57-6	0.1 - 0.25%

4. FIRST A	ID MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	None known.

Notes To Physician

5. FIRE-FIGHTING MEASURES

Treat symptomatically.

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	No
Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method	Not applicable Not applicable Not applicable

Flammability: 0

#### Flammability Limits In Air

Lower Explosion Limit Upper Explosion Limit

Health: 1

Not applicable Not applicable

Special: Not Applicable

# NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High

NFPA

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Instability: 0

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** 

**Other Information** 

**Environmental Precautions** 

Methods For Clean-Up

See Section 12 for additional Ecological Information.

Avoid contact with skin, eyes and clothing. Ensure

Prevent further leakage or spillage if safe to do so.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient

# 7. HANDLING AND STORAGE

Handling

Storage

ventilation, wear suitable respiratory equipment. Keep container tightly closed. Keep out of the reach of

Incompatible Materials

No information available

adequate ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

children.

# **Exposure Limits**

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV
Nepheline syenite	N/E	N/E	N/E	10 mg/m <sup>3</sup> - TWAEV	N/E
Kaolin	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m <sup>3</sup> - TWA particulate matter containing no asbestos and less	2 mg/m <sup>3</sup> - TWAEV containing no asbestos and less than 1% crystalline	5 mg/m³ - TWAEV

# K45501 - ULTRA SPEC EXT LOW LUSTRE FINISH WHITE

			than 1% crystalline silica	silica	
Zinc oxide	2 mg/m³ - TWA 10 mg/m³ - STEL	10 mg/m <sup>3</sup> - TWAEV 5 mg/m <sup>3</sup> - TWAEV 10 mg/m <sup>3</sup> - STEV			

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Hygiene Measures** 

# **Engineering Measures**

# Personal Protective Equipment Eye/Face Protection

Skin Protection Respiratory Protection

## Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Odorlittle or no odorOdor ThresholdNo information availableDensity (Ibs/gal)10.9 - 11.0Specific Gravity1.31 - 1.32pHNo information availableViscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableWater SolubilityNo information availableVapor PressureNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Flash Point (°C)Not applicableFlash Point (°C)Not applicable <th>Appearance</th> <th>liquid</th>	Appearance	liquid
Density (lbs/gal)10.9 - 11.0Specific Gravity1.31 - 1.32pHNo information availableViscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableWater SolubilityNo information availableEvaporation RateNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°F)32Freezing Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlash Point (°C)Not applicableFlash Point MethodNot applicableFlash Point Lower Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°	Odor	little or no odor
Specific Gravity1.31 - 1.32pHNo information availableViscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableWater SolubilityNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Flash Point (°C)Not applicableFlash Point (°C)Not applicable <tr< th=""><th></th><th></th></tr<>		
pHNo information availableViscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableWater SolubilityNo information availableEvaporation RateNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Flash Point (°C)Not applicableFlash Point (°C)Not applicable	Density (Ibs/gal)	10.9 - 11.0
Viscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableWater SolubilityNo information availableEvaporation RateNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Flash Point (°F)32Freezing Point (°C)Not applicableFlash Point (°C)Not applicable	Specific Gravity	
SolubilityNo information availableWater SolubilityNo information availableEvaporation RateNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°F)32Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlash Point LimitNot applicableLower Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Water SolubilityNo information availableEvaporation RateNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlash Point MethodNot applicableFlash Point LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available	Viscosity (cps)	
Evaporation RateNo information availableVapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50	Solubility	No information available
Vapor PressureNo information availableVapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles45 - 55Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50	Water Solubility	
Vapor DensityNo information availableWt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles45 - 55Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Freezing Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlawmability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available	Evaporation Rate	
Wt. % Solids45 - 55Vol. % Solids30 - 40Wt. % Volatiles45 - 55Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlawmability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available	•	
Vol. % Solids30 - 40Wt. % Volatiles45 - 55Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available	• •	
Wt. % Volatiles45 - 55Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)32Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)<50Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)0Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point (°C)Not applicableFlawmability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available	Vol. % Solids	
VOC Regulatory Limit (g/L)<50		
Boiling Point (°F)212Boiling Point (°C)100Freezing Point (°C)32Freezing Point (°C)0Flash Point (°C)0Flash Point (°C)Not applicableFlash Point (°C)Not applicableFlash Point (°C)Not applicableFlash Point (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Boiling Point (°C)100Freezing Point (°F)32Freezing Point (°C)0Flash Point (°F)Not applicableFlash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Freezing Point (°F)32Freezing Point (°C)0Flash Point (°F)Not applicableFlash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available	• • • •	
Freezing Point (°C)0Flash Point (°F)Not applicableFlash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Flash Point (°F)Not applicableFlash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Flash Point (°C)Not applicableFlash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		•
Flash Point MethodNot applicableFlammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Flammability (solid, gas)Not applicableUpper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Upper Explosion LimitNot applicableLower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Lower Explosion LimitNot applicableAutoignition Temperature (°F)No information available		
Autoignition Temperature (°F) No information available		
Autoignition Temperature (°C) No information available		
	Autoignition Temperature (°C)	No information available

Decomposition Temperature (°F) Decomposition Temperature (°C) Partition Coefficient (n-octanol/water) No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions To Avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility Of Hazardous Reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

# Product Information Information on likely routes of exposure

**Principal Routes of Exposure** 

Acute Toxicity Product Information Eye contact, skin contact and inhalation.

No information available

# Information on toxicological effects

Symptoms

No information available

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization:	No information available.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity

## The following values are calculated based on chapter 3.1 of the GHS document

#### ATEmix (oral)

48748 mg/kg

# **Component**

<u>Titanium dioxide</u> LD50 Oral: > 10000 mg/kg (Rat) <u>Kaolin</u> LD50 Oral: > 5000 mg/kg (Rat) <u>Zinc oxide</u> LD50 Oral: 5000 mg/kg (Rat) LC50 Inhalation (Dust): > 5700 mg/m<sup>3</sup> (Rat, 4 hr.)

# Chronic Toxicity

# Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

## **Product Information**

#### Acute Toxicity to Fish

No information available

# Acute Toxicity to Aquatic Invertebrates

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation / Accumulation**

No information available.

#### Mobility in Environmental Media

No information available.

# Ozone

No information available

# Component

#### Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

TDG	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated

# 15. REGULATORY INFORMATION

# International Inventories

TSCA: United States DSL: Canada Yes - All components are listed or exempt. Yes - All components are listed or exempt.

# National Pollutant Release Inventory (NPRI)

# NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical Name Zinc oxide <u>CAS-No</u> 1314-13-2 Weight % (max) 1 - 5%

PPE: -

NPRI Parts 1- 4 Listed

## NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

# WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

# 16. OTHER INFORMATION

Reactivity: 0

HMIS -	Health:	1
HMIS Legend		

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Flammability: 0

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 855-724-6802
Revision Date:	07-Apr-2016
Reason For Revision	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**