

SAFETY DATA SHEET

Revision Date: 11-Jan-2021

Revision Number: 8

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

BENJAMIN MOORE ULTRA SPEC 500 INTERIOR LOW SHEEN EGGSHELL BASE 4 N5374X N5374X Water thinned paint

Water thinned paint All Paint No information available

> Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not applicable

Other information No information available **WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Limestone	1317-65-3	15 - 20
Kaolin, calcined	92704-41-1	1 - 5

4. FIRST AID MEASURES		
General Advice	No hazards which require special first aid measures.	
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.	
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Inhalation	Move to fresh air. If symptoms persist, call a physician.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.	
Most Important Symptoms/Effects	None known.	
Notes To Physician	Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable

Flammability Limits In Air

Lower flammability limit: Upper flammability limit:

Health: 1

Flammability: 0

Instability: 0

Not applicable

Not applicable

Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly

NFPA

- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Limestone	N/E	15 mg/m³ - TWA
		5 mg/m³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

9. PHYSICAL AND CHEMICAL PROPERTIES

liquid

Appearance
Odor
Odor Threshold
Density (Ibs/gal)
Specific Gravity
Hq
Viscosity (cps)
Solubility(ies)
Water solubility
Evaporation Rate
Vapor pressure
Vapor density
Wt. % Solids
Vol. % Solids
Wt. % Volatiles
Vol. % Volatiles
VOC Regulatory Limit (g/L)
Boiling Point (°F)
Boiling Point (°C)
Freezing point (°F)
Freezing Point (°C)
Flash point (°F)
Flash Point (°C)
Method
Flammability (solid, gas)
Upper flammability limit:
Lower flammability limit:
Autoignition Temperature (°F)
Autoignition Temperature (°C)
Decomposition Temperature (°F)
Decomposition Temperature (°C)
Partition coefficient

little or no odor No information available 10.1 - 10.2 1.21 - 1.23 No information available 45 - 55 35 - 45 45 - 55 55 - 65 0 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity

Chemical Stability

Conditions to avoid

Not Applicable

Stable under normal conditions.

Prevent from freezing.

Incompatible Materials		No materials to be especially mentioned.	
Hazardous Decomposition Products		None under normal use.	
Possibility of hazardous reactions		None under normal conditions of use.	
1	1. TOXICOLOGIC	CAL INFORMATION	
Product Information			
Information on likely routes of e	xposure		
Principal Routes of Exposure	Eye contact, skin conta	ct and inhalation.	
Acute Toxicity			
Product Information	No information available		
Symptoms related to the physical, chemical and toxicological characteristics			
Symptoms	No information available		
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Eye contact Skin contact Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects Reproductive Effects Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure Other adverse effects Aspiration Hazard	skin and cause irritation May cause irritation of	slight skin irritation. Prolonged or repeated contact may dry n. respiratory tract. astrointestinal irritation, nausea, vomiting and diarrhea. e e. e. e. e. e. e. e. e. e. e. e.	

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

67590 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin, calcined	> 2000 mg/kg (Rat)	-	-
92704-41-1			

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated
	15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Limestone	Х	Х	Х

Legend

X - Listed

16. OTHER INFORMATION							
HMIS -	Health: 1	Flammability: 0	Reactivity: 0	PPE: -			
		-	-				
HMIS Legen	d						
0 - Minimal Ha	azard						
1 - Slight Haza	ard						
2 - Moderate H							
3 - Serious Ha	zard						
4 - Severe Haz	zard						
* - Chronic Ha	azard						
X - Consult vo	ur supervisor or SOP	for "Special" handling instruc	tions				

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	11-Jan-2021
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet