

# **SAFETY DATA SHEET**

Revision Date: 16-Feb-2021 Revision Number: 1

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ULTRA SPEC 500 INTERIOR PAINT - SATIN/PEARL BASE 4

Product Code T5454X
Alternate Product Code T5454X

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

<u>Manufacturer</u> <u>Emergency Telephone</u>

Benjamin Moore & Co. CHEMTREC: +1 703-741-5970 / 1-800-424-9300 101 Paragon Drive +1 703-527-3887 (outside US & Canada)

Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

### 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

### Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid Odor little or no odor

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Kaolin	1332-58-7	5 - 10
Nepheline syenite	37244-96-5	1 - 5
Titanium dioxide	13463-67-7	0.1 - 0.5
Ammonia	7664-41-7	0.1 - 0.5

### 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective equipment and precautions for firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 16-Feb-2021

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F) Not applicable Flash Point (°C) Not applicable

Method Not applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

### **NFPA** Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

### 7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	
Kaolin	TWA: 2 mg/m³ particulate matter	15 mg/m³ - TWA	
	containing no asbestos and <1%	5 mg/m³ - TWA	
	crystalline silica, respirable particulate		
	matter		
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	15 mg/m³ - TWA	
Ammonia	STEL: 35 ppm	50 ppm - TWA	
	TWA: 25 ppm	35 mg/m³ - TWA	

T5454X - ULTRA SPEC 500 INTERIOR PAINT - SATIN/PEARL BASE 4

Revision Date: 16-Feb-2021

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 9.25 - 9.35

 Specific Gravity
 1.11 - 1.13

pH No information available Viscosity (cps) No information available

Solubility(ies)

Water solubility

Evaporation Rate

Vapor pressure

Vapor density

No information available

 Wt. % Solids
 40 - 50

 Vol. % Solids
 30 - 40

 Wt. % Volatiles
 50 - 60

 Vol. % Volatiles
 60 - 70

 VOC Regulatory Limit (g/L)
 0

 Boiling Point (°F)
 212

Boiling Point (°C) 100

Freezing point (°C) 32

Freezing Point (°C) 0

Flash point (°F) Not applicable

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

### 10. STABILITY AND REACTIVITY

T5454X - ULTRA SPEC 500 INTERIOR PAINT - SATIN/PEARL BASE 4

Revision Date: 16-Feb-2021

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact**Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization No information available **Neurological Effects** No information available. **Mutagenic Effects** No information available. Reproductive Effects No information available. **Developmental Effects** No information available. Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. No information available. Other adverse effects No information available **Aspiration Hazard** 

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 443.8 mg/L

**Component Information** 

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
1332-58-7			
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			
Ammonia	= 350 mg/kg (Rat)	-	= 2000 ppm (Rat) 4 h
7664-41-7			

### **Chronic Toxicity**

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

### 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

#### **Acute Toxicity to Fish**

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

### Persistence / Degradability

No information available.

#### Bioaccumulation

There is no data for this product.

#### **Mobility in Environmental Media**

No information available.

#### Ozone

No information available

#### **Component Information**

### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 16-Feb-2021

environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

# 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

# Federal Regulations

### SARA 311/312 hazardous categorization

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

#### **California Proposition 65**

WARNING: Cancer and Reproductive Harm— www.P65warnings.ca.gov

#### State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Kaolin	X	X	X

## Legend

X - Listed

### 16. OTHER INFORMATION

HMIS -Health: 1 Flammability: 0 Reactivity: 0 PPE: -

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**Prepared By Product Stewardship Department** 

Benjamin Moore & Co.

101 Paragon Drive Montvale, NJ 07645 800-225-5554

16-Feb-2021 **Revision Date: Revision Summary** Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**