

# **Material Safety Data Sheet**

Revision Date: 25-Jan-2012

Revision Number: 3

**1. PRODUCT AND COMPANY IDENTIFICATION** 

Product Name Product Code Product Class Color MOORESTYLE INTERIOR ACRYLIC LATEX FLAT K56401 WATER THINNED PAINT White

### Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 201-573-9600 www.benjaminmoore.com Emergency Telephone Number(s) CANUTEC: 613-996-6666

## 2. COMPOSITION INFORMATION ON COMPONENTS

### Hazardous Components

Chemical Name	CAS-No	Weight % (max)
Calcium carbonate	471-34-1	15 - 40%
Titanium dioxide	13463-67-7	7 - 13%
Diatomaceous earth	61790-53-2	7 - 13%

## 3. HAZARDS IDENTIFICATION

Emergency Overview Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.				
Appearance liquid	<b>Odor</b> little or no odor			
Potential Health Effects				
Principal Routes of Exposure	Eye contact, skin contact and inhalation.			
Acute Effects Eyes	May cause slight irritation.			

Skin	Substance may cause slight skin irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic Effects	Repeated contact may cause allergic reactions in very susceptible persons.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known				
HMIS	Health: 1*	Flammability: 0	Reactivity: 0	PPE: -
HMIS Leger 0 - Minimal Ha 1 - Slight Haz 2 - Moderate 3 - Serious Ha 4 - Severe Ha * - Chronic H X - Consult yo handling instr	azard ard Hazard azard azard lazard bur supervisor or S.O	P. for "Special"		

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has choosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### 4. FIRST AID MEASURES

General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Notes To Physician	Treat symptomatically

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	No
Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method	Not applicable Not applicable Not applicable
Flammability Limits In Air Upper Explosion Limit Lower Explosion Limit	Not applicable Not applicable
NFPA Health: 1 Flammability: 0 In	nstability: 0 Special: -
NFPA Legend	

- 0 Not Hazardous
- 1 Slightly
- 1 Slightly
- 2 Moderate
- 3 High 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.		
Environmental Precautions	Prevent further leakage or spillage if safe to do so.		
Methods For Clean-Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
Other Information	None known		
7. HANDLING AND STORAGE			
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.		
Storago			
Storage	Keep container tightly closed. Keep out of the reach of children.		

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Limits

### **Hazardous Components**

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Calcium carbonate	N/E	10 mg/m <sup>3</sup> - TWA	N/E	N/E	10 mg/m <sup>3</sup> -
					TWAEV
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV	10 mg/m <sup>3</sup> -
			3 mg/m <sup>3</sup> - TWA		TWAEV
Diatomaceous earth	N/E	10 mg/m <sup>3</sup> - TWA	1.5 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV	6 mg/m <sup>3</sup> - TWAEV
		3 mg/m <sup>3</sup> - TWA	4 mg/m³ - TWA	containing no	
		Ŭ	Ū.	asbestos and less	
				than 1% crystalline	
				silica	
				3 mg/m <sup>3</sup> - TWAEV	
				containing no	
				asbestos and less	
				than 1% crystalline	
				silica	

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits N/E - Not established

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Density (Ibs/gal) Specific Gravity pH Viscosity (centistokes) Evaporation Rate Vapor Pressure Vapor Density Wt. % Solids Vol. % Solids Vol. % Solids Vol. % Volatiles Vol. % Volatiles VoC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C)	liquid little or no odor 10.90 - 11.0 1.30 - 1.31 Not available Not available Not available Not available 40 - 50 25 - 35 50 - 60 65 - 75 < 50 212 100
Freezing Point (°F) Freezing Point (°C)	32 0

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point (°F) Flash Point (°C) Flash Point Method Upper Explosion Limit Lower Explosion Limit Not applicable Not applicable Not applicable Not available Not available

## **10. STABILITY AND REACTIVITY**

Chemical StabilityStable under normal conditions.Conditions To AvoidPrevent from freezingIncompatible MaterialsNo materials to be especially mentionedHazardous Decomposition ProductsNone under normal use.Possibility Of Hazardous ReactionsHazardous polymerisation will not occur.

## **11. TOXICOLOGICAL INFORMATION**

Acute Toxicity

**Product** No information available

### Component

Calcium carbonate LD50 Oral: 6450 mg/kg (Rat)

<u>Titanium dioxide</u> LD50 Oral: > 10000 mg/kg (Rat) LD50 Dermal: > 10000 mg/m<sup>3</sup> (Rabbit) LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

### **Chronic Toxicity**

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
		2B - Possible		Listed
Titanium dioxide		Human		
		Carcinogen		

 Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

## **12. ECOLOGICAL INFORMATION**

### **Ecotoxicity Effects**

Product Acute Toxicity to Fish No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

## **12. ECOLOGICAL INFORMATION**

#### Acute Toxicity to Aquatic Plants No information available

### Component Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

### Acute Toxicity to Aquatic Invertebrates

No information available

### Acute Toxicity to Aquatic Plants

No information available

## **13. DISPOSAL CONSIDERATIONS**

Waste Disposal MethodDispose of in accordance with federal, state, provincial, and local regulations. Dry,<br/>empty containers may be recycled in a can recycling program. Local requirements<br/>may vary, consult your sanitation department or state-designated environmental<br/>protection agency for more disposal options.

14. TRANSPORT INFORMATION		
TDG	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	

**15. REGULATORY INFORMATION** 

# International Inventories

United States TSCAYes - All components are listed or exempt.Canada DSLYes - All components are listed or exempt.

### National Pollutant Release Inventory (NPRI)

### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

This product may contain trace amounts of (other) NPRI Parts I-4 reportable chemicals. Contact the preparer for further information.

## **15. REGULATORY INFORMATION**

### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

This product may contain trace amounts of (other) NPRI Part 5 reportable chemicals. Contact the preparer for further information.

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### WHMIS Hazard Class

D2A Very toxic materials



## **16. OTHER INFORMATION**

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture\_e.html.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 360 Route 206 - P.O. Box 4000 Flanders, NJ 07836 866-690-1961
Revision Date:	25-Jan-2012
Revision Summary	No information available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

