

# **Material Safety Data Sheet**

Revision Date: 20-Sep-2011 Revision Number: 2

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name MOORESTYLE EXTERIOR ACRYLIC LATEX FLAT PASTEL BASE

Product Code K5841B

Product Class WATER THINNED PAINT

Color

Manufacturer Emergency Telephone Number(s)

ΑII

Benjamin Moore & Co. CANUTEC: 613-996-6666 101 Paragon Drive

Montvale, NJ 07645 Phone: 201-573-9600 www.benjaminmoore.com

### 2. COMPOSITION INFORMATION ON COMPONENTS

**Hazardous Components** 

Chemical Name	CAS-No	Weight % (max)	
Titanium dioxide	13463-67-7	10 - 30%	
Limestone	1317-65-3	3 - 7%	
Zinc oxide	1314-13-2	1 - 5%	
Diatomaceous earth	61790-53-2	1 - 5%	
Silica, crystalline	14808-60-7	0.25 - 0.5%	

# 3. HAZARDS IDENTIFICATION

# **Emergency Overview**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.

Appearance liquid Odor little or no odor

**Potential Health Effects** 

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

# K5841B - MOORESTYLE EXTERIOR ACRYLIC LATEX FLAT PASTEL BASE

**Acute Effects** 

**Eyes** May cause slight irritation.

**Skin** Substance may cause slight skin irritation. **Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects Repeated contact may cause allergic reactions in very susceptible persons.

Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of

Revision Date: 20-Sep-2011

inhalation exposure to spray mist or dust from sanding the dried paint.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has choosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician if

necessary.

Notes To Physician Treat symptomatically

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** 

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

K5841B - MOORESTYLE EXTERIOR ACRYLIC LATEX FLAT PASTEL BASE

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 20-Sep-2011

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Upper Explosion LimitNot applicableLower Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

### **NFPA** Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Environmental Precautions** Prevent further leakage or spillage if safe to do so.

Methods For Clean-Up

Soak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

Other Information None known

# 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Revision Date: 20-Sep-2011

### **Exposure Limits**

**Hazardous Components** 

Chemical Name	ACGIH	Alberta	<b>British Columbia</b>	Ontario	Quebec
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV	10 mg/m <sup>3</sup> -
			3 mg/m <sup>3</sup> - TWA		TWAEV
Limestone	N/E	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	N/E	10 mg/m <sup>3</sup> -
		_	3 mg/m <sup>3</sup> - TWA		TWAEV
			20 mg/m <sup>3</sup> - STEL		
Zinc oxide	2 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWAEV	10 mg/m³ -
	10 mg/m <sup>3</sup> - STEL	5 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - STEL	10 mg/m <sup>3</sup> - STEV	TWAEV
		10 mg/m <sup>3</sup> - STEL			5 mg/m <sup>3</sup> - TWAEV
					10 mg/m <sup>3</sup> - STEV
Diatomaceous earth	N/E	10 mg/m <sup>3</sup> - TWA	1.5 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV	6 mg/m <sup>3</sup> - TWAEV
		3 mg/m³ - TWA	4 mg/m <sup>3</sup> - TWA	containing no	
				asbestos and less	
				than 1% crystalline	
				silica 3 mg/m³ - TWAEV	
				containing no	
				asbestos and less	
				than 1% crystalline	
				silica	
Silica, crystalline	0.025 mg/m <sup>3</sup> - TWA	0.1 mg/m <sup>3</sup> - TWA	0.025 mg/m <sup>3</sup> -	0.10 mg/m <sup>3</sup> -	0.1 mg/m <sup>3</sup> -
		_	TWA	TWAEV designated	TWAEV
				substance regulation	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odorlittle or no odorDensity (lbs/gal)10.3 - 10.4Specific Gravity1.20 - 1.25

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Date: 20-Sep-2011

Not available pН Not available Viscosity (centistokes) **Evaporation Rate** Not available **Vapor Pressure** Not available **Vapor Density** Not available Wt. % Solids 35 - 45 Vol. % Solids 25 - 35 55 - 65 Wt. % Volatiles Vol. % Volatiles 65 - 75 **VOC Regulatory Limit (g/L)** < 50 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing Point (°F) 32 Freezing Point (°C) 0

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Upper Explosion Limit

Lower Explosion Limit

Not applicable
Not applicable
Not available
Not available

# 10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing

Incompatible Materials No materials to be especially mentioned

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions Hazardous polymerisation will not occur.

# 11. TOXICOLOGICAL INFORMATION

Revision Date: 20-Sep-2011

# **Acute Toxicity**

#### **Product**

No information available

### Component

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat) LD50 Dermal: > 10000 mg/m³ (Rabbit)

LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Limestone

LD50 Oral: 6,450 mg/kg (Rat) vendor data Sensitization: No sensitizing effects known.

Zinc oxide

LD50 Oral: > 8437 mg/kg (Rat)

LC50 Inhalation (Dust): > 5700 mg/m³ (Rat, 4 hr.)

Silica, crystalline

LD50 Oral: 500 mg/kg (Rat) vendor data

### **Chronic Toxicity**

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
Titanium dioxide		2B - Possible		Listed
		Human		
		Carcinogen		
Silica, crystalline	A2 - Suspected	1 - Human	Known Human	Listed
	Human	Carcinogen	Carcinogen	
	Carcinogen		_	

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

Revision Date: 20-Sep-2011

# **Ecotoxicity Effects**

### **Product**

**Acute Toxicity to Fish** 

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

# **Acute Toxicity to Aquatic Plants**

No information available

# Component

**Acute Toxicity to Fish** 

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

# **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

# 13. DISPOSAL CONSIDERATIONS

### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Dry, empty containers may be recycled in a can recycling program. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

# 15. REGULATORY INFORMATION

### **International Inventories**

**United States TSCA** Yes - All components are listed or exempt.

### 15. REGULATORY INFORMATION

Revision Date: 20-Sep-2011

Canada DSL

Yes - All components are listed or exempt.

## **National Pollutant Release Inventory (NPRI)**

### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical Name CAS-No Weight % (max)

Zinc oxide 1314-13-2 1 - 5%

This product may contain trace amounts of (other) NPRI Parts I-4 reportable chemicals. Contact the preparer for further information.

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

This product may contain trace amounts of (other) NPRI Part 5 reportable chemicals. Contact the preparer for further information.

# **WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

D2A Very toxic materials



### 16. OTHER INFORMATION

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture\_e.html.

Prepared By Product Stewardship Department

Benjamin Moore & Co.

360 Route 206 - P.O. Box 4000

Flanders, NJ 07836

866-690-1961

K5841B - MOORESTYLE EXTERIOR ACRYLIC LATEX FLAT PASTEL BASE

Revision Date: 20-Sep-2011

Revision Date: 20-Sep-2011

Revision Summary No information available

### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

K5841B

**End of MSDS**