

Revision Date: 28-Jun-2023

**Revision Number:** 1

1. PRODUCT AND COMPANY IDENTIFICATION

# **Product Name**

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# WOODLUXE WATER-BASED WATERPROOFING STAIN & SEALER TRANSLUCENT MAHOGANY

K69160 K69160 LATEX STAIN Dark brown STAIN No information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com/en-ca

# Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

# Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

# **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1A
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B


# Label elements

# Danger

# Hazard statements

May cause an allergic skin reaction May cause genetic defects May damage fertility or the unborn child

### K69160 - WOODLUXE WATER-BASED WATERPROOFING STAIN & SEALER TRANSLUCENT MAHOGANY



Odor little or no odor

# **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention **Skin** 

IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

### **Precautionary Statements - Storage**

Store locked up

# Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

### Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Silica amorphous	7631-86-9	1 - 5%	-	-
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5%	-	-
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2- yl)-5-(1,1-dimethylethyl)-4-hydro		0.25 - 0.5%	-	-

### K69160 - WOODLUXE WATER-BASED WATERPROOFING STAIN & SEALER TRANSLUCENT MAHOGANY

xyphenyl]-1-oxopropyl]omega hydroxy-				
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-pip eridinyl) ester	41556-26-7	0.25 - 0.5%	-	-
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2- yl)-5-(1,1-dimethylethyl)-4-hydro xyphenyl]-1-oxopropyl]omega [3-[3-(2H-benzotriazol-2-yl)-5-(1, 1-dimethylethyl)-4-hydroxyphen yl]-1-oxoprop	104810-47-1	0.25 - 0.5%	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.1 - 0.25%	-	-
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidi nyl ester	82919-37-7	0.1 - 0.25%	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AI	D MEASURES
General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method Flammability Limits In Air Lower flammability limit: Upper flammability limit:	Not Applicable Not applicable Not applicable Not applicable Not applicable
NFPA Health hazards Flammability Stability Special:	2 0 0 Not Applicable

### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** 

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so.

**Other Information** 

**Environmental precautions** 

Methods for Cleaning Up

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

# 7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Storage

Keep container tightly closed. Keep out of the reach of children.

#### Incompatible Materials

No information available

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure Limits**

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Ethanol, 2-(2-butoxyethoxy)-	TWA: 10 ppm	-	-	TWA: 10 ppm	-
	inhalable fraction and				
	vapor				

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits N/E - Not established

#### **Engineering Measures**

**Hygiene Measures** 

#### Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields

Protective gloves and impervious clothing. Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold Density (lbs./gal) Specific Gravity pH Viscosity (cps) Solubility(ies) Water solubility Evaporation Rate Vapor pressure @20 °C (kPa) Relative vapor density liquid little or no odor No information available 8.3 - 8.7 0.99 - 1.05 No information available No information available

### K69160 - WOODLUXE WATER-BASED WATERPROOFING STAIN & SEALER TRANSLUCENT MAHOGANY

Wt. % Solids	15 - 25
Vol. % Solids	10 - 20
Wt. % Volatiles	75 - 85
Vol. % Volatiles	80 - 90
VOC Regulatory Limit (g/L)	< 100
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing point (°F)	32
Freezing Point (°C)	0
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

# 10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# **11. TOXICOLOGICAL INFORMATION**

Product Information Information on likely routes of exposure		
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity Product Information	No information available	
Symptoms related to the physical, chemical and toxicological characteristics		
Symptoms	No information available	
Delayed and immediate effects as well as chronic effe	cts from short and long-term exposure	

Eye contact	May cause slight irritation
Skin contact	Substance may cause slight skin irritation. Prolonged or
	repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	Suspected of causing genetic defects.
Reproductive Effects	May damage fertility or the unborn child.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

### **Component Information**

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica amorphous 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Ethanol, 2-(2-butoxyethoxy)- 112-34-5	= 5660 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidi nyl) ester 41556-26-7	= 2615 mg/kg (Rat)	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	> 5050 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	-

# Chronic Toxicity

### Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

# **Product Information**

### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates No information available

Acute Toxicity to Aquatic Plants

No information available

### Persistence / Degradability

No information available.

**<u>Bioaccumulation</u>** There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone Not applicable

# **Component Information**

### Acute Toxicity to Fish

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

### Acute Toxicity to Aquatic Invertebrates

Ethanol, 2-(2-butoxyethoxy)-EC50: 100 mg/L (Daphnia - 48 hr.) Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

### Acute Toxicity to Aquatic Plants

No information available

# **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

TDG	Not regulated
ICAO / IATA IMDG / IMO	Not regulated

# 15. REGULATORY INFORMATION

# International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

# National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None

### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

Chemical name	CAS No	Weight-%	NPRI Part 5
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5%	Listed

# WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

# 16. OTHER INFORMATION

MIS	
Health hazards	2*
Flammability	0
Reactivity:	0
Personal protection	-

#### HMIS Legend

Н

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	28-Jun-2023
Reason for revision	Not available

### <u>Disclaimer</u>

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

# **End of Safety Data Sheet**