

Revision Date: 05-Dec-2022 Revision Number: 3

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ELEMENT GUARD EXTERIOR PAINT SOFT GLOSS FINISH

BASE 2

Product Code K7652X
Alternate Product Code K7652X

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

**Manufactured For** 

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898

www.benjaminmoore.com/en-ca

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180

Phone: 1-866-708-9180 www.benjaminmoore.com

**Emergency Telephone** 

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

CANUTEC: 613-996-6666 (Transport Emergency Only)

## 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B

### Label elements

### Danger

#### Hazard statements

May cause genetic defects

May damage fertility or the unborn child



Appearance liquid

Odor little or no odor

Revision Date: 05-Dec-2022

## **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

# **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Titanium dioxide	13463-67-7	7 - 13%	-	-
Zinc oxide	1314-13-2	0.5 - 1%	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.1 - 0.25%	-	-
1-Methyl-2-pyrrolidinone	872-50-4	0.1 - 0.25%	-	-

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

# 4. FIRST AID MEASURES

**General Advice** 

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 05-Dec-2022

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable
Not applicable

**NFPA** 

Health hazards 2
Flammability 0
Stability 0

Special: Not Applicable

#### NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

**Environmental precautions**See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 05-Dec-2022

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

Chemical name	ACGIH TLV	Alberta	<b>British Columbia</b>	Ontario	Quebec
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup>	10 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWAEV
	nanoscale respirable		3 mg/m³ - TWA		
	particulate matter				
	TWA: 2.5 mg/m <sup>3</sup>				
	finescale respirable				
	particulate matter				
Zinc oxide	STEL: 10 mg/m <sup>3</sup>	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWAEV
	respirable particulate	10 mg/m <sup>3</sup> - STEL	10 mg/m <sup>3</sup> - STEL	10 mg/m <sup>3</sup> - STEL	5 mg/m³ - TWAEV
	matter				10 mg/m³ - STEV
	TWA: 2 mg/m <sup>3</sup>				
	respirable particulate				
	matter				
	TWA: 0.5 mg/m <sup>3</sup> Ba				
	As Barium soluble				
	compounds				
	[RR-00049-7]				

1-Methyl-2-pyrrolidinone 400 mg/m<sup>3</sup> - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas.

Revision Date: 05-Dec-2022

Personal Protective Equipment

**Eye/Face Protection Skin Protection** 

**Respiratory Protection** 

Safety glasses with side-shields

Protective gloves and impervious clothing.

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures** Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** liquid

Odor little or no odor

**Odor Threshold** No information available

Density (lbs/gal) 9.3 - 9.7**Specific Gravity** 1.11 - 1.17

Hq No information available

No information available Viscosity (cps) No information available Solubility(ies) Water solubility No information available No information available **Evaporation Rate** 

Vapor pressure @20 °C (kPa) No information available

Relative vapor density No information available

35 - 45 Wt. % Solids 25 - 35 Vol. % Solids Wt. % Volatiles 55 - 65 Vol. % Volatiles 65 - 75VOC Regulatory Limit (g/L) < 50 **Boiling Point (°F)** 212

**Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C)

Flash point (°F) Not applicable Flash Point (°C) Not applicable Method Not applicable

Not applicable Flammability (solid, gas) Upper flammability limit: Not applicable

Lower flammability limit: Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

**Product Information** 

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eve contact** May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Revision Date: 05-Dec-2022

Inhalation May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. No information available.

**Sensitization**Neurological Effects
No information available.
No information available.

Mutagenic EffectsSuspected of causing genetic defects.Reproductive EffectsMay damage fertility or the unborn child.

Developmental EffectsNo information available.Target organ effectsNo information available.STOT - single exposureNo information available.STOT - repeated exposureNo information available.

Other adverse effects Aspiration Hazard No information available. No information available. Revision Date: 05-Dec-2022

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 91656 mg/kg

### **Component Information**

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	> 5050 mg/kg (Rat)	> 10000 mg/kg(Rabbit)	-
1-Methyl-2-pyrrolidinone 872-50-4	= 3914 mg/kg (Rat)	= 8 g/kg (Rabbit)	> 5.1 mg/L (Rat)4 h

# **Chronic Toxicity**

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide		

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes:
 "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is

bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

## **Product Information**

### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

### **Acute Toxicity to Aquatic Plants**

No information available

# Persistence / Degradability

No information available.

#### Bioaccumulation

There is no data for this product.

## **Mobility in Environmental Media**

No information available.

#### Ozone

Not applicable

## **Component Information**

#### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

### **Acute Toxicity to Aquatic Invertebrates**

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

### **Acute Toxicity to Aquatic Plants**

No information available

# 13. DISPOSAL CONSIDERATIONS

#### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 05-Dec-2022

## 14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

Revision Date: 05-Dec-2022

## 15. REGULATORY INFORMATION

#### **International Inventories**

TSCA: United States

PSL: Canada

Yes - All components are listed or exempt.

No - Not all of the components are listed.

One or more component is listed on NDSL.

# National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical nameCAS NoWeight-%NPRI Parts 1- 41-Methyl-2-pyrrolidinone872-50-40.1 - 0.25%Listed

### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

None

### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

### 16. OTHER INFORMATION

#### **HMIS**

Health hazards 2\*
Flammability 0
Reactivity: 0
Personal protection -

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a

Revision Date: 05-Dec-2022

registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Issuing Date 18-Apr-2022

**Revision Date:** 05-Dec-2022 **Reason for revision** Not available

#### **Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**