



# Benjamin Moore®

## SAFETY DATA SHEET

Revision Date: 06-Oct-2023

Revision Number: 2

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** BENJAMIN MOORE ADVANCE WATERBORNE INTERIOR  
ALKYD PEARL BASE 3

**Product Code** K7923X

**Alternate Product Code** K7923X

**Product Class** Water thinned paint

**Color** All

**Recommended use** Paint

**Restrictions on use** No information available

#### **Manufactured For**

Benjamin Moore & Co., Limited  
8775 Keele Street  
Concord ON L4K 2N1  
Phone: 1-800-361-5898  
www.benjaminmoore.com/en-ca

#### **Manufacturer**

Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-866-708-9180  
www.benjaminmoore.com

#### **Emergency Telephone**

CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
+1 703-527-3887 (outside US & Canada)

### 2. HAZARDS IDENTIFICATION

#### **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization

Category 1

#### **Label elements**

##### **Warning**

##### **Hazard statements**

May cause an allergic skin reaction



**Appearance** liquid

**Odor** little or no odor

**Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray  
Contaminated work clothing should not be allowed out of the workplace  
Wear protective gloves

**Skin**

IF ON SKIN: Wash with plenty of soap and water  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other information**

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

**3. COMPOSITION INFORMATION ON COMPONENTS**

| Chemical name    | CAS No     | Weight-% |
|------------------|------------|----------|
| Kaolin           | 1332-58-7  | 5 - 10   |
| Titanium dioxide | 13463-67-7 | 1 - 5    |

**4. FIRST AID MEASURES**

**General Advice**

No hazards which require special first aid measures.

**Eye Contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.

|  |  |
|--|--|
| <b>Inhalation</b>                      | Move to fresh air. If symptoms persist, call a physician.                                      |
| <b>Ingestion</b>                       | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| <b>Most Important Symptoms/Effects</b> | May cause allergic skin reaction.  |
| <b>Notes To Physician</b>              | Treat symptomatically.   |

## 5. FIRE-FIGHTING MEASURES

|  |  |
|--|--|
| <b>Suitable Extinguishing Media</b>                          | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                |
| <b>Protective equipment and precautions for firefighters</b> | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| <b>Specific Hazards Arising From The Chemical</b>            | Closed containers may rupture if exposed to fire or extreme heat.  |
| <b>Sensitivity to mechanical impact</b>                      | No   |
| <b>Sensitivity to static discharge</b>                       | No   |
| <b>Flash Point Data</b>                                      |  |
| Flash point (°F)   | Not Applicable   |
| Flash Point (°C)   | Not applicable   |
| Method   | Not applicable   |
| <b>Flammability Limits In Air</b>                            |  |
| Lower flammability limit:                                    | Not applicable   |
| Upper flammability limit:                                    | Not applicable   |
| <b>NFPA</b>  |  |
| Health hazards   | 1  |
| Flammability   | 0  |
| Stability  | 0  |
| Special:   | Not Applicable   |

### NFPA Legend

0 - Not Hazardous  
1 - Slightly  
2 - Moderate  
3 - High  
4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## 6. ACCIDENTAL RELEASE MEASURES

|                                  |   |
|----------------------------------|---|
| <b>Personal Precautions</b>      | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.                          |
| <b>Other Information</b>         | Prevent further leakage or spillage if safe to do so.   |
| <b>Environmental precautions</b> | See Section 12 for additional Ecological Information.   |
| <b>Methods for Cleaning Up</b>   | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |

## 7. HANDLING AND STORAGE

|                               |  |
|-------------------------------|--|
| <b>Handling</b>               | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
| <b>Storage</b>                | Keep container tightly closed. Keep out of the reach of children.  |
| <b>Incompatible Materials</b> | No information available   |

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

| Chemical name    | ACGIH TLV  | OSHA PEL  |
|------------------|--|---|
| Kaolin           | TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter             | 15 mg/m <sup>3</sup> - TWA<br>5 mg/m <sup>3</sup> - TWA |
| Titanium dioxide | TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter<br>TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter | 15 mg/m <sup>3</sup> - TWA                              |

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits  
 OSHA - Occupational Safety & Health Administration Exposure Limits  
 N/E - Not Established

|                                      |  |
|--------------------------------------|--|
| <b>Engineering Measures</b>          | Ensure adequate ventilation, especially in confined areas.   |
| <b>Personal Protective Equipment</b> |  |
| <b>Eye/Face Protection</b>           | Safety glasses with side-shields.  |
| <b>Skin Protection</b>               | Protective gloves and impervious clothing.   |
| <b>Respiratory Protection</b>        | In case of insufficient ventilation wear suitable respiratory equipment.   |
| <b>Hygiene Measures</b>              | Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                |                          |
|--------------------------------|--------------------------|
| Appearance                     | liquid                   |
| Odor                           | little or no odor        |
| Odor Threshold                 | No information available |
| Density (lbs./gal)             | 9.7 - 10.1               |
| Specific Gravity               | 1.16 - 1.21              |
| pH                             | No information available |
| Viscosity (cps)                | No information available |
| Solubility(ies)                | No information available |
| Water solubility               | No information available |
| Evaporation Rate               | No information available |
| Vapor pressure @20 °C (kPa)    | No information available |
| Relative vapor density         | No information available |
| Wt. % Solids                   | 40 - 50                  |
| Vol. % Solids                  | 30 - 40                  |
| Wt. % Volatiles                | 50 - 60                  |
| Vol. % Volatiles               | 60 - 70                  |
| VOC Regulatory Limit (g/L)     | < 50                     |
| Boiling Point (°F)             | 212                      |
| Boiling Point (°C)             | 100                      |
| Freezing point (°F)            | 32                       |
| Freezing Point (°C)            | 0                        |
| Flash point (°F)               | Not Applicable           |
| Flash Point (°C)               | Not applicable           |
| Method                         | Not applicable           |
| Flammability (solid, gas)      | Not applicable           |
| Upper flammability limit:      | Not applicable           |
| Lower flammability limit:      | Not applicable           |
| Autoignition Temperature (°F)  | No information available |
| Autoignition Temperature (°C)  | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient          | No information available |

## 10. STABILITY AND REACTIVITY

|                                    |  |
|------------------------------------|--|
| Reactivity                         | Not Applicable                           |
| Chemical Stability                 | Stable under normal conditions.          |
| Conditions to avoid                | Prevent from freezing.                   |
| Incompatible Materials             | No materials to be especially mentioned. |
| Hazardous Decomposition Products   | None under normal use.                   |
| Possibility of hazardous reactions | None under normal conditions of use.     |

## 11. TOXICOLOGICAL INFORMATION

**Product Information**

**Information on likely routes of exposure**

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity**

**Product Information** No information available

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Eye contact** May cause slight irritation.  
**Skin contact** Prolonged skin contact may cause skin irritation and/or dermatitis. May cause sensitization by skin contact.  
**Inhalation** May cause irritation of respiratory tract.  
**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
**Sensitization** May cause an allergic skin reaction  
**Neurological Effects** No information available.  
**Mutagenic Effects** No information available.  
**Reproductive Effects** No information available.  
**Developmental Effects** No information available.  
**Target organ effects** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Other adverse effects** No information available.  
**Aspiration Hazard** No information available

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 50740 mg/kg

**Component Information** Caution - This mixture contains a substance not yet fully tested

| Chemical name                  | Oral LD50             | Dermal LD50          | Inhalation LC50 |
|--------------------------------|-----------------------|----------------------|-----------------|
| Kaolin<br>1332-58-7            | > 5000 mg/kg ( Rat )  | > 5000 mg/kg ( Rat ) | -               |
| Titanium dioxide<br>13463-67-7 | > 10000 mg/kg ( Rat ) | -                    | -               |

**Chronic Toxicity**

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name    | IARC                           | NTP | OSHA   |
|------------------|--------------------------------|-----|--------|
| Titanium dioxide | 2B - Possible Human Carcinogen |     | Listed |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

**Legend**

IARC - International Agency for Research on Cancer  
NTP - National Toxicity Program  
OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

**Product Information**

**Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Persistence / Degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

No information available.

**Ozone**

Not applicable

**Component Information**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**

**Acute Toxicity to Aquatic Plants**

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method** Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

**ICAO / IATA** Not regulated

**IMDG / IMO** Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA: United States** Yes - All components are listed or exempt.  
**DSL: Canada** No - Not all of the components are listed.  
One or more component is listed on NDSL.

### Federal Regulations

#### SARA 311/312 Hazard Categories

|                                   |     |
|-----------------------------------|-----|
| Acute health hazard               | Yes |
| Chronic Health Hazard             | No  |
| Fire hazard                       | No  |
| Sudden release of pressure hazard | No  |
| Reactive Hazard                   | No  |

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

None


#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

### US State Regulations

#### California Proposition 65

 **WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Toluene which are known to the State of



California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**U.S. State Right-to-Know Regulations**

| Chemical name    | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Water            |               |            | X            |
| Kaolin           | X             | X          | X            |
| Limestone        | X             | X          | X            |
| Titanium dioxide | X             | X          | X            |

**Legend**

X - Listed

**16. OTHER INFORMATION**

**HMIS**

|                     |   |
|---------------------|---|
| Health hazards      | 1 |
| Flammability        | 0 |
| Reactivity:         | 0 |
| Personal protection | - |

**HMIS Legend**

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Prepared By** Product Stewardship Department  
 Benjamin Moore & Co.  
 101 Paragon Drive  
 Montvale, NJ 07645  
 800-225-5554

Revision Date: 06-Oct-2023  
Revision Summary: Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**