

SAFETY DATA SHEET

Revision Date: 09-Jun-2017 Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SUPER SPEC HP ACRYLIC METAL PRIMER WHITE

Product Code KP0401
Alternate Product Code KP0401

Product Class WATER THINNED PAINT

Color White Recommended use Primers

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive

Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com **Emergency Telephone Number(s)**

CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Carcinogenicity Category 2

Label elements

Warning

Hazard statements

Suspected of causing cancer

Revision Date: 09-Jun-2017



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

If exposed or concerned get medical attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Titanium dioxide	13463-67-7	7 - 13%
Kaolin	1332-58-7	5 - 10%
Talc	14807-96-6	3 - 7%
Zinc phosphate	7779-90-0	0.5 - 1%
Zinc oxide	1314-13-2	0.5 - 1%
Sodium C14-C16 olefin sulfonate	68439-57-6	0.25 - 0.5%
Sodium nitrite	7632-00-0	0.1 - 0.25%

4. FIRST AID MEASURES

General AdviceNo hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

KP0401 - SUPER SPEC HP ACRYLIC METAL PRIMER WHITE

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And Precautions For As in

Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 09-Jun-2017

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)Not applicableFlash Point (°C)Not applicableFlash Point MethodNot applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental PrecautionsSee Section 12 for additional Ecological Information.

Methods For Clean-Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 09-Jun-2017

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWA	10 mg/m³ - TWA	10 mg/m ³ - TWAEV
		-	3 mg/m ³ - TWA		_
Kaolin	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m ³ - TWA	2 mg/m³ - TWA	5 mg/m³ - TWAEV
Talc	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m ³ - TWA	2 mg/m³ - TWA	3 mg/m³ - TWAEV
Zinc oxide	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m ³ - TWA	2 mg/m³ - TWA	10 mg/m ³ - TWAEV
	10 mg/m ³ - STEL	5 mg/m³ - TWAEV			
					10 mg/m ³ - STEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face ProtectionSafety glasses with side-shields.

Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

KP0401 - SUPER SPEC HP ACRYLIC METAL PRIMER WHITE

No information available

Revision Date: 09-Jun-2017

 Density (lbs/gal)
 10.7 - 11.1

 Specific Gravity
 1.28 - 1.33

pHNo information availableViscosity (cps)No information availableSolubilityNo information availableWater SolubilityNo information availableEvaporation RateNo information availableVapor PressureNo information available

 Wt. % Solids
 50 - 60

 Vol. % Solids
 40 - 50

 Wt. % Volatiles
 40 - 50

 Vol. % Volatiles
 50 - 60

 VOC Regulatory Limit (g/L)
 < 100</td>

 Boiling Point (°F)
 212.0

 Boiling Point (°C)
 100.0

Freezing Point (°F)

Freezing Point (°C)

No information available

No information available

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Flammability (solid, gas)

Upper Explosion Limit

Lower Explosion Limit

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Vapor Density

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

KP0401 - SUPER SPEC HP ACRYLIC METAL PRIMER WHITE

Acute Toxicity

Product Information No information available

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Revision Date: 09-Jun-2017

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization: No information available. No information available. **Neurological Effects Mutagenic Effects** No information available. **Reproductive Effects** No information available. **Developmental Effects** No information available. **Target Organ Effects** No information available. No information available. STOT - single exposure STOT - repeated exposure No information available. Other adverse effects No information available. **Aspiration Hazard** No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 29154 mg/kg

Component

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

Zinc oxide

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Dust): > 5700 mg/m³ (Rat, 4 hr.)

Sodium nitrite

LD50 Oral: 180 mg/kg (Rat)

LC50 Inhalation (Dust): 5.5 mg/m³ (Rat, 4 hr.)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	
	2B - Possible Human Carcinogen		
Titanium dioxide	_		

KP0401 - SUPER SPEC HP ACRYLIC METAL PRIMER WHITE

Revision Date: 09-Jun-2017

	2A - Probable Human Carcinogen	
Sodium nitrite		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 09-Jun-2017

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical Name	CAS-No	Weight % (max)	NPRI Parts 1-4
Zinc phosphate	7779-90-0	0.5 - 1%	Listed
Zinc oxide	1314-13-2	0.5 - 1%	Listed
Sodium nitrite	7632-00-0	0.1 - 0.25%	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Revision Date: 09-Jun-2017

16. OTHER INFORMATION

Health: 1* Flammability: 0 PPE: -HMIS -Reactivity: 0

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked questions-questions posees-eng.php.

Prepared By Product Stewardship Department

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

855-724-6802

Revision Date: 09-Jun-2017 Reason For Revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET