

SAFETY DATA SHEET

Revision Date: 04-Oct-2018 Revision Number: 5

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SUPER KOTE 5000 ACRYLIC LATEX SATIN DEEP BASE

Product Code 1160-34
Alternate Product Code TR3434

Product Class WATER THINNED PAINT

Color All Recommended use Paint

Restrictions on use No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. CHEMTREC (US): 800-424-9300 101 Paragon Drive CHEMTREC (outside US): (703)-527-3887

Montvale, NJ 07645 Phone: 1-866-708-9180 coronadopaint.com

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid Odor little or no odor

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Kaolin	1332-58-7	10
Titanium dioxide	13463-67-7	10
Limestone	1317-65-3	5
Propanoic acid, 2-methyl-, monoester with	25265-77-4	5
2,2,4-trimethyl-1,3-pentanediol		

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Revision Date: 04-Oct-2018

Protective Equipment And Precautions For As in any fire, wear self-contained breathing apparatus

Firefighters pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

1160-34 - SUPER KOTE 5000 ACRYLIC LATEX SATIN

DEEP BASE

Revision Date: 04-Oct-2018

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable
Not applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautions See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Kaolin	2 mg/m³ - TWA	15 mg/m³ - TWA
		5 mg/m³ - TWA
Titanium dioxide	10 mg/m³ - TWA	15 mg/m³ - TWA
Limestone	N/E	15 mg/m³ - TWA
		5 mg/m³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

1160-34 - SUPER KOTE 5000 ACRYLIC LATEX SATIN DEEP BASE

Revision Date: 04-Oct-2018

N/E - Not Established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 9.9 - 10.0

 Specific Gravity
 1.19 - 1.21

pH No information available
Viscosity (cps) No information available
Solubility(ies) No information available
Water solubility No information available
Evaporation Rate No information available
Vapor pressure @20 °C (kPa) No information available

Vapor pressure @20 °C (kPa)No information availableVapor densityNo information available

Wt. % Solids 40 - 50 Vol. % Solids 25 - 35 Wt. % Volatiles 50 - 60 Vol. % Volatiles 65 - 75 VOC Regulatory Limit (g/L) < 100 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing Point (°F) 32 Freezing Point (°C)

Flash Point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

1160-34 - SUPER KOTE 5000 ACRYLIC LATEX SATIN

DEEP BASE

Revision Date: 04-Oct-2018

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions

None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation.

Skin contact Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization No information available No information available. **Neurological Effects Mutagenic Effects** No information available. **Reproductive Effects** No information available. No information available. **Developmental Effects** Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available. No information available **Aspiration Hazard**

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 95573 mg/kg

 ATEmix (dermal)
 1261834 mg/kg

Component Information

Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

1160-34 - SUPER KOTE 5000 ACRYLIC LATEX SATIN DEEP BASE

Revision Date: 04-Oct-2018

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

DEEP BASE

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 04-Oct-2018

environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.

Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

Revision Date: 04-Oct-2018

US State Regulations

California Proposition 65

⚠ WARNING: Cancer and Reproductive Harm
— www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Kaolin	X	X	X
Titanium dioxide	X	X	X
Limestone	X	X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS -Health: 1 Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 04-Oct-2018

1160-34 - SUPER KOTE 5000 ACRYLIC LATEX SATIN DEEP BASE

Revision Date: 04-Oct-2018

Revision Summary

Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET