

# SAFETY DATA SHEET

Revision Date: 15-Aug-2023

**Revision Number: 1** 

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# CORONADO FINAL TOUCH FLAT - PASTEL BASE 136-32

UA8032 Water thinned paint All Paint No information available

# Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.coronadopaint.com

#### Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

Category 1A

2. HAZARDS IDENTIFICATION

# **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity

# Label elements

Danger		
Hazard statements May cause cancer		
Appearance liquid	Odor	little or no odor

# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

# Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

# **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

# Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%
Limestone	1317-65-3	20 - 25
Titanium dioxide	13463-67-7	10 - 15
Kaolin, calcined	92704-41-1	5 - 10
Silica, crystalline	14808-60-7	0.1 - 0.5

# 4. FIRST AID MEASURES

General Advice	No hazards which require special first aid measures.	
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.	
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Inhalation	Move to fresh air. If symptoms persist, call a physician.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.	
Most Important Symptoms/Effects	None known.	
Notes To Physician	Treat symptomatically.	

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	Not Applicable Not applicable Not applicable
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health hazards Flammability Stability Special:	1 0 0 Not Applicable
NFPA Legend 0 - Not Hazardous 1 - Slightly	

2 - Moderate

3 - High

4 - Severe

П

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES		
Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.	
Other Information	Prevent further leakage or spillage if safe to do so.	
Environmental precautions	See Section 12 for additional Ecological Information.	
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.	

# 7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	
Limestone	-	15 mg/m³ - TWA	
		5 mg/m³ - TWA	
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable	15 mg/m³ - TWA	
	particulate matter		
	TWA: 2.5 mg/m <sup>3</sup> finescale respirable		
	particulate matter		
Silica, crystalline	TWA: 0.025 mg/m <sup>3</sup> respirable	TWA: 50 μg/m³	
	particulate matter	TWA: 50 µg/m <sup>3</sup> excludes	
		construction work, agricultural	
		operations, and exposures that result	
		from the processing of sorptive clays	
		(vacated) TWA: 0.1 mg/m <sup>3</sup> respirable	
		dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		respirable fraction	

# Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor liquid little or no odor

**Odor Threshold** Density (lbs./gal) **Specific Gravity** pН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) **Relative vapor density** Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

No information available 11.5 - 11.9 1.37 - 1.43 No information available 50 - 60 30 - 40 40 - 50 60 - 70 < 50 212 100 32 0 Not Applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

**11. TOXICOLOGICAL INFORMATION** 

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity	
Product Information	No information available
Symptoms related to the physi	cal, chemical and toxicological characteristics
Symptoms	No information available
Delayed and immediate effects	as well as chronic effects from short and long-term exposure
Eye contact Skin contact	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects Reproductive Effects Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure Other adverse effects Aspiration Hazard	May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. No information available No information available. No information available. Causes damage to organs through prolonged or repeated exposure if inhaled. No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

95846 mg/kg

**Component Information** 

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Kaolin, calcined 92704-41-1	> 2000 mg/kg (Rat)	-	-

# Chronic Toxicity

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	IARC NTP	
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		
	1 - Human Carcinogen	Known	Х
Silica, crystalline			

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes:

"No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

# **Product Information**

# Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

# Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

# Mobility in Environmental Media

No information available.

# Ozone

Not applicable

# **Component Information**

# Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

# Acute Toxicity to Aquatic Invertebrates

No information available

# Acute Toxicity to Aquatic Plants

No information available

# **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.	
	14. TRANSPORT INFORMATION	
DOT	Not regulated	
ΙCAO / ΙΑΤΑ	Not regulated	
IMDG / IMO	Not regulated	
	15. REGULATORY INFORMATION	

# International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

# Federal Regulations

# SARA 311/312 Hazard Categories

)
s
)
)
)
,

# SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

None

<u>Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)</u> This product contains the following HAPs:

None

# US State Regulations

# California Proposition 65

**WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause of the reproductive harm. For more information go to

# www.P65Warnings.ca.gov

# U.S. State Right-to-Know

# **Regulations**

Chemical name	Massachusetts	New Jersey	Pennsylvania
Water			Х
Limestone	X	Х	Х
Titanium dioxide	Х	X	Х
Silica, crystalline	X	X	Х

#### Legend

X - Listed

# **16. OTHER INFORMATION**

#### HMIS

Health hazards	1*
Flammability	0
Reactivity:	0
Personal protection	-

#### HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

#### **Prepared By**

Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554

Revision Date:	15-Aug-2023
Revision Summary	Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

# **End of Safety Data Sheet**