



LENMAR[®]

SAFETY DATA SHEET

Revision Date: 02-Jun-2016

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name QUICKSTAIN GLAZE CLEAR BASE
Product Code 1GZ-1200FR
Alternate Product Code HL8237
Product Class FINISH COATING
Color Clear
Recommended use Topcoat
Restrictions on use No information available

Manufactured For
Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
lenmar-coatings.ca

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
lenmar-coatings.com

Emergency Telephone Number(s)
CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Acute toxicity - Inhalation (Vapors)	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2
Physical hazard not otherwise classified	Category 1

Label elements

Danger

Hazard statements

Toxic if inhaled
 Causes skin irritation
 Causes serious eye irritation
 May cause cancer
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Highly flammable liquid and vapor
 Risk of spontaneous combustion

**Appearance** liquid**Odor** solvent**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection
 Do not breathe dust/fume/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces, no smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool
 Immediately after use, place rags, steel wool or waste used with this product in a sealed water-filled metal container or lay flat to dry.

Precautionary Statements - Response

If exposed or concerned get medical attention

Eyes

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists get medical attention

Skin

If skin irritation occurs get medical attention

If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water

Wash contaminated clothing before reuse

Inhalation

If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or physician

Ingestion

If swallowed immediately call a POISON CENTER or physician

Do NOT induce vomiting

Fire

In case of fire use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Heptane	142-82-5	15 - 40%
VM&P naphtha	64742-89-8	10 - 30%
Talc	14807-96-6	10 - 30%
n-Butyl acetate	123-86-4	7 - 13%
Octane	111-65-9	1 - 5%
Ethanol	64-17-5	1 - 5%
Silica, crystalline	14808-60-7	0.1 - 0.25%

4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

Protection Of First-Aiders

Use personal protective equipment.

Most Important Symptoms/Effects

No information available.

Notes To Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.

Suitable Extinguishing Media

Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective Equipment And Precautions For Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Hazardous Combustion Products

Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.

Specific Hazards Arising From The Chemical

Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity To Mechanical Impact

No

Sensitivity To Static Discharge

Yes

Flash Point Data

Flash Point (°F)	27
Flash Point (°C)	-3
Flash Point Method	PMCC

Flammability Limits In Air

Lower Explosion Limit	Not available
Upper Explosion Limit	Not available

NFPA **Health:** 2 **Flammability:** 3 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods For Clean-Up

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Heptane	400 ppm - TWA 500 ppm - STEL	400 ppm - TWA 1640 mg/m ³ - TWA 500 ppm - STEL 2050 mg/m ³ - STEL	400 ppm - TWA 500 ppm - STEL	400 ppm - TWA 500 ppm - STEL	400 ppm - TWAEV 1640 mg/m ³ - TWAEV 500 ppm - STEV 2050 mg/m ³ - STEV
Talc	2 mg/m ³ - TWA	2 mg/m ³ - TWA	2 mg/m ³ - TWA	2 mg/m ³ - TWA	3 mg/m ³ - TWAEV
n-Butyl acetate	150 ppm - TWA 200 ppm - STEL	150 ppm - TWA 713 mg/m ³ - TWA 200 ppm - STEL 950 mg/m ³ - STEL	20 ppm - TWA	150 ppm - TWA 200 ppm - STEL	150 ppm - TWAEV 713 mg/m ³ - TWAEV 200 ppm - STEV 950 mg/m ³ - STEV
Octane	300 ppm - TWA	300 ppm - TWA 1400 mg/m ³ - TWA	300 ppm - TWA	300 ppm - TWA	300 ppm - TWAEV 1400 mg/m ³ - TWAEV 375 ppm - STEV 1750 mg/m ³ - STEV
Ethanol	1000 ppm - STEL	1000 ppm - TWA 1880 mg/m ³ - TWA	1000 ppm - STEL	1000 ppm - STEL	1000 ppm - TWAEV 1880 mg/m ³ - TWAEV
Silica, crystalline	0.025 mg/m ³ - TWA	0.025 mg/m ³ - TWA	0.025 mg/m ³ - TWA	0.10 mg/m ³ - TWA	0.1 mg/m ³ - TWAEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 Alberta - Alberta Occupational Exposure Limits
 British Columbia - British Columbia Occupational Exposure Limits
 Ontario - Ontario Occupational Exposure Limits
 Quebec - Quebec Occupational Exposure Limits
 N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin Protection

Protective gloves and impervious clothing.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Odor

solvent

Odor Threshold

No information available

Density (lbs/gal)

7.0 - 7.3

Specific Gravity

0.84 - 0.88

pH

No information available

Viscosity (cps)

No information available

Solubility

No information available

Water Solubility

No information available

Evaporation Rate

No information available

Vapor Pressure

No information available

Vapor Density

No information available

Wt. % Solids	15 - 25
Vol. % Solids	5 - 15
Wt. % Volatiles	75 - 85
Vol. % Volatiles	85 - 95
VOC Regulatory Limit (g/L)	<680
Boiling Point (°F)	167
Boiling Point (°C)	75
Freezing Point (°F)	No information available
Freezing Point (°C)	No information available
Flash Point (°F)	27
Flash Point (°C)	-3
Flash Point Method	PMCC
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	Not applicable
Lower Explosion Limit	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure

Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Contact with eyes may cause irritation.
Skin contact	May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.
Inhalation	Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
Ingestion	Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
Sensitization:	No information available.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	Possible risk of impaired fertility. Possible risk of harm to the unborn child.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	May cause disorder and damage to the. Respiratory system. Central nervous system (CNS).
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled. Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint. May cause disorder and damage to the. Central nervous system (CNS).
Other adverse effects	No information available.
Aspiration Hazard	May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	56716 mg/kg
ATEmix (dermal)	4441 mg/kg
ATEmix (inhalation-dust/mist)	266 mg/L
ATEmix (inhalation-vapor)	10 mg/L

Component

Heptane

LC50 Inhalation (Vapor): 103000 mg/m³ (Rat, 4 hr.)

n-Butyl acetate

LD50 Oral: 10768 mg/kg (Rat)

LD50 Dermal: > 17600 mg/kg (Rabbit)
 LC50 Inhalation (Vapor): ppm (Rat, 4 hr.)
 Sensitization: non-sensitizing (guinea pig)
Ethanol
 LD50 Oral: mg/kg (Rat)
 LC50 Inhalation (Vapor): ppm (Rat, 10 hr.)
Silica, crystalline
 LD50 Oral: 500 mg/kg (Rat)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP
Silica, crystalline	1 - Human Carcinogen	Known Human Carcinogen

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

Legend

IARC - International Agency for Research on Cancer
 NTP - National Toxicity Program
 OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component**Acute Toxicity to Fish**

n-Butyl acetate
LC50: 18 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

n-Butyl acetate
EC50: 72.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

n-Butyl acetate
EC50: 674.7 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

TDG

Proper Shipping Name	Paint
Hazard Class	3
UN-No	UN1263
Packing Group	II
Description	UN1263, Paint, , 3, II

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)**NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Parts 1- 4</u>
Heptane	142-82-5	15 - 40%	Listed
n-Butyl acetate	123-86-4	7 - 13%	Listed
Octane	111-65-9	1 - 5%	Listed
Ethanol	64-17-5	1 - 5%	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Part 5</u>
VM&P naphtha	64742-89-8	10 - 30%	Listed
n-Butyl acetate	123-86-4	7 - 13%	Listed
Ethanol	64-17-5	1 - 5%	Listed

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 3 Reactivity: 0 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-sem/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.

101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 02-Jun-2016
Reason For Revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET