



LENMAR[®]

SAFETY DATA SHEET

Revision Date: 01-Jul-2016

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name QUICKSTAIN LACQUER WIPING STAIN DARK CHERRY
Product Code 1LS-1215FR
Alternate Product Code HL7067
Product Class STAIN
Color Red brown
Recommended use Stain
Restrictions on use No information available

Manufactured For
Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
lenmar-coatings.ca

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
lenmar-coatings.com

Emergency Telephone Number(s)
CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 2
Physical hazard not otherwise classified	Category 1

Label elements

Danger

Hazard statements

Harmful if swallowed
Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May damage fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor
Reactive flammable material



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear eye/face protection
Do not breathe dust/fume/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces, no smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

If exposed or concerned get medical attention

Eyes

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists get medical attention

Skin

If skin irritation occurs get medical attention

If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water

Wash contaminated clothing before reuse

Inhalation

If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion

If swallowed immediately call a POISON CENTER or physician

Do NOT induce vomiting

Rinse mouth

Fire

In case of fire use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

Other hazards

May cause allergic skin reaction

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
2-Butoxyethanol	111-76-2	15 - 40%
Propylene glycol monomethyl ether acetate	108-65-6	10 - 30%
Distillates, petroleum, hydrotreated light	64742-47-8	10 - 30%
Stoddard solvent	8052-41-3	3 - 7%
n-Butyl acetate	123-86-4	3 - 7%
Acetone	67-64-1	1 - 5%
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl ester (DINP)	68515-48-0	1 - 5%
cellulose, nitrate	9004-70-0	1 - 5%
VM&P naphtha	64742-89-8	1 - 5%
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 5%
1,2,4-Trimethylbenzene	95-63-6	1 - 5%
Isopropyl alcohol	67-63-0	1 - 5%
2-Methoxy-1-propanol acetate	70657-70-4	0.25 - 0.5%
Carbon black	1333-86-4	0.1 - 0.25%

4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

Protection Of First-Aiders

Use personal protective equipment.

Most Important Symptoms/Effects May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.

Suitable Extinguishing Media Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Hazardous Combustion Products Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.

Specific Hazards Arising From The Chemical Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge Yes

Flash Point Data

Flash Point (°F) 47
Flash Point (°C) 8
Flash Point Method PMCC

Flammability Limits In Air

Lower Explosion Limit Not available
Upper Explosion Limit Not available

NFPA **Health:** 3 **Flammability:** 3 **Instability:** 1 **Special:** Not Applicable

NFPA Legend

0 - Not Hazardous
1 - Slightly
2 - Moderate
3 - High
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Remove all sources of ignition. Take precautions to

prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods For Clean-Up

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
2-Butoxyethanol	20 ppm - TWA	20 ppm - TWA 97 mg/m ³ - TWA	20 ppm - TWA	20 ppm - TWA	20 ppm - TWAEV 97 mg/m ³ - TWAEV
Propylene glycol monomethyl ether acetate	N/E	N/E	50 ppm - TWA 75 ppm - STEL	50 ppm - TWA 270 mg/m ³ - TWA	N/E
Distillates, petroleum, hydrotreated light	N/E	N/E	200 mg/m ³ - TWA Skin absorption can contribute to overall	N/E	N/E

			exposure.		
Stoddard solvent	100 ppm - TWA	100 ppm - TWA 572 mg/m ³ - TWA	290 mg/m ³ - TWA 580 mg/m ³ - STEL	525 mg/m ³ - TWA	100 ppm - TWAEV 525 mg/m ³ - TWAEV
n-Butyl acetate	150 ppm - TWA 200 ppm - STEL	150 ppm - TWA 713 mg/m ³ - TWA 200 ppm - STEL 950 mg/m ³ - STEL	20 ppm - TWA	150 ppm - TWA 200 ppm - STEL	150 ppm - TWAEV 713 mg/m ³ - TWAEV 200 ppm - STEV 950 mg/m ³ - STEV
Acetone	250 ppm - TWA 500 ppm - STEL	500 ppm - TWA 1200 mg/m ³ - TWA 750 ppm - STEL 1800 mg/m ³ - STEL	250 ppm - TWA 500 ppm - STEL	500 ppm - TWA 750 ppm - STEL	500 ppm - TWAEV 1190 mg/m ³ - TWAEV 1000 ppm - STEV 2380 mg/m ³ - STEV
Isopropyl alcohol	200 ppm - TWA 400 ppm - STEL	200 ppm - TWA 492 mg/m ³ - TWA 400 ppm - STEL 984 mg/m ³ - STEL	200 ppm - TWA 400 ppm - STEL	200 ppm - TWA 400 ppm - STEL	400 ppm - TWAEV 985 mg/m ³ - TWAEV 500 ppm - STEV 1230 mg/m ³ - STEV
2-Methoxy-1-propanol acetate	N/E	N/E	20 ppm - TWA 40 ppm - STEL	N/E	N/E
Carbon black	3 mg/m ³ - TWA	3.5 mg/m ³ - TWA	3 mg/m ³ - TWA	3 mg/m ³ - TWA	3.5 mg/m ³ - TWAEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 Alberta - Alberta Occupational Exposure Limits
 British Columbia - British Columbia Occupational Exposure Limits
 Ontario - Ontario Occupational Exposure Limits
 Quebec - Quebec Occupational Exposure Limits
 N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin Protection

Protective gloves and impervious clothing.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Odor

solvent

Odor Threshold

No information available

Density (lbs/gal)

7.4 - 7.7

Specific Gravity

0.88 - 0.92

pH

No information available

Viscosity (cps)

No information available

Solubility

No information available

Water Solubility

No information available

Evaporation Rate

No information available

Vapor Pressure

No information available

Vapor Density

No information available

Wt. % Solids

5 - 15

Vol. % Solids

5 - 15

Wt. % Volatiles

85 - 95

Vol. % Volatiles

85 - 95

VOC Regulatory Limit (g/L)

< 850

Boiling Point (°F)	248
Boiling Point (°C)	120
Freezing Point (°F)	No information available
Freezing Point (°C)	No information available
Flash Point (°F)	47
Flash Point (°C)	8
Flash Point Method	PMCC
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	Not applicable
Lower Explosion Limit	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Contact with eyes may cause irritation. Vapor may cause irritation.

Skin contact May cause skin irritation and/or dermatitis. Prolonged skin

Inhalation

contact may defat the skin and produce dermatitis. Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

Ingestion

Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Sensitization:

May cause an allergic skin reaction.

Neurological Effects

No information available.

Mutagenic Effects

No information available.

Reproductive Effects

May damage fertility or the unborn child.

Developmental Effects

No information available.

Target Organ Effects

No information available.

STOT - single exposure

May cause disorder and damage to the. Respiratory system. Central nervous system (CNS).

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled. May cause disorder and damage to the. Liver. Kidney. Spleen. Blood. Central nervous system (CNS). Causes damage to organs through prolonged or repeated exposure if swallowed. Causes damage to organs through prolonged or repeated exposure in contact with skin.

Other adverse effects

No information available.

Aspiration Hazard

May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	1344 mg/kg
ATEmix (dermal)	2228 mg/kg
ATEmix (inhalation-dust/mist)	81.3 mg/L
ATEmix (inhalation-vapor)	27 mg/L

Component

2-Butoxyethanol

LD50 Oral: 470 mg/kg (Rat)

LD50 Dermal: 220 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 450 ppm (Rat, 4 hr.)

Propylene glycol monomethyl ether acetate

LD50 Oral: 8532 mg/kg (Rat)

LD50 Dermal: > 5000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 4345 ppm

Distillates, petroleum, hydrotreated light

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3,000 mg/kg (Rabbit)

Stoddard solvent

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3160 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 6.1 mg/L (Rat)

n-Butyl acetate

LD50 Oral: 10768 mg/kg (Rat)

LD50 Dermal: > 17600 mg/kg (Rabbit)

LC50 Inhalation (Vapor): ppm (Rat, 4 hr.)

Sensitization: non-sensitizing (guinea pig)

Acetone

LD50 Oral: 5800 mg/kg (Rat)

Solvent naphtha, petroleum, light aromatic

LD50 Oral: 8400 mg/kg (Rat)

1,2,4-Trimethylbenzene

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Vapor): 18000 mg/m³ (Rat, 4 hr.)

Isopropyl alcohol

LD50 Oral: mg/kg (Rat)

LD50 Dermal: mg/kg (Rabbit)

LC50 Inhalation (Vapor): ppm (Rat)

2-Methoxy-1-propanol acetate

LD50 Dermal: > 5000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 100 ppm (Rat)

Carbon black

LD50 Oral: > 15400 mg/kg (Rat)

LD50 Dermal: > 3000 mg/kg (Rabbit)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	IARC	NTP
Carbon black	2B - Possible Human Carcinogen	

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

n-Butyl acetate

LC50: 18 mg/L (Fathead Minnow - 96 hr.)

Acetone

LC50: 8300 (Bluegill - 96 hr.) mg/L

Acute Toxicity to Aquatic Invertebrates

n-Butyl acetate

EC50: 72.8 mg/L (Daphnia magna - 48 hr.)

Acetone

EC50: 12600 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

n-Butyl acetate

EC50: 674.7 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

TDG

Proper Shipping Name

Paint

Hazard Class

3

UN-No

UN1263

Packing Group

II

Description

UN1263, Paint, , 3, II

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

TSCA: United States

Yes - All components are listed or exempt.

DSL: Canada

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Parts 1- 4</u>
2-Butoxyethanol	111-76-2	15 - 40%	Listed
Propylene glycol monomethyl ether acetate	108-65-6	10 - 30%	Listed
n-Butyl acetate	123-86-4	3 - 7%	Listed
Acetone	67-64-1	1 - 5%	Listed
1,2,4-Trimethylbenzene	95-63-6	1 - 5%	Listed
Isopropyl alcohol	67-63-0	1 - 5%	Listed
2-Methoxy-1-propanol acetate	70657-70-4	0.25 - 0.5%	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Part 5</u>
2-Butoxyethanol	111-76-2	15 - 40%	Listed
Propylene glycol monomethyl ether acetate	108-65-6	10 - 30%	Listed
Distillates, petroleum, hydrotreated light	64742-47-8	10 - 30%	Listed
Stoddard solvent	8052-41-3	3 - 7%	Listed
n-Butyl acetate	123-86-4	3 - 7%	Listed
VM&P naphtha	64742-89-8	1 - 5%	Listed
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 5%	Listed
1,2,4-Trimethylbenzene	95-63-6	1 - 5%	Listed
Isopropyl alcohol	67-63-0	1 - 5%	Listed

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 3* Flammability: 3 Reactivity: 1 PPE: -

HMIS Legend

0 - Minimal Hazard

1 - Slight Hazard

- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 01-Jul-2016
Reason For Revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET