
COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

4

CAS# 108-65-6
PROPYLENE GLYCOL m-METHYL ETHER ACETATE
PCT BY WT: 3 - 7 VAPOR PRESSURE: 3.700 MMHG @ 20C
EXPOSURE LIMIT:
LC50: Inhalation (Rat, Male) - > 4345 ppm/6 Hrs
LD50: Oral (Rat, Female)- 8.5 g/kg

5 n-BUTYL ACETATE

CAS# 123-86-4
ACETIC ACID BUTYL ESTER
PCT BY WT: 10 - 30 VAPOR PRESSURE: 15.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 150 ppm
ACGIH TLV/STEL: STEL 200 ppm
OSHA PEL/TWA: TWA 150 ppm
OSHA STEL: 200 ppm
LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs
LD50: Oral (Rat)- 14,130 mg/kg

6 ETHYLENE GLYCOL N-BUTYL ETHER

CAS# 111-76-2
2-BUTOXYETHANOL
PCT BY WT: 1 - 5 VAPOR PRESSURE: .660 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: 20 ppm TWA (Skin)
OSHA PEL/TWA: 50 ppm TWA (Skin)
LC50: Inhalation (Mouse) - 700 ppm/7 Hrs
LD50: Oral (Rat)- 1746 mg/kg
CA PROPOSITION 65: No

7 ACETONE

CAS# 67-64-1
2-PROPANONE
PCT BY WT: 3 - 7 VAPOR PRESSURE: 185.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 500 ppm
ACGIH TLV/STEL: STEL 750 ppm
OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

8 ISOBUTYL ALCOHOL

CAS# 78-83-1
2-METHYL-1-PROPANOL
PCT BY WT: 1 - 5 VAPOR PRESSURE: 8.800 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: 50 ppm - TWA

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

OSHA PEL/TWA: 100 ppm - TWA
LC50: Inhalation (Rat)- >8000 ppm/4 Hour (s)
LD50: Oral (Rat): 2.5-6.4 g/kg

9

CAS# 64-17-5
ETHYL ALCOHOL
PCT BY WT: 7 - 13 VAPOR PRESSURE: 57.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 1000 ppm
OSHA PEL/TWA: TWA 1000 ppm
LD50: Oral (Rat) - 7060 mg/kg

10

CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: 1 - 5 VAPOR PRESSURE: 7.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 100 ppm
ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains one or more reported or suspected reproductive
toxins.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Exposure to liquid may cause mild eye irritation. Symptoms
may include stinging, tearing, and redness.
SKIN: Prolonged or repeated skin contact may cause drying, cracking
or irritation.
INHALATION: High vapor concentrations may cause drowsiness and
irritation of the eyes or respiratory tract.
INGESTION: Swallowing small amounts of this product during normal
handling is not likely to cause harmful effects, but
swallowing large amounts may be harmful.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

XYLENE: Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver & kidney damage, nausea, and vomiting in humans. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B).

TOLUENE: Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness.

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

ACETONE: Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, convulsions, and coma with possible liver and kidney injury. Based on animal data and structure-activity relationships, this product is NOT expected to cause nervous system damage.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: Seek medical advice.

NOTE TO PHYSICIAN:
Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : OSHA Flammable Liquid - Class 1B
Flashpoint : 2.2 °C
Explosion Level : Low - .1
High - 36.0

EXTINGUISHING MEDIA

Water spray, dry chemical, carbon dioxide (CO2), alcohol foam

SPECIAL FIRE-FIGHTING PROCEDURES

Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. The fire could easily be spread by the use of water in an area where the water could not be contained. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS

FLAMMABLE. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent build-up of vapors or gases to explosive concentrations.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor respirator approved by NIOSH for protection against chemicals in Section 2 &/or 15.

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State : LIQUID
Vapor Pressure : 185.00
Vapor Density : 4.60
Boiling Point Range : Lower - 56.1 °C
Higher - 172.7 °C
Specific Gravity : 1.098
VOC - Total (gm/l) : 628.02
Evaporation Rate : 14.400 (n-Butyl Acetate = 1)
Volatile by Weight : 58.4992
Volatile by Volume : 75.9780

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

This product is stable.

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

High temperatures.

HAZARDOUS DECOMPOSITION

May form: carbon dioxide and carbon monoxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. Mix with compatible chemical, which is less flammable and incinerate.

Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

TDG HAZARD CLASS : 3
TDG PACKAGING GROUP : PG II
TDG SHIPPING NAME : PAINT
UN/NA NUMBER : UN1263

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

CANADA DSL - YES - All components are listed or exempt.

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 03/25/2009
Last Revision Date : 03/24/2009
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 3 Flammability- 3
 Reactivity- 2

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by these regulations.

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-804K

per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.