



# LENMAR<sup>®</sup>

## SAFETY DATA SHEET

Revision Date: 11-Mar-2019

Revision Number: 2

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** ULTRALAQ PRECATALYZED WHITE TOPCOATS GLOSS  
**Product Code** 1M-808FR  
**Alternate Product Code** HL1801  
**Product Class** LACQUER  
**Color** White  
**Recommended use** Topcoat  
**Restrictions on use** No information available

**Manufactured For**

Benjamin Moore & Co., Limited  
8775 Keele Street  
Concord ON L4K 2N1  
Phone: 1-800-361-5898  
lenmar-coatings.ca

**Manufacturer**

Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-866-708-9180  
lenmar-coatings.com

**Emergency Telephone**

CANUTEC: 613-996-6666

### 2. HAZARDS IDENTIFICATION

**Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2
Physical hazard not otherwise classified	Category 1

**Label elements**

**Danger**

**Hazard statements**

Causes skin irritation  
Causes serious eye damage  
May cause cancer  
May damage fertility or the unborn child  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor  
Reactive flammable material



**Appearance** liquid

**Odor** solvent

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

Immediately call a POISON CENTER or doctor/physician

**Skin**

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other information**

No information available

**3. COMPOSITION INFORMATION ON COMPONENTS**

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Titanium dioxide	13463-67-7	10 - 30%	-	-
n-Butyl acetate	123-86-4	10 - 30%	-	-
Ethanol	64-17-5	7 - 13%	-	-
Acetone	67-64-1	5 - 10%	-	-
Propylene glycol monomethyl ether acetate	108-65-6	3 - 7%	-	-
VM&P naphtha	64742-89-8	1 - 5%	-	-
cellulose, nitrate	9004-70-0	1 - 5%	-	-
Isopropyl alcohol	67-63-0	1 - 5%	-	-
Isobutyl alcohol	78-83-1	1 - 5%	-	-
Xylene	1330-20-7	1 - 5%	-	-
2-Butoxyethanol	111-76-2	1 - 5%	-	-
Aluminum hydroxide	21645-51-2	1 - 5%	-	-
Toluene	108-88-3	1 - 5%	-	-
Ethyl benzene	100-41-4	0.25 - 0.5%	-	-
Octane	111-65-9	0.1 - 0.25%	-	-
Heptane	142-82-5	0.1 - 0.25%	-	-
2-Methoxy-1-propanol acetate	70657-70-4	0.1 - 0.25%	-	-

**Confidential Business Information note**

\*The exact percentage (concentration) of composition has been withheld as a trade secret

**4. FIRST AID MEASURES**

**General Advice**

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.

**Skin Contact**

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Inhalation**

Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
<b>Protection Of First-Aiders</b>	Use personal protective equipment.
<b>Most Important Symptoms/Effects</b>	No information available.
<b>Notes To Physician</b>	Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
<b>Suitable Extinguishing Media</b>	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective Equipment And Precautions For Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Hazardous combustion products</b>	Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.
<b>Specific Hazards Arising From The Chemical</b>	Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.
<b>Sensitivity To Mechanical Impact</b>	No
<b>Sensitivity To Static Discharge</b>	Yes
<b>Flash Point Data</b>	
Flash Point (°F)	36
Flash Point (°C)	2
Method	PMCC
<b>Flammability Limits In Air</b>	
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**NFPA**    **Health:** 2                      **Flammability:** 3                      **Instability:** 1                      **Special:** Not Applicable

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions**

Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

**Other Information**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

**Environmental precautions**

See Section 12 for additional Ecological Information.

**Methods for Cleaning Up**

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

**7. HANDLING AND STORAGE**

**Handling**

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach

of children.

**Incompatible Materials**

Incompatible with strong acids and bases and strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Limits**

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA 3 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV
n-Butyl acetate	150 ppm - TWA 200 ppm - STEL	150 ppm - TWA 713 mg/m <sup>3</sup> - TWA 200 ppm - STEL 950 mg/m <sup>3</sup> - STEL	20 ppm - TWA	150 ppm - TWA 200 ppm - STEL	150 ppm - TWAEV 713 mg/m <sup>3</sup> - TWAEV 200 ppm - STEV 950 mg/m <sup>3</sup> - STEV
Ethanol	STEL: 1000 ppm	1000 ppm - TWA 1880 mg/m <sup>3</sup> - TWA	1000 ppm - STEL	1000 ppm - STEL	1000 ppm - TWAEV 1880 mg/m <sup>3</sup> - TWAEV
Acetone	250 ppm - TWA 500 ppm - STEL	500 ppm - TWA 1200 mg/m <sup>3</sup> - TWA 750 ppm - STEL 1800 mg/m <sup>3</sup> - STEL	250 ppm - TWA 500 ppm - STEL	500 ppm - TWA 750 ppm - STEL	500 ppm - TWAEV 1190 mg/m <sup>3</sup> - TWAEV 1000 ppm - STEV 2380 mg/m <sup>3</sup> - STEV
Propylene glycol monomethyl ether acetate	N/E	N/E	50 ppm - TWA 75 ppm - STEL	50 ppm - TWA 270 mg/m <sup>3</sup> - TWA	N/E
Isopropyl alcohol	200 ppm - TWA 400 ppm - STEL	200 ppm - TWA 492 mg/m <sup>3</sup> - TWA 400 ppm - STEL 984 mg/m <sup>3</sup> - STEL	200 ppm - TWA 400 ppm - STEL	200 ppm - TWA 400 ppm - STEL	400 ppm - TWAEV 985 mg/m <sup>3</sup> - TWAEV 500 ppm - STEV 1230 mg/m <sup>3</sup> - STEV
Isobutyl alcohol	50 ppm - TWA	50 ppm - TWA 152 mg/m <sup>3</sup> - TWA	50 ppm - TWA	50 ppm - TWA	50 ppm - TWAEV 152 mg/m <sup>3</sup> - TWAEV
Xylene	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 434 mg/m <sup>3</sup> - TWA 150 ppm - STEL 651 mg/m <sup>3</sup> - STEL	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 150 ppm - STEL	100 ppm - TWAEV 434 mg/m <sup>3</sup> - TWAEV 150 ppm - STEV 651 mg/m <sup>3</sup> - STEV
2-Butoxyethanol	20 ppm - TWA	20 ppm - TWA 97 mg/m <sup>3</sup> - TWA	20 ppm - TWA	20 ppm - TWA	20 ppm - TWAEV 97 mg/m <sup>3</sup> - TWAEV
Aluminum hydroxide	1 mg/m <sup>3</sup> - TWA	N/E	1.0 mg/m <sup>3</sup> - TWA	1 mg/m <sup>3</sup> - TWA	N/E
Toluene	20 ppm - TWA	50 ppm - TWA 188 mg/m <sup>3</sup> - TWA Substance may be readily absorbed through intact skin	20 ppm - TWA Adverse reproductive effect	20 ppm - TWA	50 ppm - TWAEV 188 mg/m <sup>3</sup> - TWAEV Skin absorption can contribute to overall exposure.
Ethyl benzene	20 ppm - TWA	100 ppm - TWA 434 mg/m <sup>3</sup> - TWA 125 ppm - STEL 543 mg/m <sup>3</sup> - STEL	20 ppm - TWA	20 ppm - TWA	100 ppm - TWAEV 434 mg/m <sup>3</sup> - TWAEV 125 ppm - STEV 543 mg/m <sup>3</sup> - STEV
Octane	300 ppm - TWA	300 ppm - TWA 1400 mg/m <sup>3</sup> - TWA	300 ppm - TWA	300 ppm - TWA	300 ppm - TWAEV 1400 mg/m <sup>3</sup> - TWAEV 375 ppm - STEV 1750 mg/m <sup>3</sup> - STEV
Heptane	400 ppm - TWA 500 ppm - STEL	400 ppm - TWA 1640 mg/m <sup>3</sup> - TWA 500 ppm - STEL 2050 mg/m <sup>3</sup> - STEL	400 ppm - TWA 500 ppm - STEL	400 ppm - TWA 500 ppm - STEL	400 ppm - TWAEV 1640 mg/m <sup>3</sup> - TWAEV 500 ppm - STEV 2050 mg/m <sup>3</sup> - STEV
2-Methoxy-1-propanol acetate	N/E	N/E	20 ppm - TWA 40 ppm - STEL	N/E	N/E

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists  
Alberta - Alberta Occupational Exposure Limits  
British Columbia - British Columbia Occupational Exposure Limits  
Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits  
N/E - Not established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles

**Skin Protection**

Protective gloves and impervious clothing.

**Respiratory Protection**

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	liquid
<b>Odor</b>	solvent
<b>Odor Threshold</b>	No information available
<b>Density (lbs/gal)</b>	9.1 - 9.2
<b>Specific Gravity</b>	1.09 - 1.11
<b>pH</b>	No information available
<b>Viscosity (cps)</b>	No information available
<b>Solubility(ies)</b>	No information available
<b>Water solubility</b>	No information available
<b>Evaporation Rate</b>	No information available
<b>Vapor pressure @20 °C (kPa)</b>	No information available
<b>Vapor density</b>	No information available
<b>Wt. % Solids</b>	35 - 45
<b>Vol. % Solids</b>	20 - 30
<b>Wt. % Volatiles</b>	55 - 65
<b>Vol. % Volatiles</b>	70 - 80
<b>VOC Regulatory Limit (g/L)</b>	<680
<b>Boiling Point (°F)</b>	136
<b>Boiling Point (°C)</b>	58
<b>Freezing Point (°F)</b>	No information available
<b>Freezing Point (°C)</b>	No information available
<b>Flash Point (°F)</b>	36
<b>Flash Point (°C)</b>	2
<b>Method</b>	PMCC
<b>Flammability (solid, gas)</b>	Not applicable
<b>Upper flammability limit:</b>	Not applicable
<b>Lower flammability limit:</b>	Not applicable
<b>Autoignition Temperature (°F)</b>	No information available
<b>Autoignition Temperature (°C)</b>	No information available
<b>Decomposition Temperature (°F)</b>	No information available
<b>Decomposition Temperature (°C)</b>	No information available

Partition coefficient No information available

## 10. STABILITY AND REACTIVITY

**Reactivity** Not Applicable

**Chemical Stability** Stable under normal conditions. Hazardous polymerisation does not occur.

**Conditions to avoid** Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.

**Incompatible Materials** Incompatible with strong acids and bases and strong oxidizing agents.

**Hazardous Decomposition Products** Thermal decomposition can lead to release of irritating gases and vapors.

**Possibility of hazardous reactions** None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Product Information Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

### Acute Toxicity Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** Severely irritating to eyes. May cause burns. Risk of serious damage to eyes.

**Skin contact** May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.

**Inhalation** Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

**Ingestion** Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury,



**Sensitization**  
**Neurological Effects**  
**Mutagenic Effects**  
**Reproductive Effects**  
**Developmental Effects**  
**Target organ effects**  
**STOT - single exposure**

**STOT - repeated exposure**

**Other adverse effects**  
**Aspiration Hazard**

possibly progressing to death.  
No information available.  
No information available.  
No information available.  
May damage fertility or the unborn child.  
No information available.  
No information available.  
May cause disorder and damage to the. Respiratory system. Central nervous system.  
Causes damage to organs through prolonged or repeated exposure if inhaled. May cause disorder and damage to the. liver. kidney. spleen. blood. Central nervous system. Causes damage to organs through prolonged or repeated exposure.  
No information available.  
May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 6109 mg/kg  
**ATEmix (dermal)** 8860 mg/kg  
**ATEmix (inhalation-dust/mist)** 52.2 mg/L  
**ATEmix (inhalation-vapor)** 60.9 mg/L

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
n-Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	-
Ethanol 64-17-5	= 7060 mg/kg ( Rat )	-	= 124.7 mg/L ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Propylene glycol monomethyl ether acetate 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	-
VM&P naphtha 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-
cellulose, nitrate 9004-70-0	5 g/kg ( Rat )	-	-
Isopropyl alcohol 67-63-0	= 1870 mg/kg ( Rat )	= 4059 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h
Isobutyl alcohol 78-83-1	= 2460 mg/kg ( Rat )	= 3400 mg/kg ( Rabbit )	> 6.5 mg/L ( Rat ) 4 h
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
2-Butoxyethanol 111-76-2	= 1300 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.9 mg/L (Rat) 3H
Aluminum hydroxide 21645-51-2	> 5000 mg/kg ( Rat )	-	-

Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Ethyl benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Octane 111-65-9	-	-	= 118 g/m <sup>3</sup> ( Rat ) 4 h = 25260 ppm ( Rat ) 4 h
Heptane 142-82-5	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> ( Rat ) 4 h

Component n-Butyl acetate  
123-86-4 ( 10 - 30% )

Sensitization  
non-sensitizing ( guinea pig )

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
Titanium dioxide	2B - Possible Human Carcinogen	
Ethyl benzene	2B - Possible Human Carcinogen	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

### Product Information

#### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### Bioaccumulation

There is no data for this product.

#### Mobility in Environmental Media

No information available.

**Ozone**

No information available

**Component Information**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

n-Butyl acetate

LC50: 18 mg/L (Fathead Minnow - 96 hr.)

Acetone

LC50: 8300 (Bluegill - 96 hr.) mg/L

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**

n-Butyl acetate

EC50: 72.8 mg/L (Daphnia magna - 48 hr.)

Acetone

EC50: 12600 mg/L (Daphnia magna - 48 hr.)

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

**Acute Toxicity to Aquatic Plants**

n-Butyl acetate

EC50: 674.7 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**Empty Container Warning**

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

**TDG**

Proper Shipping Name	PAINT
Hazard class	3
UN-No.	UN1263
Packing Group	II
Description	UN1263, PAINT, 3, II

**ICAO / IATA**

Contact the preparer for further information.

**IMDG / IMO**

Contact the preparer for further information.

15. REGULATORY INFORMATION

**International Inventories**

**TSCA: United States** Yes - All components are listed or exempt.  
**DSL: Canada** Yes - All components are listed or exempt.

**National Pollutant Release Inventory (NPRI)**

**NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>NPRI Parts 1- 4</u>
Isopropyl alcohol	67-63-0	1 - 5%	Listed
Isobutyl alcohol	78-83-1	1 - 5%	Listed
Xylene	1330-20-7	1 - 5%	Listed
2-Butoxyethanol	111-76-2	1 - 5%	Listed
Toluene	108-88-3	1 - 5%	Listed
Ethyl benzene	100-41-4	0.25 - 0.5%	Listed

**NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>NPRI Part 5</u>
n-Butyl acetate	123-86-4	10 - 30%	Listed
Ethanol	64-17-5	7 - 13%	Listed
Propylene glycol monomethyl ether acetate	108-65-6	3 - 7%	Listed
VM&P naphtha	64742-89-8	1 - 5%	Listed
Isopropyl alcohol	67-63-0	1 - 5%	Listed
Xylene	1330-20-7	1 - 5%	Listed
2-Butoxyethanol	111-76-2	1 - 5%	Listed
Toluene	108-88-3	1 - 5%	Listed

**WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

## 16. OTHER INFORMATION

HMIS - Health: 2\* Flammability: 3 Reactivity: 1 PPE: -

### HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/ewh-semtd/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semtd/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision Date:** 11-Mar-2019  
**Reason for revision** Not available

### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**