
COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-808K

4

CAS# 67-63-0
ISOPROPYL ALCOHOL
PCT BY WT: 1 - 5 VAPOR PRESSURE: 33.000 MMHG @ 20C
EXPOSURE LIMIT:
 ACGIH TLV/TWA: 200 ppm - TWA
 ACGIH TLV/STEL: 400 ppm - STEL
 OSHA PEL/TWA: 400 ppm - TWA
 OSHA STEL: 500 ppm
 LC50: Rat (8 Hrs) - > 12,000 ppm
 LD50: Oral (Rat) - 5000 mg/kg

5

CAS# 108-65-6
PROPYLENE GLYCOL m-METHYL ETHER ACETATE
PCT BY WT: 3 - 7 VAPOR PRESSURE: 3.700 MMHG @ 20C
EXPOSURE LIMIT:
 LC50: Inhalation (Rat, Male) - >4345 ppm/6 Hrs
 LD50: Oral (Rat, Female)- 8.5 g/kg

6 n-BUTYL ACETATE

CAS# 123-86-4
ACETIC ACID BUTYL ESTER
PCT BY WT: 10 - 30 VAPOR PRESSURE: 15.000 MMHG @ 20C
EXPOSURE LIMIT:
 ACGIH TLV/TWA: TWA 150 ppm
 ACGIH TLV/STEL: STEL 200 ppm
 OSHA PEL/TWA: TWA 150 ppm
 OSHA STEL: 200 ppm
 LC50: Inhalation (Rat) - > 1800 ppm/6 Hrs
 LD50: Oral (Rat)- 14,130 mg/kg

7 ETHYLENE GLYCOL N-BUTYL ETHER

CAS# 111-76-2
2-BUTOXYETHANOL
PCT BY WT: 1 - 5 VAPOR PRESSURE: .660 MMHG @ 20C
EXPOSURE LIMIT:
 ACGIH TLV/TWA: 20 ppm TWA (Skin)
 OSHA PEL/TWA: 50 ppm TWA (Skin)
 LC50: Inhalation (Mouse) - 700 ppm/7 Hrs
 LD50: Oral (Rat)- 1746 mg/kg
 CA PROPOSITION 65: No

8 ACETONE

CAS# 67-64-1
2-PROPANONE
PCT BY WT: 3 - 7 VAPOR PRESSURE: 185.000 MMHG @ 20C
EXPOSURE LIMIT:
 ACGIH TLV/TWA: TWA 500 ppm
 ACGIH TLV/STEL: STEL 750 ppm

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-808K

OSHA PEL/TWA: TWA 750 ppm
OSHA STEL: 1000 ppm
LC50: Inhalation (Rat)- >16,000 ppm/4Hrs
LD50: Oral (Rat): 6715 - 8453 mg/kg
CA PROPOSITION 65: No

9 ISOBUTYL ALCOHOL
CAS# 78-83-1
2-METHYL-1-PROPANOL
PCT BY WT: 1 - 5 VAPOR PRESSURE: 8.800 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: 50 ppm - TWA
OSHA PEL/TWA: 100 ppm - TWA
LC50: Inhalation (Rat)- >8000 ppm/4 Hour (s)
LD50: Oral (Rat): 2.5-6.4 g/kg

10
CAS# 64-17-5
ETHYL ALCOHOL
PCT BY WT: 7 - 13 VAPOR PRESSURE: 57.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 1000 ppm
OSHA PEL/TWA: TWA 1000 ppm
LD50: Oral (Rat) - 7060 mg/kg

11
CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: 1 - 5 VAPOR PRESSURE: 7.000 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 100 ppm
ACGIH TLV/STEL: STEL 25 ppm
OSHA PEL/TWA: TWA 100 ppm
OSHA STEL: 125 ppm
LD50: Oral, Rat - 3500 mg/kg
CA PROPOSITION 65: Yes

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains one or more reported or suspected reproductive
toxins.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-808K

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Exposure to liquid may cause mild eye irritation. Symptoms may include stinging, tearing, and redness.

SKIN: Prolonged or repeated skin contact may cause drying, cracking or irritation.

INHALATION: High vapor concentrations may cause drowsiness and irritation of the eyes or respiratory tract.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

If applicable, refer to the message(s) below.

HEALTH HAZARDS SPECIFIC TO PRODUCT COMPONENTS:

EFFECTS OF CHRONIC OVEREXPOSURE TO:

XYLENE: Studies have shown a possible association with exposure to xylene and respiratory tract irritation, liver & kidney damage, nausea, and vomiting in humans. Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen (Group 2B).

TOLUENE: Intentional abuse, misuse or other massive exposure to toluene may cause multiple organ (liver, kidney, brain cell) damage and/or death. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness.

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

ACETONE: Extensive human experience and animal data indicate that acetone is of low toxicity. However, ingestion of very large amounts or inhalation of extremely high vapor concentrations can cause irritation, nausea, vomiting, confusion, drowsiness, convulsions, and coma with possible

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-808K

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Keep container tightly closed. Keep container in a well-ventilated place.

SPECIAL COMMENTS

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing high vapor concentrations. Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Use exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor respirator approved by NIOSH for protection against chemicals in Section 2 &/or 15.

EYE PROTECTION

Use safety eyewear with splashguards and side shields.

SKIN PROTECTION

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-808K

warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

SECTION 14 - TRANSPORT INFORMATION

TDG HAZARD CLASS : 3
TDG PACKAGING GROUP : PG II
TDG SHIPPING NAME : PAINT
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

CANADA DSL - YES - All components are listed or exempt.

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 03/25/2009
Last Revision Date : 03/24/2009
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 2 Flammability- 3
 Reactivity- 0

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by these regulations.

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1M-808K

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.
