

Revision Date: 05-Jun-2019

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

### Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

### Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 lenmar-coatings.com

### AQUA-PLASTIC WATERBORNE URETHANE SEMI-GLOSS CLEAR 1WB-1410 TE6500 Water thinned paint Clear Topcoat No information available

Emergency Telephone CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

### **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity Category 1B	

### Label elements

Danger	
Hazard statements May damage fertility or the unborn child	
Appearance liquid	Odor little or no odor

### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### Other information

No information available

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Diethylene glycol monomethyl ether	111-77-3	1 - 5
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	1 - 5
Propylene glycol	57-55-6	1 - 5
1-Methyl-2-pyrrolidinone	872-50-4	1 - 5
Dibutyl phthalate	84-74-2	0.5 - 1
Ammonia	7664-41-7	0.1 - 0.5

## 4. FIRST AID MEASURES

General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
<u>NFPA</u> Health: 2 Flammability: 0	Instability: 0 Special: Not Applicable
NFPA Legend	

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

### **Storage** Keep container tightly closed. Keep out of the reach of children.

**Incompatible Materials** 

No information available

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Dibutyl phthalate	5 mg/m³ - TWA	5 mg/m³ - TWA
Ammonia	25 ppm - TWA	50 ppm - TWA
	35 ppm - STEL	35 mg/m³ - TWA

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

### **Engineering Measures** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	Protective gloves and impervious clothing.
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contamina

easures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold Density (lbs/gal) Specific Gravity pH Viscosity (cps) Solubility(ies) Water solubility Evaporation Rate Vapor pressure Vapor density Wt. % Solids Vol. % Solids Vol. % Solids Vol. % Volatiles VoC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing point (°F)	liquid little or no odor No information available 8.55 - 8.65 1.02 - 1.04 No information available No information available No information available No information available No information available No information available No information available 25 - 35 25 - 35 65 - 75 65 - 75 65 - 75 65 - 75 212 100 32
---	---

#### 1WB-1410 - AQUA-PLASTIC WATERBORNE URETHANE SEMI-GLOSS CLEAR

Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°C) Partition coefficient

#### 0

Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

Product Information		
Information on likely routes of e	exposure	
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Symptoms related to the physical, chemical and toxicological characteristics		
Symptoms	No information available	
Delayed and immediate effects as well as chronic effects from short and long-term exposure		
Eye contact Skin contact Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. No information available No information available. No information available.	

Reproductive Effects	May damage fertility or the unborn child.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available

#### Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	35321 mg/kg
ATEmix (dermal)	14546 mg/kg
ATEmix (inhalation-dust/mist)	110.5 mg/L

### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diethylene glycol monomethyl ether	= 4 mL/kg (Rat)	= 650 mg/kg (Rabbit) = 2500	-
111-77-3		μL/kg (Rabbit)	
Propanoic acid, 2-methyl-,	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	> 3.55 mg/L (Rat)6 h
monoester with			
2,2,4-trimethyl-1,3-pentanediol			
25265-77-4			
Propylene glycol	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
57-55-6	· ·		
1-Methyl-2-pyrrolidinone	= 3914 mg/kg (Rat)	= 8 g/kg (Rabbit)	= 3.1 mg/L (Rat) 4 h
872-50-4	· ·		
Dibutyl phthalate	= 7499 mg/kg (Rat)	> 20 mL/kg (Rabbit)	> 15.68 mg/L (Rat)4 h
84-74-2			,
Ammonia	= 350 mg/kg (Rat)	-	= 2000 ppm (Rat) 4 h
7664-41-7	/		

### Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

# **12. ECOLOGICAL INFORMATION**

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

#### <u>Acute Toxicity to Fish</u> No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

#### <u>Acute Toxicity to Aquatic Plants</u> No information available

### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

### Mobility in Environmental Media

No information available.

#### **Ozone**

No information available

### **Component Information**

### Acute Toxicity to Fish

Propylene glycol LC50: 710 mg/L (Fathead Minnow - 96 hr.)

### Acute Toxicity to Aquatic Invertebrates

Propylene glycol EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

### Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
	14. TRANSPORT INFORMATION
DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated
	15. REGULATORY INFORMATION

## International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

# Federal Regulations

### SARA 311/312 hazardous categorization

Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No.	Weight-%	CERCLA/SARA 313 (de minimis concentration)
Diethylene glycol monomethyl ether	111-77-3	1 - 5	1.0
1-Methyl-2-pyrrolidinone	872-50-4	1 - 5	1.0

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical name	CAS No.	Weight-%	Hazardous Air Pollutant
Diethylene glycol monomethyl ether	111-77-3	1 - 5	<u>(HAP)</u> Listed
Dibutyl phthalate	84-74-2	0.5 - 1	Listed

### **US State Regulations**

### **California Proposition 65**

**MARNING:** Cancer and Reproductive Harm– www.P65warnings.ca.gov

### State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Diethylene glycol monomethyl ether	Х	X	Х
1-Methyl-2-pyrrolidinone	Х	X	Х

### Legend

X - Listed

# 16. OTHER INFORMATION

HMIS - Health: 2\* Flammability: 0 Reactivity: 0 PPE: -

### HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard

- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	05-Jun-2019
Revision Summary	Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

### End of Safety Data Sheet