



SAFETY DATA SHEET

Revision Date: 17-Jan-2017

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name TEXCRETE WB ACRYLIC MASONRY WATERPROOFER
Product Code 3194-34FR
Alternate Product Code HV4834
Product Class WATER THINNED PAINT
Color All
Recommended use Paint
Restrictions on use No information available

Manufactured For
Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
coronadopaint.ca

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
coronadopaint.com

Emergency Telephone Number(s)
CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

| | |
|-----------------|-------------|
| Carcinogenicity | Category 1A |
|-----------------|-------------|

Label elements

Danger

Hazard statements
May cause cancer



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Precautionary Statements - Response

If exposed or concerned get medical attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical Name | CAS-No | Weight % (max) |
|--|------------|----------------|
| Nepheline syenite | 37244-96-5 | 10 - 30% |
| Titanium dioxide | 13463-67-7 | 3 - 7% |
| Silica, mica | 12001-26-2 | 1 - 5% |
| Propylene glycol | 57-55-6 | 1 - 5% |
| Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol | 25265-77-4 | 1 - 5% |
| Silica, crystalline | 14808-60-7 | 0.25 - 0.5% |
| Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl- | 330-54-1 | 0.1 - 0.25% |

4. FIRST AID MEASURES

General Advice

No hazards which require special first aid measures.

Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

Inhalation

Move to fresh air. If symptoms persist, call a physician.

Ingestion

Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

| | |
|--|------------------------|
| Most Important Symptoms/Effects | None known. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity To Mechanical Impact | No |
| Sensitivity To Static Discharge | No |
| Flash Point Data | |
| Flash Point (°F) | Not applicable |
| Flash Point (°C) | Not applicable |
| Flash Point Method | Not applicable |
| Flammability Limits In Air | |
| Lower Explosion Limit | Not applicable |
| Upper Explosion Limit | Not applicable |

NFPA **Health:** 1 **Flammability:** 0 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------------|---|
| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental Precautions | See Section 12 for additional Ecological Information. |
| Methods For Clean-Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |

7. HANDLING AND STORAGE

| | |
|-------------------------------|--|
| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
| Storage | Keep container tightly closed. Keep out of the reach of children. |
| Incompatible Materials | No information available |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

| Chemical Name | ACGIH | Alberta | British Columbia | Ontario | Quebec |
|---|-------------------------------|-------------------------------|---|---|-------------------------------|
| Nepheline syenite | N/E | N/E | N/E | 10 mg/m ³ - TWA | N/E |
| Titanium dioxide | 10 mg/m ³ - TWA | 10 mg/m ³ - TWA | 10 mg/m ³ - TWA 3 mg/m ³ - TWA | 10 mg/m ³ - TWA | 10 mg/m ³ - TWAEV |
| Silica, mica | 3 mg/m ³ - TWA | 3 mg/m ³ - TWA | 3 mg/m ³ - TWA | 3 mg/m ³ - TWA | 3 mg/m ³ - TWAEV |
| Propylene glycol | N/E | N/E | N/E | 10 mg/m ³ - TWA 50 ppm - TWA 155 mg/m ³ - TWA | N/E |
| Silica, crystalline | 0.025 mg/m ³ - TWA | 0.025 mg/m ³ - TWA | 0.025 mg/m ³ - TWA | 0.10 mg/m ³ - TWA | 0.1 mg/m ³ - TWAEV |
| Urea, N-(3,4-dichlorophenyl)-N,N-di methyl- | 10 mg/m ³ - TWA | 10 mg/m ³ - TWA | 10 mg/m ³ - TWA | 10 mg/m ³ - TWA | 10 mg/m ³ - TWAEV |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

| | |
|-----------------------------|--|
| Engineering Measures | Ensure adequate ventilation, especially in confined areas. |
|-----------------------------|--|

Personal Protective Equipment

Eye/Face Protection

Skin Protection

Respiratory Protection

Safety glasses with side-shields.
Protective gloves and impervious clothing.
In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------|--------------------------|
| Appearance | liquid |
| Odor | little or no odor |
| Odor Threshold | No information available |
| Density (lbs/gal) | 10.9 - 11.0 |
| Specific Gravity | 1.30 - 1.32 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility | No information available |
| Water Solubility | No information available |
| Evaporation Rate | No information available |
| Vapor Pressure | No information available |
| Vapor Density | No information available |

| | |
|---|--------------------------|
| Wt. % Solids | 50 - 60 |
| Vol. % Solids | 35 - 45 |
| Wt. % Volatiles | 40 - 50 |
| Vol. % Volatiles | 55 - 65 |
| VOC Regulatory Limit (g/L) | < 100 |
| Boiling Point (°F) | 212 |
| Boiling Point (°C) | 100 |
| Freezing Point (°F) | 32 |
| Freezing Point (°C) | 0 |
| Flash Point (°F) | Not applicable |
| Flash Point (°C) | Not applicable |
| Flash Point Method | Not applicable |
| Flammability (solid, gas) | Not applicable |
| Upper Explosion Limit | Not applicable |
| Lower Explosion Limit | Not applicable |
| Autoignition Temperature (°F) | No information available |
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition Coefficient (n-octanol/water) | No information available |

10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | Not Applicable |
| Chemical Stability | Stable under normal conditions. |
| Conditions To Avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility Of Hazardous Reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation
Skin contact Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation May cause irritation of respiratory tract.
Ingestion Ingestion may cause gastrointestinal irritation, nausea,

Sensitization:
Neurological Effects
Mutagenic Effects
Reproductive Effects
Developmental Effects
Target Organ Effects
STOT - single exposure
STOT - repeated exposure

vomiting and diarrhea.
No information available.
No information available.
No information available.
No information available.
No information available.
No information available.
No information available.
No information available.
Causes damage to organs through prolonged or repeated exposure if inhaled. Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
No information available.
No information available.

Other adverse effects
Aspiration Hazard

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 95637 mg/kg
ATEmix (dermal) 574847 mg/kg

Component

Titanium dioxide
LD50 Oral: > 10000 mg/kg (Rat)
Silica, mica
LD50 Oral: > 16000 mg/kg (Rat)
Propylene glycol
LD50 Oral: 20000 mg/kg (Rat)
LD50 Dermal: 20800 mg/kg (Rabbit)
Silica, crystalline
LD50 Oral: 500 mg/kg (Rat)
Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-
LD50 Oral: 1017 mg/kg (Rat)
LD50 Dermal: > 5000 mg/kg (Rat)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

| Chemical Name | IARC | NTP |
|---------------------|--------------------------------|------------------------|
| Titanium dioxide | 2B - Possible Human Carcinogen | |
| Silica, crystalline | 1 - Human Carcinogen | Known Human Carcinogen |

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer
NTP - National Toxicity Program
OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-

LC50: 3.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary,

consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

| | |
|-------------|---------------|
| TDG | Not regulated |
| ICAO / IATA | Not regulated |
| IMDG / IMO | Not regulated |

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

| <u>Chemical Name</u> | <u>CAS-No</u> | <u>Weight % (max)</u> | <u>NPRI Parts 1- 4</u> |
|---|---------------|-----------------------|------------------------|
| Propylene glycol | 57-55-6 | 1 - 5% | Listed |
| Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol | 25265-77-4 | 1 - 5% | Listed |

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 1* Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semnt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 17-Jan-2017
Reason For Revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET