

Material Safety Data Sheet

Revision Date: 18-Mar-2013 Revision Number: 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name MOORES ACRYLIC ROOF PAINT KELLY GREEN

Product Code R0006232

Product Class WATER THINNED PAINT

Color Green

Manufacturer Emergency Telephone Number(s)
Beniamin Moore & Co. CHEMTREC: 800-424-9300

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 201-573-9600 www.benjaminmoore.com

2. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Components

nazardous components						
Chemical Name	CAS-No	Weight % (max)				
C.I. Pigment Green 7	1328-53-6	5				
Titanium dioxide	13463-67-7	5				

3. HAZARDS IDENTIFICATION

Emergency Overview

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.

Appearance liquid Odor little or no odor

Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Effects

Eyes May cause slight irritation.

Skin InhalationSubstance may cause slight skin irritation.

May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects Repeated contact may cause allergic reactions in very susceptible persons.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 1 Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of water. Consult a physician if

necessary.

Notes To Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 18-Mar-2013

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

Sensitivity To Mechanical Impact No

SALEN

Revision Date: 18-Mar-2013

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Environmental Precautions Prevent further leakage or spillage if safe to do so.

Methods For Clean-Up Soak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

Other Information None known

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Hazardous Components

nazarada demperence					
Chemical Name	ACGIH	OSHA			
C.I. Pigment Green 7	N/E	N/E			
Titanium dioxide	10 mg/m ³ - TWA	15 mg/m ³ - TWA total			

Revision Date: 18-Mar-2013

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Freezing Point (°F)

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing

In case of insufficient ventilation wear suitable respiratory equipment. **Respiratory Protection**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing **Hygiene Measures**

before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor Density (lbs/gal) 9.15 - 9.25**Specific Gravity** 1.09 - 1.11Not available Hq **Evaporation Rate** Not available **Vapor Pressure** Not available **Vapor Density** Not available Wt. % Solids 35 - 45 Vol. % Solids 30 - 40 Wt. % Volatiles 55 - 65 Vol. % Volatiles 60 - 70**VOC Regulatory Limit (g/L)** < 250 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 32

Freezing Point (°C) Flash Point (°F) Not applicable Flash Point (°C) Not applicable Not applicable **Flash Point Method** Not applicable **Upper Explosion Limit** Not applicable **Lower Explosion Limit**

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing

0

No materials to be especially mentioned. **Incompatible Materials**

Hazardous Decomposition Products None under normal use.

Possibility Of Hazardous Reactions

None under normal conditions of use.

Revision Date: 18-Mar-2013

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product

No information available

Component

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat) LD50 Dermal: > 10000 mg/m³ (Rabbit)

LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
		2B - Possible		Listed
Titanium dioxide		Human		
		Carcinogen		

 Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

Product

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

12. ECOLOGICAL INFORMATION

Acute Toxicity to Aquatic Plants

No information available

Component

Acute Toxicity to Fish

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state, and local regulations. Dry, empty **Waste Disposal Method**

containers may be recycled in a can recycling program. Local requirements may vary, consult your sanitation department or state-designated environmental

Revision Date: 18-Mar-2013

protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

United States TSCA Yes - All components are listed or exempt. Yes - All components are listed or exempt. Canada DSL

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard No Chronic Health Hazard No Fire Hazard Nο Sudden Release of Pressure Hazard No

Reactive Hazard

No

Revision Date: 18-Mar-2013

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical NameCAS-NoWeight % (max)C.I. Pigment Green 71328-53-65

This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further information.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

This product may contain trace amounts of (other) HAPs chemicals. Contact the preparer for further information.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
C.I. Pigment Green 7		X	X		
Titanium dioxide	X	Χ	Χ		Χ

Legend

X - Listed

16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 360 Route 206 - P.O. Box 4000

Flanders, NJ 07836 866-690-1961

R0006232 - MOORES ACRYLIC ROOF PAINT KELLY GREEN

Revision Date: 18-Mar-2013

Revision Date: 18-Mar-2013 Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of MSDS