

Revision Date: 10-Oct-2014 Revision Number: 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SUPREME HOUSE PAINT EXTERIOR FLAT - DEEP BASE Product Code 8-34

Alternate Product Code TL1834
Product Class WATER THINNED PAINT

Color All Recommended use Paint

**Restrictions on use**No information available

ManufacturerEmergency Telephone Number(s)Benjamin Moore & Co.CHEMTREC (US): 800-424-9300

01 Paragon Drive CHEMTREC (outside US): (703)-527-3887

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 800-225-5554 coronadopaint.com

## 2. HAZARDS IDENTIFICATION

#### Classification

Carcinogenicity Category 1A

#### Label elements

#### Danger

# Hazard statements May cause cancer



Appearance liquid Odor little or no odor

**BASE** 

**Precautionary Statements - Prevention** 

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

**Precautionary Statements - Response** 

If exposed or concerned get medical attention

**Precautionary Statements - Storage** 

Store locked up

**Precautionary Statements - Disposal** 

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Nepheline syenite	37244-96-5	25
Titanium dioxide	13463-67-7	10
Zinc oxide	1314-13-2	5
Distillates (petroleum), solvent-dewaxed heavy	64742-65-0	1
paraffinic		
Sodium C14-C16 olefin sulfonate	68439-57-6	0.5
Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-	330-54-1	0.5

#### 4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician if

necessary.

Most Important Symptoms/Effects No information available.

Notes To Physician Treat symptomatically

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** 

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Revision Date: 10-Oct-2014

\_\_\_\_\_

**Protective Equipment And Precautions For Firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 10-Oct-2014

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

**Flash Point Data** 

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: -

## **NFPA** Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Methods For Clean-Up**Soak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

## 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Revision Date: 10-Oct-2014

## **Exposure Limits**

Chemical Name	ACGIH	OSHA
Nepheline syenite	N/E	5 mg/m <sup>3</sup> - TWA (nuisance dust)
Titanium dioxide	10 mg/m³ - TWA	15 mg/m <sup>3</sup> - TWA
Zinc oxide	2 mg/m³ - TWA	15 mg/m <sup>3</sup> - TWA total
	10 mg/m <sup>3</sup> - STEL	5 mg/m³ - TWA
Distillates (petroleum), solvent-	N/E	N/E
dewaxed heavy paraffinic		
Sodium C14-C16 olefin sulfonate	N/E	N/E
Urea, N-(3,4-dichlorophenyl)-	10 mg/m³ - TWA	N/E
N,N-dimethyl-	-	

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

**Density (lbs/gal)** 10.6 - 11.0 **Specific Gravity** 1.27 - 1.31

pH No information available
Viscosity (cps) No information available
Solubility No information available
Water Solubility No information available
Evaporation Rate No information available
Vapor Pressure No information available
Vapor Density No information available

Wt. % Solids 45 - 55 Vol. % Solids 30 - 40 Wt. % Volatiles 45 - 55 60 - 70 Vol. % Volatiles **VOC Regulatory Limit (g/L)** <50 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing Point (°F) 32 Freezing Point (°C)

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Revision Date: 10-Oct-2014

Flammability (solid, gas)
Upper Explosion Limit
Not applicable
Not applicable
Not applicable

Autoignition Temperature (°F)
Autoignition Temperature (°C)
Decomposition Temperature (°F)
Decomposition Temperature (°C)
No information available
No information available
No information available
No information available

octanol/water)

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions

None under normal conditions of use.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

## **Product Information**

InhalationNo information availableEye contactNo information availableSkin contactNo information availableIngestionNo information available

**Acute Toxicity** 

**Product** No information available

# Information on toxicological effects

**Symptoms** No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization:No information availableMutagenic EffectsNo information availableReproductive EffectsNo information available

## **Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

8-34 - SUPREME HOUSE PAINT EXTERIOR FLAT - DEEP BASE

Revision Date: 10-Oct-2014

ATEmix (oral) 107438 mg/kg ATEmix (dermal) 1659023 mg/kg

# Acute Toxicity Component

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat) LD50 Dermal: > 10000 mg/m³ (Rabbit)

LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Zinc oxide

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Dust): > 5700 mg/m<sup>3</sup> (Rat, 4 hr.)

Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-

LD50 Oral: 1017 mg/kg (Rat) LD50 Dermal: > 5000 mg/kg (Rat)

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	IARC	NTP	OSHA Carcinogen
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		
	1 - Human Carcinogen		
Distillates (petroleum), solvent-dewaxed heavy			
paraffinic			

 Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

#### **Product**

#### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

Revision Date: 10-Oct-2014

#### **Acute Toxicity to Aquatic Plants**

No information available

## Persistence / Degradability

No information available

#### **Bioaccumulation / Accumulation**

No information available

#### **Mobility in Environmental Media**

No information available

#### Ozone

No information available

#### Component

#### **Acute Toxicity to Fish**

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

<u>Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-</u> LC50: 3.5 mg/L (Rainbow Trout - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

## **Acute Toxicity to Aquatic Plants**

No information available

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## 15. REGULATORY INFORMATION

Revision Date: 10-Oct-2014

## **International Inventories**

United States TSCA Yes - All components are listed or exempt.

Canada DSL Yes - All components are listed or exempt.

## **Federal Regulations**

#### SARA 311/312 hazardous categorization

Acute Health Hazard No
Chronic Health Hazard Yes
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name CAS-No Weight % (max)

 Zinc oxide
 1314-13-2
 5

 Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl 330-54-1
 0.5

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

#### State Regulations

#### **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

## State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	X	X	X
Zinc oxide	X	X	X
Urea, N-(3,4-dichlorophenyl)-	X	X	X
N.N-dimethyl-			

#### Legend

X - Listed

#### 16. OTHER INFORMATION

Revision Date: 10-Oct-2014

HMIS Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

## **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 855-724-6802

Revision Date: 10-Oct-2014
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**