

SAFETY DATA SHEET

Revision Date: 31-May-2018

Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 coronadopaint.com

RUST SCAT WATERBORNE ACRYLIC ENAMEL GLOSS WALNUT 80-368 TR0338 Water thinned paint brown

brown Paint No information available

Emergency Telephone

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity

Category 2

Label elements

Warning

Hazard statements Suspected of causing cancer



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

Other hazards

May cause allergic skin reaction

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Iron oxide	1309-37-1	5
Kaolin	1332-58-7	5
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	5
Hexanedioic acid, dihydrazide	1071-93-8	0.5
Ammonia	7664-41-7	0.5
Carbon black	1333-86-4	0.5

4. FIRST AID MEASURES

General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all

	contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.	
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.	
Sensitivity To Mechanical Impact	No	
Sensitivity To Static Discharge	No	
Flash Point Data Flash Point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable	
Flammability Limits In Air		
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable	
NFPA Health: 1 Flammability: 0	Instability: 0 Special: Not Applicable	
NFPA Legend 0 - Not Hazardous		

- aruous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

80-368 - RUST SCAT WATERBORNE ACRYLIC ENAMEL GLOSS WALNUT

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Iron oxide	5 mg/m³ - TWA	10 mg/m³ - TWA
		15 mg/m ³ - TWA Rouge
		5 mg/m ³ - TWA Rouge
Kaolin	2 mg/m³ - TWA	15 mg/m³ - TWA
		5 mg/m³ - TWA
Ammonia	25 ppm - TWA	50 ppm - TWA
	35 ppm - STEL	35 mg/m ³ - TWA
Carbon black	3 mg/m³ - TWA	3.5 mg/m ³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold liquid little or no odor No information available

80-368 - RUST SCAT WATERBORNE ACRYLIC ENAMEL GLOSS WALNUT

Density (lbs/gal) **Specific Gravity** pН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) **Boiling Point (°C)** Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Method Flammability (solid, gas) **Upper flammability limit:** Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

9.45 - 9.55 1.13 - 1.15 No information available 40 - 50 30 - 40 50 - 60 60 - 70 < 150 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

ReactivityNot ApplicableChemical StabilityStable under normal conditions.Conditions to avoidPrevent from freezing.Incompatible MaterialsNo materials to be especially mentioned.Hazardous Decomposition ProductsNone under normal use.Possibility of hazardous reactionsNone under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity	
Product Information	No information available
Symptoms related to the physi	cal, chemical and toxicological characteristics
Symptoms	No information available
Delayed and immediate effects	as well as chronic effects from short and long-term exposure
Eye contact Skin contact	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects Reproductive Effects Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure Other adverse effects Aspiration Hazard	May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause an allergic skin reaction No information available. No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	52998 mg/kg
ATEmix (dermal)	556559 mg/kg
ATEmix (inhalation-dust/mist)	170 mg/L

Component Information

Iron oxide LD50 Oral: > 5000 mg/kg (Rat) vendor data Kaolin LD50 Oral: > 5000 mg/kg (Rat) <u>Ammonia</u> LC50 Inhalation (Vapor): 2000 ppm (Rat, 4 hr.) <u>Carbon black</u> LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rabbit)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Carbon black	Carcinogen		

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

<u>Acute Toxicity to Aquatic Plants</u> No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local
-	requirements may vary, consult your sanitation department or state-designated
	environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Not regulated

ICAO / IATA	Not regulated
IMDG / IMO	Not regulated
	15. REGULATORY INFORMATION
International Inventories	
TSCA: United States	Yes - All components are listed or exempt.

ISCA: United States	res - All components are listed of exempt.
DSL: Canada	Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization	
Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No.	Weight-%	CERCLA/SARA 313 (de minimis concentration)
Diethylene glycol monoethyl ether	111-90-0	5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Iron oxide	Х	X	Х
Kaolin	Х	X	Х
Diethylene glycol monoethyl ether		X	Х

Carbon black	Х	Х	Х

Legend

X - Listed

16. OTHER INFORMATION					
<u>HMIS</u> -	Health: 1*	Flammability: 0	Reactivity: 0	PPE: -	
HMIS Legend 0 - Minimal Haz 1 - Slight Hazar 2 - Moderate H 3 - Serious Haz 4 - Severe Haz * - Chronic Haz	zard rd azard zard ard				

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	31-May-2018
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET