

SAFETY DATA SHEET

Revision Date: 19-May-2020

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Coronado

CORONADO SUPER KOTE 5000 EXTERIOR ACRYLIC SATIN DEEP BASE 803-34 TX0334 Water thinned paint All Paint No information available

Emergency Telephone CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B

Label elements

Danger

Hazard statements May cause genetic defects May damage fertility or the unborn child



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Kaolin	1332-58-7	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Nepheline syenite	37244-96-5	1 - 5
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	1 - 5
Propylene glycol	57-55-6	1 - 5
Zinc oxide	1314-13-2	0.5 - 1
Sodium C14-C16 olefin sulfonate	68439-57-6	0.1 - 0.5
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.1 - 0.5

4. FIRST AID MEASURES		
General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.	
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.	

Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Inhalation	Move to fresh air. If symptoms persist, call a physician.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.	
Most Important Symptoms/Effects	None known.	
Notes To Physician	Treat symptomatically.	
	5. FIRE-FIGHTING MEASURES	

- Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus Protective equipment and precautions for firefighters pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. **Specific Hazards Arising From The Chemical** Closed containers may rupture if exposed to fire or extreme heat. No Sensitivity to mechanical impact Sensitivity to static discharge No **Flash Point Data** Flash point (°F) Not applicable Flash Point (°C) Not applicable Method Not applicable Flammability Limits In Air Lower flammability limit: Not applicable Not applicable **Upper flammability limit:** NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable **NFPA Legend** 0 - Not Hazardous 1 - Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES			
Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.		
Other Information	Prevent further leakage or spillage if safe to do so.		
Environmental precautions	See Section 12 for additional Ecological Information.		
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
	7. HANDLING AND STORAGE		
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.		
Storage	Keep container tightly closed. Keep out of the reach of children.		
Incompatible Materials	No information available		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Kaolin	TWA: 2 mg/m ³ particulate matter	15 mg/m³ - TWA
	containing no asbestos and <1%	5 mg/m ³ - TWA
	crystalline silica, respirable particulate	-
	matter	
Titanium dioxide	TWA: 10 mg/m ³	15 mg/m³ - TWA
Zinc oxide	STEL: 10 mg/m ³ respirable particulate	5 mg/m ³ - TWA
	matter	15 mg/m ³ - TWA
	TWA: 2 mg/m ³ respirable particulate	C C
	matter	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** pН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) **Upper flammability limit:** Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

liquid little or no odor No information available 10.0 - 10.1 1.20 - 1.22 No information available 40 - 50 25 - 35 50 - 60 65 - 75 < 100 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information			
Information on likely routes of exposure			
Principal Routes of Exposure	Eye contact, skin contact and inhalation.		
Acute Toxicity			
Product Information	No information available		
Symptoms related to the physic	cal, chemical and toxicological characteristics		
Symptoms	No information available		
Delayed and immediate effects	as well as chronic effects from short and long-term exposure		
Eye contact Skin contact Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects Reproductive Effects Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. No information available No information available. Suspected of causing genetic defects. May damage fertility or the unborn child. No information available. No information available. No information available. No information available. No information available. No information available.		
Other adverse effects Aspiration Hazard	No information available. No information available		

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	78584 mg/kg
ATEmix (dermal)	679699 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	-
Propylene glycol 57-55-6	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Sodium C14-C16 olefin sulfonate 68439-57-6	= 2220 mg/kg (Rat)	> 740 mg/kg (Rabbit)	-

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA	
	2B - Possible Human		Listed	
Titanium dioxide	Carcinogen			

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Titanium dioxide

803-34 - CORONADO SUPER KOTE 5000 EXTERIOR ACRYLIC SATIN DEEP BASE

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Propylene glycol</u> LC50: 710 mg/L (Fathead Minnow - 96 hr.) <u>Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester</u> LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol EC50: > 10000 mg/L (Daphnia magna - 24 hr.) Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS	
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.	
	14. TRANSPORT INFORMATION	
DOT	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	
	15. REGULATORY INFORMATION	
International Inventories		
TSCA: United States DSL: Canada	Yes - All components are listed or exempt. Yes - All components are listed or exempt.	
Federal Regulations		
SARA 311/312 hazardous categ	orization	

Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains

a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Kaolin	Х	X	Х
Titanium dioxide	Х	X	Х
Carbamic acid, 1H-benzimidazol-2-yl-,		X	
methyl ester			

Legend

X - Listed

16. OTHER INFORMATION

<u>HMIS</u> -	Health: 2*	Flammability: 0	Reactivity: 0	PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead

exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
19-May-2020 Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet