

SAFETY DATA SHEET

Revision Date: 03-Apr-2020

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

CORONADO MAXUM TRANSLUCENT DECK & SIDING STAIN CLEAR B7400-10FR HB4110 STAIN Clear STAIN

Manufactured For

Complementary Coatings Corp. 360 Route 206 Flanders, NJ 07836 Phone: 1-866-708-9180 www.coronadopaint.ca

Distributor

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 coronadopaint.ca

Emergency Telephone

CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

No information available

| Skin sensitization | Category 1A |
|------------------------|-------------|
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 1B |

Label elements

Danger

Hazard statements

May cause an allergic skin reaction May cause genetic defects Suspected of causing cancer May damage fertility or the unborn child



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention **Skin** IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

| Chemical name | CAS No. | Weight-% | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|------------------|---------|----------|---|---|
| Propylene glycol | 57-55-6 | 1 - 5% | - | - |

3. COMPOSITION INFORMATION ON COMPONENTS

B7400-10FR - CORONADO MAXUM TRANSLUCENT DECK & SIDING STAIN CLEAR

| Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2- yl)-5-(1,1-dimethylethyl)-4-hydro xyphenyl]-1-oxopropyl]omega hydroxy- | 104810-48-2 | 0.1 - 0.25% | - | - |
|--|-------------|-------------|---|---|
| Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-pip eridinyl) ester | 41556-26-7 | 0.1 - 0.25% | - | - |
| Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester | 10605-21-7 | 0.1 - 0.25% | - | - |
| Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2- yl)-5-(1,1-dimethylethyl)-4-hydro xyphenyl]-1-oxopropyl]-omega [3-[3-(2H-benzotriazol-2-yl)-5-(1, 1-dimethylethyl)-4-hydroxyphen yl]-1-oxoprop | 104810-47-1 | 0.1 - 0.25% | - | - |
| Cobalt neodecanoate | 27253-31-2 | 0.1 - 0.25% | - | - |

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

| General Advice | If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance. |
|---------------------------------|--|
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | May cause allergic skin reaction. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|---|--|
| Protective equipment and precautions for firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |

| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
|--|---|
| Sensitivity to mechanical impact | No |
| Sensitivity to static discharge | No |
| Flash Point Data Flash point (°F) Flash Point (°C) Method | Not applicable Not applicable Not applicable |
| Flammability Limits In Air | |
| Lower flammability limit: Upper flammability limit: | Not applicable Not applicable |
| NFPA Health: 2 Flammability: 0 | Instability: 0 Special: Not Applicable |
| NFPA Legend 0 - Not Hazardous | |

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. | |
|---------------------------|---|--|
| Other Information | Prevent further leakage or spillage if safe to do so. | |
| Environmental precautions | See Section 12 for additional Ecological Information. | |
| Methods for Cleaning Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. | |

7. HANDLING AND STORAGE

| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. | |
|------------------------|--|--|
| Storage | Keep container tightly closed. Keep out of the reach of children. | |
| Incompatible Materials | No information available | |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | Alberta | British Columbia | Ontario | Quebec |
|------------------|-----------|---------|------------------|---|--------|
| Propylene glycol | N/E | N/E | N/E | 10 mg/m³ - TWA 50 ppm - TWA 155 mg/m³ - TWA | N/E |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits N/E - Not established

Engineering Measures

Personal Protective Equipment

| Eye/Face Protection |
|-------------------------------|
| Skin Protection |
| Respiratory Protection |

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields.

Protective gloves and impervious clothing. Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | liquid |
|----------------------------|--------------------------|
| Odor | little or no odor |
| Odor Threshold | No information available |
| Density (lbs/gal) | 8.55 - 8.65 |
| Specific Gravity | 1.02 - 1.04 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility(ies) | No information available |
| Water solubility | No information available |
| Evaporation Rate | No information available |
| Vapor pressure | No information available |
| Vapor density | No information available |
| Wt. % Solids | 20 - 30 |
| Vol. % Solids | 15 - 25 |
| Wt. % Volatiles | 70 - 80 |
| Vol. % Volatiles | 75 - 85 |
| VOC Regulatory Limit (g/L) | <250 |
| Boiling Point (°F) | 212 |
| Solubility(ies) | No information available |
| Water solubility | No information available |
| Evaporation Rate | No information available |
| Vapor pressure | No information available |
| Vapor density | No information available |
| Wt. % Solids | 20 - 30 |
| Vol. % Solids | 15 - 25 |
| Wt. % Volatiles | 70 - 80 |
| Vol. % Volatiles | 75 - 85 |
| VOC Regulatory Limit (g/L) | <250 |

| Boiling Point (°C) Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) |
|---|
| |

32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

100

Reactivity

Chemical Stability

Conditions to avoid

Incompatible Materials

Hazardous Decomposition Products

Possibility of hazardous reactions

Not Applicable

Stable under normal conditions.

Prevent from freezing.

No materials to be especially mentioned.

None under normal use.

None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

| Product Information Information on likely routes of exposure | | |
|--|--|--|
| Principal Routes of Exposure | Eye contact, skin contact and inhalation. | |
| Acute Toxicity Product Information | No information available | |
| Symptoms related to the physical, chemical and toxicological characteristics | | |
| Symptoms | No information available | |
| Delayed and immediate effects as well as chronic effects from short and long-term exposure | | |
| Eye contact Skin contact Inhalation | May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. May cause irritation of respiratory tract. | |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. | |
| Sensitization | May cause an allergic skin reaction. | |

| Neurological Effects | No information available. |
|--------------------------|---|
| Mutagenic Effects | Suspected of causing genetic defects. |
| Reproductive Effects | May damage fertility or the unborn child. |
| Developmental Effects | No information available. |
| Target organ effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available. |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

| ATEmix (oral) | 685645 mg/kg |
|-----------------|--------------|
| ATEmix (dermal) | 713071 mg/kg |

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--------------------------------------|--------------------|-----------------------------------|-----------------|
| Propylene glycol | = 20 g/kg (Rat) | = 20800 mg/kg (Rabbit) | - |
| 57-55-6 | | | |
| Decanedioic acid, | = 2615 mg/kg (Rat) | - | - |
| bis(1,2,2,6,6-pentamethyl-4-piperidi | | | |
| nyl) ester | | | |
| 41556-26-7 | | | |
| Carbamic acid, | > 5050 mg/kg (Rat) | > 10000 mg/kg (Rabbit) = 2 g/kg (| - |
| 1H-benzimidazol-2-yl-, methyl ester | = 6400 mg/kg (Rat) | Rat) = 8500 mg/kg (Rabbit) | |
| 10605-21-7 | | | |
| Cobalt neodecanoate | - | 2500 mg/kg | - |
| 27253-31-2 | | | |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP |
|---------------------|--------------------------------|------------------------------|
| | 2B - Possible Human Carcinogen | Reasonably Anticipated Human |
| Cobalt neodecanoate | | Carcinogen |

• Cobalt and cobalt compounds are listed as possible human carcinogens by IARC (2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

Propylene glycol LC50: 710 mg/L (Fathead Minnow - 96 hr.) Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol EC50: > 10000 mg/L (Daphnia magna - 24 hr.) Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

TDG

Not regulated

ICAO / IATA

IMDG / IMO

Not regulated

Not regulated

15. REGULATORY INFORMATION

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | Yes - All components are listed or exempt. |

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS -

Health: 2*

Flammability: 0

Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

| Prepared By | Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554 |
|---------------------|---|
| Revision Date: | 03-Apr-2020 |
| Reason for revision | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet