

SAFETY DATA SHEET

Revision Date: 03-Apr-2020 Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name CORONADO MAXUM TRANSLUCENT DECK & SIDING STAIN

MOUNTAIN CANYON

Product Code B7400-907

Alternate Product Code TB4197

Product Class STAIN
Color brown
Recommended use STAIN

Restrictions on use No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 1-866-708-9180 coronadopaint.com

Emergency Telephone CHEMTREC (US): 800-424-9300

CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B

Label elements

Danger

Hazard statements

May cause an allergic skin reaction
May cause genetic defects
Suspected of causing cancer
May damage fertility or the unborn child

Revision Date: 03-Apr-2020



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Propylene glycol	57-55-6	1 - 5
2-Amino-2-methly-1-propanol	124-68-5	0.1 - 0.5
Poly(oxy-1,2-ethanediyl),	104810-48-2	0.1 - 0.5
.alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimeth		
ylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegah		
ydroxy-		
Decanedioic acid,	41556-26-7	0.1 - 0.5
bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester		
Carbamic acid, 1H-benzimidazol-2-yl-, methyl	10605-21-7	0.1 - 0.5
ester		
Poly(oxy-1,2-ethanediyl),	104810-47-1	0.1 - 0.5
.alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimeth		
ylethyl)-4-hydroxyphenyl]-1-oxopropyl]omega[

3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)- 4-hydroxyphenyl]-1-oxoprop		
Cobalt neodecanoate	27253-31-2	0.1 - 0.5

4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. If skin irritation persists, call a physician. Wash

clothing before reuse. Destroy contaminated articles such as shoes.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 03-Apr-2020

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

B7400-907 - CORONADO MAXUM TRANSLUCENT DECK & SIDING STAIN MOUNTAIN CANYON

Revision Date: 03-Apr-2020

NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautions See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

No exposure limits have been established for this product.

Legend

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection Use only with adequate ventilation. In operations where exposure limits are

exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator

specified for paint spray or organic vapors.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

No information available

Revision Date: 03-Apr-2020

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 8.55 - 8.65

 Specific Gravity
 1.02 - 1.04

pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information available

 Wt. % Solids
 20 - 30

 Vol. % Solids
 15 - 25

 Wt. % Volatiles
 70 - 80

 Vol. % Volatiles
 75 - 85

 VOC Regulatory Limit (g/L)
 < 250</td>

 Boiling Point (°F)
 212

Vapor density

Boiling Point (°F) 212

Boiling Point (°C) 100

Freezing point (°F) 32

Freezing Point (°C) 0

Flash point (°F) Not applicable

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions

None under normal conditions of use.

Revision Date: 03-Apr-2020

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product InformationNo information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation.

Skin contact Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization May cause an allergic skin reaction

Neurological EffectsNo information available.

Mutagenic EffectsSuspected of causing genetic defects.Reproductive EffectsMay damage fertility or the unborn child.

Developmental Effects
Target organ effects
STOT - single exposure
STOT - repeated exposure
Other adverse effects
Aspiration Hazard
No information available.
No information available.
No information available.
No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 677021 mg/kg **ATEmix (dermal)** 704102 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propylene glycol	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
57-55-6			
2-Amino-2-methly-1-propanol	= 2900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
124-68-5			
Decanedioic acid,	= 2615 mg/kg (Rat)	-	-
bis(1,2,2,6,6-pentamethyl-4-piperidi			
nyl) ester			
41556-26-7			
Carbamic acid,	> 5050 mg/kg (Rat)	> 10000 mg/kg (Rabbit) = 2 g/kg (-
1H-benzimidazol-2-yl-, methyl ester	= 6400 mg/kg (Rat)	Rat) = 8500 mg/kg (Rabbit)	

B7400-907 - CORONADO MAXUM TRANSLUCENT DECK & SIDING STAIN MOUNTAIN CANYON

Revision Date: 03-Apr-2020

10605-21-7			
Cobalt neodecanoate 27253-31-2	-	2500 mg/kg	-

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
Cobalt neodecanoate	2B - Possible Human Carcinogen	Reasonably Anticipated Human	Listed
	0	Carcinogen	

• Cobalt and cobalt compounds are listed as possible human carcinogens by IARC (2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Propylene glycol

LC50: 710 mg/L (Fathead Minnow - 96 hr.)

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Propylene glycol

EC50: > 10000 mg/L (Daphnia magna - 24 hr.) Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 0.22 mg/L (water flea - 48 hr.)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 03-Apr-2020

environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States DSL: CanadaYes - All components are listed or exempt.
Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Revision Date: 03-Apr-2020

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical nameCAS No.Weight-%Hazardous Air Pollutant (HAP)Cobalt neodecanoate27253-31-20.1 - 0.5Listed

US State Regulations

California Proposition 65



WARNING: Cancer and Reproductive Harm- www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Propylene glycol		X	X
Carbamic acid, 1H-benzimidazol-2-yl-,		X	
methyl ester			
Cobalt neodecanoate		X	Х

Legend

X - Listed

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead

B7400-907 - CORONADO MAXUM TRANSLUCENT DECK & SIDING STAIN MOUNTAIN CANYON

Revision Date: 03-Apr-2020

exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 03-Apr-2020 **Revision Summary** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet