



# INSLX

## SAFETY DATA SHEET

Revision Date: 25-Aug-2023

Revision Number: 7

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** GARAGEGUARD WATERBORNE EPOXY GARAGE FLOOR COATING SHOWROOM GRAY  
**Product Code** EGG-310SF  
**Alternate Product Code** XF0910, XF0931  
**Product Class** WATERBORNE EPOXY  
**Color** Gray  
**Recommended use** Paint  
**Restrictions on use** No information available

#### **Manufactured For**

Benjamin Moore & Co., Limited  
8775 Keele Street  
Concord ON L4K 2N1  
Phone: 1-800-361-5898  
www.inslx.ca

#### **Manufacturer**

Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-866-708-9180  
www.insl-x.com

#### **Emergency Telephone**

CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
+1 703-527-3887 (outside US & Canada)  
CANUTEC: 613-996-6666 (Transport Emergency Only)

### 2. HAZARDS IDENTIFICATION

#### **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

#### **Label elements**

##### **Danger**

##### **Hazard statements**

Causes skin irritation  
Causes serious eye damage  
May cause cancer

Causes damage to organs  
Causes damage to organs through prolonged or repeated exposure



**Appearance** liquid

**Odor** little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not breathe dust/fume/gas/mist/vapors/spray  
Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor

##### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing  
Immediately call a POISON CENTER or doctor/physician

##### **Skin**

IF ON SKIN: Wash with plenty of soap and water  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Other information**

No information available

**IMPORTANT:** Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Talc	14807-96-6	10 - 30%	-	-
Titanium dioxide	13463-67-7	10 - 30%	-	-
Aliphatic polyamine	-	10 - 30%	HMIRC # 9649	Granted: April 21, 2016
2-Propoxyethanol	2807-30-9	7 - 13%	-	-
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5%	-	-
Silica, crystalline	14808-60-7	0.25 - 0.5%	-	-
Carbon black	1333-86-4	0.1 - 0.25%	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

<b>General Advice</b>	Immediately call a POISON CENTER or doctor/physician.
<b>Eye Contact</b>	Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
<b>Skin Contact</b>	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before reuse.
<b>Inhalation</b>	Call a physician or poison control center immediately. Move to fresh air. If not breathing, give artificial respiration.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice.
<b>Protection Of First-Aiders</b>	Use personal protective equipment.
<b>Most Important Symptoms/Effects</b>	None known.
<b>Notes To Physician</b>	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-------------------------------------	---

---

<b>Protective equipment and precautions for firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Specific Hazards Arising From The Chemical</b>	Closed containers may rupture if exposed to fire or extreme heat.
<b>Sensitivity to mechanical impact</b>	No
<b>Sensitivity to static discharge</b>	No
<b>Flash Point Data</b>	
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable
<b>Flammability Limits In Air</b>	
Lower flammability limit:	Not applicable
Upper flammability limit:	Not applicable
<b>NFPA</b>	
Health hazards	1
Flammability	0
Stability	0
Special:	Not Applicable

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
<b>Other Information</b>	Prevent further leakage or spillage if safe to do so.
<b>Environmental precautions</b>	See Section 12 for additional Ecological Information.
<b>Methods for Cleaning Up</b>	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Storage</b>	Keep container tightly closed. Keep out of the reach of children.
<b>Incompatible Materials</b>	No information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Talc	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWAEV
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA 3 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV
2-Propoxyethanol	-	-	-	25 ppm - TWA 110 mg/m <sup>3</sup> - TWA Danger of cutaneous absorption	-
Dipropylene glycol monomethyl ether	TWA: 50 ppm	100 ppm - TWA 606 mg/m <sup>3</sup> - TWA 150 ppm - STEL 909 mg/m <sup>3</sup> - STEL Substance may be readily absorbed through intact skin	100 ppm - TWA 150 ppm - STEL Skin absorption can contribute to overall exposure.	100 ppm - TWA 150 ppm - STEL Danger of cutaneous absorption	100 ppm - TWAEV 606 mg/m <sup>3</sup> - TWAEV 150 ppm - STEV 909 mg/m <sup>3</sup> - STEV Skin absorption can contribute to overall exposure.
Silica, crystalline	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
Carbon black	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	3.5 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWA	3 mg/m <sup>3</sup> - TWA	3.5 mg/m <sup>3</sup> - TWAEV

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists  
 Alberta - Alberta Occupational Exposure Limits  
 British Columbia - British Columbia Occupational Exposure Limits  
 Ontario - Ontario Occupational Exposure Limits  
 Quebec - Quebec Occupational Exposure Limits  
 N/E - Not established

<b>Engineering Measures</b>	Ensure adequate ventilation, especially in confined areas.
<b>Personal Protective Equipment</b>	
<b>Eye/Face Protection</b>	Safety glasses with side-shields
<b>Skin Protection</b>	Protective gloves and impervious clothing.
<b>Respiratory Protection</b>	In case of insufficient ventilation wear suitable respiratory

equipment.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	little or no odor
Odor Threshold	No information available
Density (lbs./gal)	11.6 - 12.0
Specific Gravity	1.39 - 1.44
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available
Wt. % Solids	55 - 65
Vol. % Solids	35 - 45
Wt. % Volatiles	35 - 45
Vol. % Volatiles	55 - 65
VOC Regulatory Limit (g/L)	< 250
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing point (°F)	32
Freezing Point (°C)	0
Flash point (°F)	Not Applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

## 10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.

---

Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

#### Acute Toxicity

Product Information No information available

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Causes eye irritation Risk of serious damage to eyes May cause burns Severely irritating to eyes
Skin contact	Irritating to skin. Prolonged skin contact may cause skin irritation and/or dermatitis. May cause burns.
Inhalation	Harmful by inhalation. Causes respiratory tract irritation. Vapours may be irritating to eyes, nose, throat, and lungs. May cause additional affects as listed under "Ingestion".
Ingestion	Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Can burn mouth, throat, and stomach.
Sensitization	No information available.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	May cause disorder and damage to the. Respiratory system. Digestive System.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled. Causes damage to organs through prolonged or repeated exposure if swallowed. kidney.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	2999 mg/kg
ATEmix (dermal)	10554 mg/kg
ATEmix (inhalation-dust/mist)	10.6 mg/l

**Component Information**

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
2-Propoxyethanol 2807-30-9	= 3089 mg/kg ( Rat )	= 870 mg/kg ( Rabbit ) = 960 µL/kg ( Rabbit )	= 1530 ppm ( Rat ) 7 h
Dipropylene glycol monomethyl ether 34590-94-8	= 5.35 g/kg ( Rat )	= 9500 mg/kg ( Rabbit )	-
Carbon black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-

**Chronic Toxicity**

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical name	IARC	NTP
Titanium dioxide	2B - Possible Human Carcinogen	
Silica, crystalline	1 - Human Carcinogen	Known
Carbon black	2B - Possible Human Carcinogen	

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

**Legend**

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

**Product Information**

**Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available



**Persistence / Degradability**

No information available.

**Bioaccumulation**

There is no data for this product.

**Mobility in Environmental Media**

No information available.

**Ozone**

Not applicable

**Component Information**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**14. TRANSPORT INFORMATION**

**TDG** Not regulated

**ICAO / IATA** Not regulated

**IMDG / IMO** Not regulated

**15. REGULATORY INFORMATION**

---

### International Inventories

**TSCA: United States** Yes - All components are listed or exempt.  
**DSL: Canada** Yes - All components are listed or exempt.

### National Pollutant Release Inventory (NPRI)

#### **NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

None

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

None

### **WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

## 16. OTHER INFORMATION

### **HMIS**

<b>Health hazards</b>	1*
<b>Flammability</b>	0
<b>Reactivity:</b>	0
<b>Personal protection</b>	-

### **HMIS Legend**

0 - Minimal Hazard  
1 - Slight Hazard  
2 - Moderate Hazard  
3 - Serious Hazard  
4 - Severe Hazard  
\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself

---

and your family by logging onto Health Canada at  
[http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision Date:** 25-Aug-2023  
**Reason for revision** Not available

**Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**