



Benjamin Moore®

SAFETY DATA SHEET

Revision date 13-Jan-2026

Revision Number 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name HP ALKYD URETHANE ENAMEL SEMI-GLOSS - BLACK
Product Code CHP2210-80
Alternate Product Code UC2180
Product Class SOLVENT THINNED PAINT
Color Black
Recommended use Paint
Restrictions on use No information available

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.benjaminmoore.com

Emergency Telephone
CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

Label elements

Danger

Hazard statements

May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May damage fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure
Flammable liquid and vapor



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves
Do not breathe dust
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use only non-sparking tools
Take action to prevent static discharges

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Hazards not otherwise classified (HNOC)

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Talc	14807-96-6	10 - 15
Methyl acetate	79-20-9	5 - 10
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5
4-Chlorobenzotrifluoride	98-56-6	1 - 5
Carbon black	1333-86-4	0.5 - 1
1,3,5-Trimethylbenzene	108-67-8	0.5 - 1
Xylene	1330-20-7	0.1 - 0.5
Diethylbenzene	25340-17-4	0.1 - 0.5
Hexanoic acid, 2-ethyl-, zirconium salt	22464-99-9	0.1 - 0.5
Ethyl benzene	100-41-4	0.1 - 0.5
2-Butoxyethanol	111-76-2	0.1 - 0.5
Cobalt bis(2-ethylhexanoate)	136-52-7	0.1 - 0.5

4. FIRST AID MEASURES

Description of first aid measures

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties Vapors may travel considerable distance to a source of

ignition and flash back. Vapors may cause flash fire.

Suitable Extinguishing Media

Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Hazardous combustion products

Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.

Special Provisions

Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity to mechanical impact

No

Sensitivity to static discharge

Yes

Flash Point Data

Flash point (°F)	73
Flash Point (°C)	23
Method	PMCC

Flammability Limits In Air

Lower flammability limit:	No data available
Upper flammability limit:	No data available

NFPA

Health hazards	2
Flammability	3
Stability	0
Special:	Not Applicable

NFPA Legend

0 - Not Hazardous
1 - Slightly
2 - Moderate
3 - High
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.
Other Information	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling	<p>Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.</p> <p>Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.</p>
Storage	<p>Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.</p> <p>DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.</p>
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Technical measures/Precautions	<p>Ensure adequate ventilation. Use only where airflow will keep vapors from building up in or near the work area in adjoining rooms. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids.</p> <p>Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. All equipment should be non-sparking and explosion proof. Use explosion proof electrical equipment for ventilation, lighting and material handling.</p>

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Talc	TWA: 2 mg/m ³ respirable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit
Methyl acetate	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm TWA: 610 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m ³
1,2,4-Trimethylbenzene	TWA: 10 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³
4-Chlorobenzotrifluoride	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F (vacated) TWA: 2.5 mg/m ³
Carbon black	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³
1,3,5-Trimethylbenzene	TWA: 10 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³
Xylene	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³
Hexanoic acid, 2-ethyl-, zirconium salt	TWA: 5 mg/m ³ Zr STEL: 10 mg/m ³ Zr	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr
Ethyl benzene	TWA: 20 ppm pOt	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ dSk Sdv

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Appropriate engineering

controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles.

Skin Protection Long sleeved clothing. Protective gloves.

Respiratory Protection Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	solvent
Odor threshold	No information available
Density (lbs./gal)	11.8 - 12.2
Specific Gravity	1.41 - 1.47
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available
Wt. % Solids	75 - 85
Vol. % Solids	60 - 70
Wt. % Volatiles	15 - 25
Vol. % Volatiles	30 - 40
VOC Regulatory Limit (g/L)	< 250
Boiling Point (°F)	158
Boiling Point (°C)	70
Freezing point (°F)	No information available
Freezing Point (°C)	No information available
Flash point (°F)	73
Flash Point (°C)	23
Method	PMCC
Flammability	Not applicable
Upper flammability limit:	No data available
Lower flammability limit:	No data available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	No data available
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions to avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Contact with eyes may cause irritation.
Skin contact May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
Inhalation Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
Sensitization May cause an allergic skin reaction

Neurological effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	May damage fertility or the unborn child.
Developmental toxicity	No information available.
Target organ effects	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled.
STOT - single exposure	No information available.
Other adverse effects	No information available.

Aspiration Hazard May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	43826 mg/kg
ATEmix (inhalation-dust/mist)	68.6 mg/L
ATEmix (inhalation-vapor)	347.5 mg/L

Component Information Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Talc 14807-96-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Methyl acetate 79-20-9	= 6482 mg/kg (Rat)	> 5 g/kg (Rabbit)	49.2 - 98.4 mg/L (Rat) 4 h
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat) > 3492 mg/kg (Rat) = 6984 mg/kg (Rat) = 8970 mg/kg (Rat)	> 3440 mg/kg (Rat) > 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h > 6193 mg/m ³ (Rat) 4 h
4-Chlorobenzotrifluoride 98-56-6	= 13 g/kg (Rat)	> 3300 mg/kg (Rabbit)	> 32.03 mg/L (Rat) 4 h
Carbon black 1333-86-4	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m ³ (Rat) 4 h
1,3,5-Trimethylbenzene 108-67-8	> 3492 mg/kg (Rat) = 6984 mg/kg (Rat) = 8970 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 24 g/m ³ (Rat) 4 h > 6193 mg/m ³ (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h > 5.04 mg/L (Rat) 4 h
Diethylbenzene 25340-17-4	= 2050 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 2100 ppm (Rat) 7 h
Ethyl benzene 100-41-4	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)	= 15400 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h > 5.04 mg/L (Rat) 4 h

2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Cobalt bis(2-ethylhexanoate) 136-52-7	= 3129 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 10 mg/L (Rat) 1 h

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical name	IARC	NTP	OSHA
Talc			X
4-Chlorobenzotrifluoride	Group 2B - Possibly carcinogenic to humans		X
Carbon black	Group 2B - Possibly carcinogenic to humans		X
Xylene	Group 3 - Unclassifiable as to carcinogenicity in humans		
Ethyl benzene	Group 2B - Possibly carcinogenic to humans		X
2-Butoxyethanol	Group 3 - Unclassifiable as to carcinogenicity in humans		
Cobalt bis(2-ethylhexanoate)	Group 2B - Possibly carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	X

• Cobalt and cobalt compounds are listed as possible human carcinogens by IARC (2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence and degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility

No information available.

Hazardous to the ozone layer

Not classified

Component Information

Acute Toxicity to Fish

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.


Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

Xylene	1330-20-7	0.1 - 0.5	Listed
Ethyl benzene	100-41-4	0.1 - 0.5	Listed
2-Butoxyethanol	111-76-2	0.1 - 0.5	Listed
Cobalt bis(2-ethylhexanoate)	136-52-7	0.1 - 0.5	Listed

US State Regulations

California Proposition 65

 **WARNING:** This product can expose you to chemicals including Crystalline Silica, which are known to the State of California to cause cancer, and Toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

U.S. State Right-to-Know Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania
Limestone	X	X	X
Talc	X	X	X
Methyl acetate	X	X	X
1,2,4-Trimethylbenzene	X	X	X
4-Chlorobenzotrifluoride		X	
Carbon black	X	X	X
Ethyl benzene	X	X	X
2-Butoxyethanol	X	X	X
Cobalt bis(2-ethylhexanoate)		X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS

Health hazards	2*
Flammability	3
Reactivity:	0
Personal protection	-

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or

risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision date 13-Jan-2026
Revision Note Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet