



Benjamin Moore®

SAFETY DATA SHEET

Revision Date: 23-Feb-2024

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name HP ALKYD URETHANE ENAMEL SATIN - BRONZETONE
Product Code HP2220-62FR
Alternate Product Code UF6262
Product Class SOLVENT THINNED PAINT
Color Bronze
Recommended use Paint
Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
www.benjaminmoore.com/en-ca

Manufacturer

Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.benjaminmoore.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)
CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Physical hazard not otherwise classified	Category 1

Label elements

Danger

Hazard statements

May cause an allergic skin reaction

May cause genetic defects
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Risk of spontaneous combustion



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Immediately after use, place rags, steel wool or waste used with this product in a sealed water-filled metal container or lay flat to dry.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Nepheline syenite	37244-96-5	10 - 30%	-	-
Distillates, petroleum, hydrotreated light	64742-47-8	10 - 30%	-	-
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	5 - 10%	-	-
Talc	14807-96-6	1 - 5%	-	-
Zinc phosphate	7779-90-0	1 - 5%	-	-
Magnesium carbonate	546-93-0	1 - 5%	-	-
Titanium dioxide	13463-67-7	1 - 5%	-	-
Iron oxide	1309-37-1	1 - 5%	-	-
Zinc oxide	1314-13-2	1 - 5%	-	-
Carbon black	1333-86-4	1 - 5%	-	-
Methyl ethyl ketoxime	96-29-7	0.1 - 0.25%	-	-
Ethyl benzene	100-41-4	0.1 - 0.25%	-	-

Confidential Business Information note

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.

Inhalation

Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

Protection Of First-Aiders

Use personal protective equipment.

Most Important Symptoms/Effects

May cause allergic skin reaction.

Notes To Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical

Combustible material. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity to mechanical impact

No

Sensitivity to static discharge

Yes

Flash Point Data

Flash point (°F)

105

Flash Point (°C)

137

Method

PMCC

Flammability Limits In Air

Lower flammability limit:

No data available

Upper flammability limit:

No data available

NFPA

Health hazards

2

Flammability

2

Stability

0

Special:

Not Applicable

NFPA Legend

0 - Not Hazardous

1 - Slightly

2 - Moderate

3 - High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment. Remove all sources of ignition.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions

See Section 12 for additional Ecological Information.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Nepheline syenite	-	-	-	10 mg/m ³ - TWA	-
Talc	TWA: 2 mg/m ³ particulate matter	2 mg/m ³ - TWA	2 mg/m ³ - TWA	2 mg/m ³ - TWA	2 mg/m ³ - TWA EV

	containing no asbestos and <1% crystalline silica, respirable particulate matter				
Magnesium carbonate	-	-	10 mg/m ³ - TWA 3 mg/m ³ - TWA	-	10 mg/m ³ - TWAEV
Titanium dioxide	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	10 mg/m ³ - TWA	10 mg/m ³ - TWA 3 mg/m ³ - TWA	10 mg/m ³ - TWA	10 mg/m ³ - TWAEV
Iron oxide	TWA: 5 mg/m ³ respirable particulate matter	5 mg/m ³ - TWA	10 mg/m ³ - TWA 3 mg/m ³ - TWA 5 mg/m ³ - TWA 10 mg/m ³ - STEL	5 mg/m ³ - TWA	5 mg/m ³ - TWAEV 10 mg/m ³ - TWAEV
Zinc oxide	STEL: 10 mg/m ³ respirable particulate matter TWA: 2 mg/m ³ respirable particulate matter TWA: 0.5 mg/m ³ Ba As Barium soluble compounds [RR-00049-7]	2 mg/m ³ - TWA 10 mg/m ³ - STEL	2 mg/m ³ - TWA 10 mg/m ³ - STEL	2 mg/m ³ - TWA 10 mg/m ³ - STEL	10 mg/m ³ - TWAEV 5 mg/m ³ - TWAEV 10 mg/m ³ - STEV
Carbon black	TWA: 3 mg/m ³ inhalable particulate matter	3.5 mg/m ³ - TWA	3 mg/m ³ - TWA	3 mg/m ³ - TWA	3.5 mg/m ³ - TWAEV
Ethyl benzene	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	100 ppm - TWA 434 mg/m ³ - TWA 125 ppm - STEL 543 mg/m ³ - STEL	20 ppm - TWA	20 ppm - TWA	100 ppm - TWAEV 434 mg/m ³ - TWAEV 125 ppm - STEV 543 mg/m ³ - STEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
Alberta - Alberta Occupational Exposure Limits
British Columbia - British Columbia Occupational Exposure Limits
Ontario - Ontario Occupational Exposure Limits
Quebec - Quebec Occupational Exposure Limits
N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields If splashes are likely to occur, wear: Tightly fitting safety goggles
Long sleeved clothing. Protective gloves.

Skin Protection

Respiratory Protection

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	solvent
Odor Threshold	No information available
Density (lbs./gal)	10.3 - 10.8
Specific Gravity	1.23 - 1.30
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available
Wt. % Solids	65 - 75
Vol. % Solids	45 - 55
Wt. % Volatiles	25 - 35
Vol. % Volatiles	45 - 55
VOC Regulatory Limit (g/L)	< 400
Boiling Point (°F)	279
Boiling Point (°C)	137
Freezing point (°F)	No information available
Freezing Point (°C)	No information available
Flash point (°F)	105
Flash Point (°C)	137
Method	PMCC
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions to avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.

Possibility of hazardous reactions

None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure

Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Contact with eyes may cause irritation.

Skin contact

May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.

Inhalation

High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

Ingestion

Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. May cause an allergic skin reaction.

Sensitization

No information available.

Neurological Effects

No information available.

Mutagenic Effects

No information available.

Reproductive Effects

No information available.

Developmental Effects

No information available.

Target organ effects

No information available.

STOT - single exposure

May cause disorder and damage to the. Central nervous system. Respiratory system.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.

Other adverse effects

No information available.

Aspiration Hazard

May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

14460 mg/kg

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates, petroleum, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Iron oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Methyl ethyl ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
Ethyl benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen.:

Chemical name	IARC	NTP
Titanium dioxide	2B - Possible Human Carcinogen	
Carbon black	2B - Possible Human Carcinogen	
Ethyl benzene	2B - Possible Human Carcinogen	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Methyl ethyl ketoxime

LC50: 48 mg/L (Bluegill sunfish - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Methyl ethyl ketoxime

EC50: 750 mg/L (Daphnia magna - 48 hr.)

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

TDG

Proper Shipping Name Paint
Transport hazard class(es) 3
UN-No UN1263
Packing Group III
Description UN1263, Paint, 3, III

In Canada, Class 3 flammable liquids may be reclassified as non-regulated for domestic ground transportation if they meet the requirements of TDG General Exemption SOR/2008-34.

ICAO / IATA Contact the preparer for further information.

IMDG / IMO Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>NPRI Parts 1- 4</u>
Ethyl benzene	100-41-4	0.1 - 0.25%	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>NPRI Part 5</u>
Distillates, petroleum, hydrotreated light	64742-47-8	10 - 30%	Listed

Solvent naphtha, petroleum, medium
aliphatic

64742-88-7

5 - 10%

Listed

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

16. OTHER INFORMATION

HMIS

Health hazards	2*
Flammability	2
Reactivity:	0
Personal protection	-

HMIS Legend

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 23-Feb-2024
Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet