



Benjamin Moore®

SAFETY DATA SHEET

Revision Date: 22-Mar-2023

Revision Number: 8

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ULTRA SPEC HP D.T.M ACRYLIC SEMI-GLOSS ENAMEL
BRONZETONE
Product Code HP2964
Alternate Product Code HP2964, HP2999
SAP Material Number N/A, 3001250
Product Class Water thinned paint
Color Orange
Recommended use Industrial paint
Restrictions on use No information available

Manufacturer
 Benjamin Moore & Co.
 101 Paragon Drive
 Montvale, NJ 07645
 Phone: 1-866-708-9180
 www.benjaminmoore.com

Emergency Telephone
 CHEMTREC: +1 703-741-5970 / 1-800-424-9300
 +1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|-----------------------|------------|
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 2 |

Label elements

Warning

Hazard statements

Suspected of causing cancer
 Suspected of damaging fertility or the unborn child



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No | Weight-% |
|-----------------------------------------------|------------|-----------|
| 2,2,4-trimethyl-1,3-pentanediol diisobutyrate | 6846-50-0 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Kaolin | 1332-58-7 | 1 - 5 |
| Zinc phosphate | 7779-90-0 | 1 - 5 |
| Iron oxide | 1309-37-1 | 1 - 5 |
| Carbon black | 1333-86-4 | 0.5 - 1 |
| Ammonium hydroxide | 1336-21-6 | 0.1 - 0.5 |

4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Move to fresh air. If symptoms persist, call a physician.

| | |
|----------------------------------------|------------------------------------------------------------------------------------------------|
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | None known. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| | |
|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective equipment and precautions for firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity to mechanical impact | No |
| Sensitivity to static discharge | No |
| Flash Point Data | |
| Flash point (°F) | 250 |
| Flash Point (°C) | 121 |
| Method | PMCC |
| Flammability Limits In Air | |
| Lower flammability limit: | Not applicable |
| Upper flammability limit: | Not applicable |
| NFPA | |
| Health hazards | 2 |
| Flammability | 1 |
| Stability | 0 |
| Special: | Not Applicable |

NFPA Legend

0 - Not Hazardous
1 - Slightly
2 - Moderate
3 - High
4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
- Other Information** Prevent further leakage or spillage if safe to do so.
- Environmental precautions** See Section 12 for additional Ecological Information.
- Methods for Cleaning Up** Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

- Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
- Storage** Keep container tightly closed. Keep out of the reach of children.
- Incompatible Materials** No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Titanium dioxide | TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter | 15 mg/m ³ - TWA |
| Kaolin | TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter | 15 mg/m ³ - TWA 5 mg/m ³ - TWA |
| Iron oxide | TWA: 5 mg/m ³ respirable particulate matter | 10 mg/m ³ - TWA 15 mg/m ³ - TWA Rouge 5 mg/m ³ - TWA Rouge |
| Carbon black | TWA: 3 mg/m ³ inhalable particulate matter | 3.5 mg/m ³ - TWA |
| Ammonium hydroxide | STEL: 35 ppm TWA: 25 ppm | - |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits
OSHA - Occupational Safety & Health Administration Exposure Limits
N/E - Not Established

- Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

- Eye/Face Protection** Safety glasses with side-shields.
- Skin Protection** Protective gloves and impervious clothing.
- Respiratory Protection** In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a

NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|--------------------------|
| Appearance | liquid |
| Odor | little or no odor |
| Odor Threshold | No information available |
| Density (lbs./gal) | 9.35 - 9.45 |
| Specific Gravity | 1.10 - 1.12 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility(ies) | No information available |
| Water solubility | No information available |
| Evaporation Rate | No information available |
| Vapor pressure @20 °C (kPa) | No information available |
| Relative vapor density | No information available |
| Wt. % Solids | 40 - 50 |
| Vol. % Solids | 35 - 45 |
| Wt. % Volatiles | 50 - 60 |
| Vol. % Volatiles | 55 - 65 |
| VOC Regulatory Limit (g/L) | < 150 |
| Boiling Point (°F) | 212 |
| Boiling Point (°C) | 100 |
| Freezing point (°F) | 32 |
| Freezing Point (°C) | 0 |
| Flash point (°F) | 250 |
| Flash Point (°C) | 121 |
| Method | PMCC |
| Flammability (solid, gas) | Not applicable |
| Upper flammability limit: | Not applicable |
| Lower flammability limit: | Not applicable |
| Autoignition Temperature (°F) | No information available |
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient | No information available |

10. STABILITY AND REACTIVITY

| | |
|----------------------------------|------------------------------------------|
| Reactivity | Not Applicable |
| Chemical Stability | Stable under normal conditions. |
| Conditions to avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |

Possibility of hazardous reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|---------------------------------|--------------------------------------------------------------------------------------------------------------|
| Eye contact | May cause slight irritation. |
| Skin contact | Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. |
| Inhalation | May cause irritation of respiratory tract. |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Sensitization | No information available |
| Neurological Effects | No information available. |
| Mutagenic Effects | No information available. |
| Reproductive Effects | Possible risk of impaired fertility. Possible risk of harm to the unborn child. |
| Developmental Effects | No information available. |
| Target organ effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 41309 mg/kg

Component Information Caution - This mixture contains a substance not yet fully tested

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|------------------------------------------------------------|-----------------------|----------------------|------------------------|
| 2,2,4-trimethyl-1,3-pentanediol diisobutyrate 6846-50-0 | > 3200 mg/kg (Rat) | - | > 5.3 mg/L (Rat) 6 h |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Kaolin 1332-58-7 | > 5000 mg/kg (Rat) | > 5000 mg/kg (Rat) | - |
| Zinc phosphate 7779-90-0 | > 5000 mg/kg (Rat) | - | - |
| Iron oxide 1309-37-1 | > 10000 mg/kg (Rat) | - | - |

| | | | |
|---------------------------------|-----------------------|---------------------|---|
| Carbon black 1333-86-4 | > 15400 mg/kg (Rat) | > 3 g/kg (Rabbit) | - |
| Ammonium hydroxide 1336-21-6 | = 350 mg/kg (Rat) | - | - |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen..

| Chemical name | IARC | NTP | OSHA |
|------------------|--------------------------------|-----|--------|
| Titanium dioxide | 2B - Possible Human Carcinogen | | Listed |
| Carbon black | 2B - Possible Human Carcinogen | | Listed |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Not regulated

ICAO / IATA

Not regulated

IMDG / IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States

Yes - All components are listed or exempt.

DSL: Canada

Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | No |
| Chronic Health Hazard | Yes |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| <u>Chemical name</u> | <u>CAS No</u> | <u>Weight-%</u> | <u>CERCLA/SARA 313 (de minimis concentration)</u> |
|----------------------|---------------|-----------------|-------------------------------------------------------|
| Zinc phosphate | 7779-90-0 | 1 - 5 | 1.0 |


Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

 **WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

U.S. State Right-to-Know Regulations

| <u>Chemical name</u> | <u>Massachusetts</u> | <u>New Jersey</u> | <u>Pennsylvania</u> |
|----------------------|----------------------|-------------------|---------------------|
| Titanium dioxide | X | X | X |
| Kaolin | X | X | X |
| Zinc phosphate | | X | X |
| Iron oxide | X | X | X |
| Carbon black | X | X | X |

Legend

X - Listed

16. OTHER INFORMATION

HMIS

| | |
|----------------------------|----|
| Health hazards | 2* |
| Flammability | 1 |
| Reactivity: | 0 |
| Personal protection | - |

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Issuing Date 07-Aug-2021

Revision Date: 22-Mar-2023

Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet